Electrolux PROFESSIONAL

Modular Cooking Range Line 700XP 4-Hot Plates Electric Boiling Top Range on Electric Oven



Short Form Specification

Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. Four 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed oven base plate. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

ITEM #

SIS #

AIA #

<u>MODEL #</u> NAME #

- The four round 2.6kW cast-iron plates are hermtically sealed to the one-piece top.
- Base compartment consists of an electric standard oven with thick oven door for heat insulation, positioned beneath the base plate.
- Electric oven to have separate thermostats for top and bottom heating elements.
- Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans).
- Ribbed enamelled steel oven base plate.
- The special design of the control knob system guarantees against water infiltration.
- IPX 4 water protection.
- Oven thermostat adjustable from 100 °C to 300 °C.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

• 1 of GN2/1 chrome grid for static PNC 164250 oven

Optional Accessories

- GN2/1 chrome grid for static oven PNC 164250 🛛
- Junction sealing kit PNC 206086 🗅
- 4 wheels, 2 swivelling with brake PNC 206135 □ (700/900XP). It is mandatory to install with base supports for feet/wheels.
- Flanged feet kit PNC 206136 🛛
- Frontal kicking strip for concrete PNC 206148 installation, 800mm
- Frontal kicking strip for concrete PNC 206150 installation, 1000mm
- Frontal kicking strip for concrete PNC 206151 installation, 1200mm
- Frontal kicking strip for concrete PNC 206152 🗅 installation, 1600mm
- Frontal kicking strip, 800mm (not PNC 206176 for refr-freezer base)
- Frontal kicking strip, 1000mm (not PNC 206177 for refr-freezer base)
- Frontal kicking strip, 1200mm (not PNC 206178 for refr-freezer base)
- Frontal kicking strip, 1600mm (not PNC 206179 for refr-freezer base)

APPROVAL:





PNC 206209	
PNC 206210	
PNC 206249	
PNC 206265	
PNC 206289	
PNC 206291	
PNC 206304	
PNC 206307	
PNC 206308	
PNC 206367	
PNC 206368	
PNC 206369	
PNC 206370	
PNC 206374	
PNC 206375	
PNC 206376	
PNC 206400	
PNC 216000	
PNC 216047	
PNC 216049	
PNC 216050	
PNC 216186	
PNC 921695	
	PNC 206210 PNC 206249 PNC 206265 PNC 206289 PNC 206304 PNC 206307 PNC 206307 PNC 206308 PNC 206367 PNC 206367 PNC 206370 PNC 206370 PNC 206376 PNC 206375 PNC 206375 PNC 206375 PNC 206376 PNC 206400 PNC 216000 PNC 216047 PNC 216049 PNC 216050 PNC 216186



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Electrolux PROFESSIONAL



El = Electrical inlet (power) EQ = Equipotential screw



Тор



Modular Cooking Range Line 700XP 4-Hot Plates Electric Boiling Top Range on Electric Oven

Electric

Supply voltage:	
371016 (E7ECEH4REO)	380-400 V/3 ph/50-60 Hz
371128 (E7ECEH4REN)	230 V/3 ph/50/60 Hz
Predisposed for:	
Total Watts:	16.4 kW

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Oven working Temperature:	100 °C MIN; 300 °C MAX
Oven Cavity Dimensions	E / O
(width):	540 mm
Oven Cavity Dimensions (height):	300 mm
Oven Cavity Dimensions	
(depth):	650 mm
External dimensions, Width:	800 mm
External dimensions, Depth:	730 mm
External dimensions, Height:	850 mm
Net weight:	80 kg
Shipping weight:	95 kg
Shipping height:	
371016 (E7ECEH4REO)	1080 mm
371128 (E7ECEH4REN)	1140 mm
Shipping width:	820 mm
Shipping depth:	860 mm
Shipping volume:	
371016 (E7ECEH4REO)	0.76 m³
371128 (E7ECEH4REN)	0.8 m³
Certification group:	
371016 (E7ECEH4REO)	EH74O
371128 (E7ECEH4REN)	N7CE1
Front Plates Power:	2.6 - 2.6 kW
Back Plates Power:	2.6 - 2.6 kW
Front Plates dimensions:	Ø 230 Ø 230
Back Plates dimensions:	Ø 230 Ø 230

Modular Cooking Range Line 700XP 4-Hot Plates Electric Boiling Top Range on Electric Oven

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.