

Modular Cooking Range Line 700XP 4-Hot Plates Electric Boiling Top Range

ITEM # _____
 MODEL # _____
 NAME # _____
 SIS # _____
 AIA # _____



371015 (E7ECEH4R00) 4-hot plate (2,6 kW each)
electric boiling top

371127 (E7ECEH4R0N) 4-hot plate (2,6 kW each)
electric boiling top

Short Form Specification

Item No. _____

To be installed on open base installations, bridging supports or cantilever systems. Four 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The four 2.6kW cast-iron plates are hermetically sealed to the one-piece top.
- The special design of the control knob system guarantees against water infiltration.
- IPX 4 water protection.
- Suitable for countertop installation.


Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Optional Accessories

- Junction sealing kit PNC 206086 ☐
- Support for bridge type system, 800mm PNC 206137 ☐
- Support for bridge type system, 1000mm PNC 206138 ☐
- Support for bridge type system, 1200mm PNC 206139 ☐
- Support for bridge type system, 1400mm PNC 206140 ☐
- Support for bridge type system, 1600mm PNC 206141 ☐
- Water coulmun with swivel arm (water column extension not included) PNC 206289 ☐
- Water column extension for 700 line PNC 206291 ☐
- Chimney upstand, 800mm PNC 206304 ☐
- Right and left side handrails PNC 206307 ☐
- BACK HANDRAIL 800 MM - MARINE PNC 206308 ☐
- Chimney grid net, 400mm PNC 206400 ☐
- Frontal handrail 800mm PNC 216047 ☐
- Frontal handrail 1200mm PNC 216049 ☐
- Frontal handrail 1600mm PNC 216050 ☐
- Large handrail - portioning shelf, 800mm PNC 216186 ☐
- 2 side covering panels for top appliances PNC 216277 ☐
- Basket for 7lt fryers (only for 371015) PNC 921608 ☐

APPROVAL: _____



Electric

Supply voltage:

371015 (E7ECEH4R00)	380-400 V/3 ph/50-60 Hz
371127 (E7ECEH4R0N)	230 V/3 ph/50/60 Hz

Predisposed for:

Total Watts:	10.4 kW
--------------	---------

Key Information:

External dimensions, Width: 800 mm

External dimensions, Depth: 730 mm

External dimensions, Height: 250 mm

Net weight: 40 kg

Shipping weight:

371015 (E7ECEH4R00)	39 kg
371127 (E7ECEH4R0N)	40 kg

Shipping height:

371015 (E7ECEH4R00)	520 mm
371127 (E7ECEH4R0N)	540 mm

Shipping width: 820 mm

Shipping depth: 860 mm

Shipping volume:

371015 (E7ECEH4R00)	0.37 m ³
371127 (E7ECEH4R0N)	0.38 m ³

Certification group:

371015 (E7ECEH4R00)	EH74T
371127 (E7ECEH4R0N)	N7CE1

Front Plates Power:

2.6 - 2.6 kW

Back Plates Power:

2.6 - 2.6 kW

Front Plates dimensions:

Ø 230 Ø 230

Back Plates dimensions:

Ø 230 Ø 230

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.