



Modular Cooking Range Line 900XP 2-Hot Plates Electric Boiling Top

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



391039 (E9ECED2Q00)

2-hot square plates (4 kW each) electric boiling top

391165 (E9ECED2Q0N)

2-hot plate (4 kW each) electric boiling top

Short Form Specification

Item No. _____

To be installed on open base installations, bridging supports or cantilever systems. Two 4 kW square cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels of unit in stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The two 4kW cast-iron plates are hermetically sealed to the one-piece top. Hot plates with a power of 4kW for each plate.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Top configuration allows installation on ambient base only (not possible to install on refrigerated nor freezer base).
- Suitable for countertop installation.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

APPROVAL: _____




Experience the Excellence
www.electroluxprofessional.com


Optional Accessories

• Pair of cast iron plate bars for electric cooking top	PNC 206056	☐
• Junction sealing kit	PNC 206086	☐
• Support for bridge type system, 800mm	PNC 206137	☐
• Support for bridge type system, 1000mm	PNC 206138	☐
• Support for bridge type system, 1200mm	PNC 206139	☐
• Support for bridge type system, 1400mm	PNC 206140	☐
• Support for bridge type system, 1600mm	PNC 206141	☐
• Support for bridge type system, 400mm	PNC 206154	☐
• Water coulumn with swivel arm (water column extension not included)	PNC 206289	☐
• Water column extension for 900 line	PNC 206290	☐
• Chimney upstand, 400mm	PNC 206303	☐
• BACK HANDRAIL 800 MM - MARINE	PNC 206308	☐
• BACK HANDRAIL 1200 MM - MARINE	PNC 206309	☐
• Chimney grid net, 400mm	PNC 206400	☐
• Side handrail-right/left hand	PNC 216044	☐
• Frontal handrail 400mm	PNC 216046	☐
• Frontal handrail 800mm	PNC 216047	☐
• Frontal handrail 1200mm	PNC 216049	☐
• Frontal handrail 1600mm	PNC 216050	☐
• Large handrail - portioning shelf, 400mm	PNC 216185	☐
• Large handrail - portioning shelf, 800mm	PNC 216186	☐
• 2 side covering panels for top, d=900mm	PNC 216278	☐
• 1x1/1GN basket for 40lt pasta cookers (only for 391039)	PNC 927216	☐
• Upper support frame to hold 6 round baskets for 40lt pasta cookers (alternative to 927219 for 6 round baskets) (only for 391165)	PNC 960644	☐

Front




Side



EI = Electrical inlet (power)
 EQ = Equipotential screw

Top



Electric

Supply voltage:

391039 (E9ECED2Q00)

380-400 V/3N ph/50-60 Hz

391165 (E9ECED2Q0N)

230 V/3 ph/50/60 Hz

Predisposed for:

Total Watts:

8 kW

Key Information:

External dimensions, Width: 400 mm

External dimensions, Depth: 930 mm

External dimensions, Height: 250 mm

Net weight: 35 kg

Shipping weight: 43 kg

Shipping height:

391039 (E9ECED2Q00) 520 mm

391165 (E9ECED2Q0N) 540 mm

Shipping width:

460 mm

Shipping depth:

1020 mm

Shipping volume:

391039 (E9ECED2Q00) 0.24 m³

391165 (E9ECED2Q0N) 0.25 m³

Certification group:

391039 (E9ECED2Q00) EH927

391165 (E9ECED2Q0N) N9CEI

Front Plates Power:

4 - 0 kW

Back Plates Power:

4 - kW

Front Plates dimensions:

300x300

Back Plates dimensions:

300x300

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.