

# Modular Cooking Range Line 900XP 4-Burner Gas Range 10 kW on Gas Oven

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



391006 (E9GCGH4CGM)

4-burner (10 kW each) gas range on gas oven (8,5 kW)

## **Short Form Specification**

#### Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. High efficiency flower flame burners with continuous power regulation and optimized combustion. Flame failure device as standard on burners to protect against accidental extinguishing. Oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed, cast-iron oven base plate. Exterior panels of unit in stainless steel with Scotch Brite finish. Pan supports in heavy duty cast iron. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

#### Main Features

- Unit to be mounted on stainless steel feet with height adjustment up to 50 mm. Unit can be easily mounted on cantilever systems.
- Four 10 kW high efficiency burners are equipped with continuous power regulation from 2.2 kW to 10 kW.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Burners with optimized combustion.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Protected pilot light.
- Base compartment consists of a gas heated standard oven with stainless steel burners and self stabilizing flame positioned beneath the base plate. Oven chamber to have 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans) and ribbed cast iron base plate.
- 40 mm thick oven door for heat insulation.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Control knobs provide smooth, continuous rotation from min to max power level.

### Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

#### Sustainability

• [NOTTRANSLATED]



#### **Included Accessories**

 1 of GN2/1 chrome grid for PNC 164250 static oven

## **Optional Accessories**

• GN2/1 chrome grid for static PNC 164250 ☐ oven

Junction sealing kit PNC 206086 □
 Draught diverter with 150mm diameter

#### APPROVAL:






# Modular Cooking Range Line 900XP 4-Burner Gas Range 10 kW on Gas Oven


	Matching ring for flue condenser	PNC 206133		• Rear paneling - 1200mm (700/900)	PNC 206376	[
•	4 wheels, 2 swivelling with brake (700/900XP). It is mandatory to	PNC 206135		<ul> <li>Kit town gas nozzles (G150) for 900 gas ranges on gas oven</li> </ul>	PNC 206385	L
	install with base supports for feet/			• Chimney grid net, 400mm	PNC 206400	Į
	wheels.			• - NOTTRANSLATED -	PNC 206458	Į
	Flanged feet kit	PNC 206136		<ul> <li>Side handrail-right/left hand</li> </ul>	PNC 216044	Į
•	Frontal kicking strip for concrete	PNC 206148		<ul> <li>Frontal handrail 800mm</li> </ul>	PNC 216047	Į
	installation, 800mm	DNIC 204150		<ul> <li>Frontal handrail 1200mm</li> </ul>	PNC 216049	Į
•	Frontal kicking strip for concrete installation, 1000mm	PNC 206150		<ul> <li>Frontal handrail 1600mm</li> </ul>	PNC 216050	Į
•	Frontal kicking strip for concrete installation, 1200mm	PNC 206151		<ul> <li>2 side covering panels for free standing appliances</li> </ul>	PNC 216134	[
•	Frontal kicking strip for concrete installation, 1600mm	PNC 206152		• Large handrail - portioning shelf, 400mm	PNC 216185	[
•	2 SIDE KICKING STRIPS- CONCRETE INST-900	PNC 206157		Large handrail - portioning shelf, 800mm	PNC 216186	Į
•	Single burner smooth plate	PNC 206171		<ul> <li>2 half size baskets for 18/23lt well fryers</li> </ul>	PNC 927223	Ļ
•	Single burner ribbed plate	PNC 206172		<ul> <li>Pressure regulator for gas units</li> </ul>	PNC 927225	Г
	refr-freezer base)	PNC 206176		- Tressore regulator for gas office	1110 727220	•
	Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177				
	Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178				
	Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179	_			
	Pair of side kicking strips (not for refr-freezer base)	PNC 206180	_			
	2 panels for service duct for single installation	PNC 206181				
	2 panels for service duct for back to back installation					
	4 feet for concrete installation	PNC 206210				
•	Flue condenser for 1 module, 150 mm diameter	PNC 206246				
•	Water coulumn with swivel arm (water column extension not included)	PNC 206289				
•	Water column extension for 900 line	PNC 206290				
•	Stainless steel double grid for 2 burners	PNC 206298				
•	Chimney upstand, 800mm	PNC 206304				
	BACK HANDRAIL 800 MM - MARINE	PNC 206308				
•	BACK HANDRAIL 1200 MM - MARINE	PNC 206309				
•	Wok pan support for open burners (700/900)	PNC 206363				
	Base support for feet or wheels - 800mm (700/900)	PNC 206367				
	Base support for feet or wheels - 1200mm (700/900)	PNC 206368				
	Base support for feet or wheels - 1600mm (700/900)	PNC 206369				
	Base support for feet or wheels - 2000mm (700/900)	PNC 206370				
	Rear paneling - 800mm (700/900)	PNC 206374				
•	Rear paneling - 1000mm (700/900)	PNC 206375				






# Modular Cooking Range Line 900XP 4-Burner Gas Range 10 kW on Gas Oven





Gas connection



**C** € 5%

Gas

Gas Power: 48.5 kW

Natural Gas G20 (20mbar) Standard gas delivery:

Gas Type Option: LPG; Natural Gas

Gas Inlet: 1/2"

## **Key Information:**

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat

insulation fitted.

120 °C MIN; 270 °C MAX Oven working Temperature:

**Oven Cavity Dimensions** 

(width): 575 mm

**Oven Cavity Dimensions** (height):

300 mm

**Oven Cavity Dimensions** 

(depth): 700 mm External dimensions, Width: 800 mm External dimensions, Depth: 930 mm External dimensions, Height: 850 mm Net weight: 155 kg Shipping weight: 137 kg

Shipping height: 1080 mm 1020 mm Shipping width: Shipping depth: 860 mm 0.95 m<sup>3</sup> Shipping volume:

ISO 9001; ISO 14001 - ISO

Front Burners Power: 9001; ISO 14001 kW

**Back Burners Power:** 10 - 10 kW Certification group: N9CG

**Back Burners Dimension -**

Ø 100 Ø 100


Front Burners Dimension -

Note:

Ø 100 Ø 100 mm

> EcoFlame model available to save up to 20% on gas

>>> 391642



Modular Cooking Range Line 900XP 4-Burner Gas Range 10 kW on Gas Oven

