



Modular Cooking Range Line 900XP Gas Cylindrical Boiling Pan 100lt indirect heat



391100 (E9BSGHIPFO)

100-lt gas boiling pan with pressure switch, indirect heating

Short Form Specification

Item No.

Suitable for natural gas or LPG. To be installed on cantilever systems but also incorporates fixing points for bridging. Robust burners in stainless steel with flame failure device and protected pilot light. Exterior panels panels of unit in stainless steel with Scotch Brite finish. Double jacketed lid made in 2mm thick AISI 316 stainless steel. Pressed well with rounded edges manufactured from AISI 316 stainless steel. Right-angled side edges to allow flush-fitting junction between units. Includes safety valve to control working pressure. Temperature limiter for power regulation allowing precise temperature cooking.

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____

Main Features

- Round kettle is suitable to cook, sauté or poach all kinds of produce.
- Produce is uniformly heated in the base and side walls of the kettle by an indirect heating system that uses integrally generated saturated steam at a temperature of 110° C in the jacket.
- External valve allows to manually evacuate excess air accumulated in the jacket during heating phase.
- Appliance is IPX5 water resistance certified.
- Manometer allows to correctly control the functioning of the pan.
- Energy regulation through a control knob.
- Safety thermostat protects against low water level.
- Safety valve avoids overpressure of the steam in the jacket.
- No overshooting of cooking temperatures, fast reaction.
- Large capacity food tap enables safe and effortless discharging of contents.
- Ergonomic: the depth of the vessel facilitates stirring the food, also the most delicate food.
- Discharge tube and tap are very easy to clean from outside.
- Solenoid valve to refill with hot and cold water.
- Smooth large surfaces, easy access for cleaning.
- The special design of the control knob system guarantees against water infiltration.
- Minimum load for correct functioning is 20 liters.

Construction

- Pressed cooking vessel in 316L AISI Stainless steel.
- Robust burners in stainless steel with flame failure device, protected pilot light and optimized combustion.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Usable capacity of the well 85 liters.

Sustainability

- Kettle shall be double jacketed including high quality thermal insulation of the pan, saving energy and keeping ambient temperature low.
- Firmly fitting cover to reduce cooking time and save energy costs.
- Closed heating system – no waste of energy.
- Pressure switch control monitors energy and water consumption.



Included Accessories



- 1 of Water additive against corrosion for indirect boiling pans PNC 927222

Optional Accessories

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com


Front

Side

CWI = Cold Water inlet 1 (cleaning)

D = Drain

EI = Electrical inlet (power)

G = Gas connection

HWI = Hot water inlet

Top

Electric
Supply voltage: 220-230 V/1 ph/50 Hz

Total Watts: 0.1 kW

Gas
Gas Power: 21 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG;Natural Gas

Gas Inlet: 1/2"

Key Information:

No clearance needed on rear sides of unit if wall is of non combustible type. If wall is combustible, minimum 50 mm wall clearance should be maintained.

Pan useful capacity: 98 lt

Vessel (round) diameter: 600 mm

Net weight: 135 kg

Shipping weight: 132 kg

Shipping height: 1210 mm

Shipping width: 1110 mm

Shipping depth: 860 mm

Shipping volume: 1.16 m³
Certification group: N9PIG