

Plug In SpeeDelight with adjustable tube, ribbed, removable teflon plate

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



603946 (HSG2RPRSE3)

SpeeDelight with manual adjustable top plate, removable ribbed teflon plate

Main Features

- It combines 3 cooking technologies: contact, infrared radiation and microwaves to provide perfectly cooked food, heated to the core.
- Manually adjustable upper plate to heat food up to a minimum height.
- The Energy Saving Mode automatically switches to stand-by after an amount of time settled by the operator (from 1 to 60 minutes).
- Delivered with USB port and wi-fi connection to optimize workflows allowing local and remote inteaction (temperatures, countdowns, warnings).
- Electronic control with digital 4.3" LED display with adjustable brightness.
- 8 programs selectable on the display.
 The 8 programs can be adjusted by the user. The programmable parameters are:
 - -top plate temperature
 - -bottom plate temperature
 - -total duration of e
- Countdown display and buzzer with adjustable volume at the end of the cycle.
- Automatic mechanical lid holding and opening system controlled.
- Ergonomic handle for easy movement of the lid.
- Non-stick pressed tray to be used during all cooking cycles for maximum cleanability, meeting food contact requirements.
- Compliant with Regulation (EC) No 1935/2004 and its amendments, Regulation (EC) No 2023/2006 and its amendments.

Construction


- Aluminum ribbed top contact plate (215 x 215 mm) treated with a special non-stick coating.
- 2 temperature probes for an independent control of the top and bottom plate temperature.
- Smooth 4 mm thick quartz glass bottom cooking surface (250 x 250 mm).
- Independent temperature setting of the top and bottom plates from 50 to 250 °C.
- Automatic lifting of the lid at the end of the cooking cycle via mechanical spring.
- Lid covers, handle and side panels in high-grade reinforced composite material.
- 800W heating element on the top plate.
- 800W electrical armored heating element on the bottom plate.
- 2 x 1050W magnetrons for microwave.
- Front air inlet and back outlet for efficient cooling ventilation allows easy air filters removal and side by side installation.
- IPx4 water protection.

User Interface & Data Management

 Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory - contact the Company for more details).

APPROVAL:







Included Accessories

included Accessories		
 1 of Glass saver for SpeeDelight 	PNC 653527	
 1 of Cleaning brush for SpeeDelight 	PNC 653623	
 1 of Spatula for SpeeDelight 	PNC 653625	
 1 of 4 rubber feet - Height = 26 mm for SpeeDelight 	PNC 653792	
 1 of SpeeDelight spacer stop kit for rear ventilation 	PNC 653800	
 1 of Pressed non-stick tray 	PNC 653802	
 1 of Brush with nylon bristles 	PNC 653803	
 1 of Brush with brass bristles 	PNC 653804	
Optional Accessories		
Glass saver for SpeeDelight	PNC 653527	
 Cleaning brush for SpeeDelight 	PNC 653623	
 Spatula for SpeeDelight 	PNC 653625	
 Removable ribbed teflon plate for SpeeDelight 	PNC 653787	
 4 stainless steel feet - Height = 76 mm for SpeeDelight 	PNC 653791	
 4 rubber feet - Height = 40 mm for SpeeDelight 	PNC 653793	
SpeeDelight spacer stop kit for rear ventilation	PNC 653800	
Pressed non-stick tray	PNC 653802	
Brush with nylon bristles	PNC 653803	
 Brush with brass bristles 	PNC 653804	
Recommended Detergents		
• *NOTTRANSLATED*	PNC 0S2292	
 S02 DEGREASER 6pzx750ml - ADR&IMDG Limited Quantity 	PNC 0S2882	





Plug In SpeeDelight with adjustable tube, ribbed, removable teflon plate

Electric

Supply voltage: 380-400 V/3N ph/50 Hz

Rated amps: 9 A **Total Watts:** 5 kW


IEC 60309 3P+N+T Plug type:


Installation:

Clearance: 190mm from rear vertical panel

Key Information:

Cooking surface (WxD) 250 x 250 mm External dimensions, Width: 370 mm External dimensions, Depth: 683 mm External dimensions, Height: 619 mm Net weight: 46 kg Shipping weight: 58 kg 710 mm Shipping height: Shipping width: 450 mm Shipping depth: 760 mm Shipping volume: 0.24 m³





Electrical inlet (power)

Electrical Outlet

