

Modular Cooking Range Line thermaline 85 - 23 liter Freestanding Gas Deep Fat Fryer, 1 Side with Backsplash

| ITEM # | |
|---------|--|
| MODEL # | |
| MODEL # | |
| NAME # | |
| SIS # | |
| | |
| AIA# | |



588632 (MBFDGBEDPO) 23-It gas deep fat fryer, one-side operated with backsplash

Short Form Specification

Item No.

Unit constructed according to DIN 18860 2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction and external heating elements allow easy cleaning. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Appliance designed to deep fry meat, fish and vegetables (french fries). Deep drawn V-shaped well with thermostatic regulation of oil temperature up to a maximum of 185 °C. Electrical ignition powered by battery with thermocouple for added safety. Flame failure device on each burner, with safety thermostat and thermostatic control. Reduced power setting to melt solid fat. Oil can be easily drained via a ball-valve. All-round basin raised edges to protect against soil infiltration. Large overflow stamped area around the well. Overheat protection switches off the supply in case of overheating. Metal knobs with embedded hygienic silicon "soft" arip enable easier handling and cleaning. IPX4 water resistant certification.

Configuration: Freestanding, one side operated with backsplash.

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Overheat protection: a temperature sensor switches off the supply in case of overheating.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Deep drawn V-Shaped well.
- Large overflow stamped area, located around the well.
- Indirect oil heating system and uniform heat distribution to guarantee extended oil life.
- Reduced power setting to melt solid fat.
- Oil level mark for MAX/MIN filling.
- Designed for deep fat frying of meat, fish, specialities and vegetable (french fries, chips).
- Oil can be drained off via a ball-valve with a lock to prevent unintentional opening. When opened, the ball valve provides a full cross-section opening to easily clean the drainage system.
- Flame failure device on each burner.
- Safety thermostat and thermostatic control.
- Thermostatic regulation of oil temperature up to a maximum of 185 °C.
- Electrical ignition powered by battery with thermocouple for added safety.

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- IPx4 water protection.
- Internal frame for heavy duty sturdiness in stainless steel.

Included Accessories

• 1 of 2 half size baskets for 23lt PNC 913140 deep fat fryer

Optional Accessories

- Discharge vessel for 14 & 23lt fryers
 Lid for discharge vessel 14 & 23lt fryers
 Connecting rail kit for appliances with backsplash, 850mm
 Portioning shelf, 500mm width
 PNC 912523
- ◆ Portioning shelf, 500mm width PNC 912553 ☐ **APPROVAL**:






Modular Cooking Range Line thermaline 85 - 23 liter Freestanding Gas Deep Fat Fryer, 1 Side with Backsplash

| • Folding shelf, 300x850mm | PNC 912579 | |
|--|------------|--|
| • Folding shelf, 400x850mm | PNC 912580 | |
| • Fixed side shelf, 200x850mm | PNC 912586 | |
| Fixed side shelf, 300x850mm | PNC 912587 | |
| Fixed side shelf, 400x850mm | PNC 912588 | |
| Stainless steel front kicking strip, 500mm width | PNC 912631 | |
| • Stainless steel side kicking strip left and right, wall mounted, 850mm width | PNC 912659 | |
| Stainless steel side kicking strip left and right, back-to-back, 1700mm width | PNC 912662 | |
| Stainless steel plinth, against wall, 500mm width | PNC 912879 | |
| • Stainless steel side panel (12mm) 850x700mm, right side, against wall | PNC 913003 | |
| Stainless steel side panel (12mm) 850x700mm, left side, against wall | PNC 913004 | |
| Back panel, 500x700mm, for tops and units with backsplash | PNC 913010 | |
| Endrail kit, flush-fitting, with backsplash, left | PNC 913115 | |
| Endrail kit, flush-fitting, with backsplash, right | PNC 913116 | |
| 1 full size basket for 23lt deep fat fryer | PNC 913141 | |
| Unclogging rod for 23lt deep fat fryer - draining pipe | PNC 913142 | |
| Deflector for floured products - 23lt deep fat fryer | PNC 913143 | |
| Sediment tray for 23lt deep fat fryer | PNC 913144 | |
| Filter for deep fat fryer oil collection basin | PNC 913146 | |
| Endrail kit (12mm) for thermaline 85 units with backsplash, left | PNC 913206 | |
| Endrail kit (12mm) for thermaline 85 units with backsplash, right | PNC 913207 | |
| U-clamping rail for back-to-back installations with backsplash | PNC 913226 | |
| • - NOTTRANSLATED - | PNC 913231 | |
| • - NOTTRANSLATED - | PNC 913261 | |
| • - NOTTRANSLATED - | PNC 913262 | |
| ADD. WALL MOUNT. FIXATION USA | PNC 913640 | |
| LOWER SIDE PANEL TL85 WALL MOUNT.(L)H300 | PNC 913641 | |
| LOWER SIDE PANEL TL85 WALL MOUNT.(R)H300 | PNC 913642 | |
| • TL85/90 WALL MOUNTING KIT - UNITS H700 | PNC 913655 | |
| • - NOTTRANSLATED - | PNC 913670 | |
| • - NOTTRANSLATED - | PNC 913686 | |
| | | |





Modular Cooking Range Line thermaline 85 - 23 liter Freestanding Gas Deep Fat Fryer, 1 Side with Backsplash



| Gas | |
|--|----------------------------------|
| Gas Power: Gas Type Option: Gas Inlet: | 21 kW LPG;Natural Gas 1/2" |
| Key Information: | |
| Number of wells: | 1 |
| Usable well dimensions (width): | 340 mm |
| Usable well dimensions (height): | 250 mm |
| Usable well dimensions (depth): | 400 mm |
| Well capacity: | 20 lt MIN; 23 lt MAX |
| Thermostat Range: | 120 °C MIN; 190 °C MAX |
| External dimensions, Width: | 500 mm |
| External dimensions, Depth: | 850 mm |
| External dimensions, Height: | 700 mm |
| Net weight: | 80 kg |
| | On Base;One-Side |

Operated

Configuration: