

### Modular Cooking Range Line thermaline 85 - Full Module Freestanding Gas Fry Top, 1 Side with Backsplash

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



588668 (MBHBGBHDPO) Gas fry top with smooth chrome plate, oneside operated with backsplash

588672 (MBHDGBHDPO) Gas fry top with ribbed chrome plate, oneside operated with backsplash

## **Short Form Specification**

#### Item No.

Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Smooth chromium-plated mild steel cooking surface with non-stick finishing for optimal grilling. Stainless steel high splash guards on the rear and sides. Features safety thermostat, thermostatic control and led indication of pilot flame. Electrical ignition powered by battery with thermocouple for added safety. Large drain hole enables draining of cooking juices into a large collector. Overheat protection switches off the supply in case of overheating. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.

IPX4 water resistant certification.

Configuration: Freestanding, one side operated with backsplash.

### **Main Features**

- Choice of one or two heating zones. An indicator lamp shows operating state of each zone.
- Large drain hole on cooking surface permits the draining of residual cooking juices into a large collector placed under the cooking surface.
- Overheat protection: a temperature sensor switches off the supply in case of overheating.
- Safety thermostat and thermostatic control.
- Stainless steel high splash guards on the rear and sides of cooking surface.
- Units have separate controls for each half module of the cooking surface.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic silicon "soft" grip for easier handling and cleaning. The special design of the controls prevent infiltration of liquids or soil into vital components.
- Electrical ignition powered by battery with thermocouple for added safety.
- Led indication of pilot flame

## Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Cooking surface in chromium-plated mild steel with non-stick finishing for optimum grilling results.
- Cooking surface to be completely smooth or completely ribbed.
- IPX4 water resistance certification.
- Internal frame for heavy duty sturdiness in stainless steel.

#### APPROVAL:





# Modular Cooking Range Line thermaline 85 - Full Module Freestanding Gas Fry Top, 1 Side with Backsplash

Optional Accessories			Gas	
<ul> <li>Connecting rail kit for appliances with backsplash, 850mm</li> </ul>	PNC 912498		Gas Power:	20 kW
<ul> <li>Portioning shelf, 800mm width</li> </ul>	PNC 912526		Gas Type Option: Gas Inlet:	Natural Gas 1/2"
<ul> <li>Portioning shelf, 800mm width</li> </ul>	PNC 912556			1/ 2
<ul> <li>Folding shelf, 300x850mm</li> </ul>	PNC 912579		Key Information:	
<ul> <li>Folding shelf, 400x850mm</li> </ul>	PNC 912580		Cooking Surface Depth:	615 mm
<ul> <li>Fixed side shelf, 200x850mm</li> </ul>	PNC 912586		Cooking Surface Width:	700 mm
<ul> <li>Fixed side shelf, 300x850mm</li> </ul>	PNC 912587		Working Temperature MIN: Working Temperature MAX:	110 °C 270 °C
<ul> <li>Fixed side shelf, 400x850mm</li> </ul>	PNC 912588		External dimensions, Width:	800 mm
<ul> <li>Stainless steel front kicking strip, 800mm width</li> </ul>	PNC 912634		External dimensions, Depth:	850 mm
<ul> <li>Stainless steel side kicking strip left</li> </ul>	DNIC 012650		External dimensions, Height:	700 mm
and right, wall mounted, 850mm width	FINC 712037	_	Storage Cavity Dimensions (width):	580 mm
<ul> <li>Stainless steel side kicking strip left</li> </ul>	PNC 912662		Storage Cavity Dimensions	770
and right, back-to-back, 1700mm	1110 712002	_	(height): Storage Cavity Dimensions	330 mm
width			(depth):	740 mm
<ul> <li>Stainless steel plinth, against wall, 800mm width</li> </ul>	PNC 912882		Net weight:	145 kg
Stainless steel side panel (12mm)	PNC 913003		Configuration:	On Base;One-Side Operated
850x700mm, right side, against	1110 713003	_	Cooking surface type:	Operated
wall			588668 (MBHBGBHDPO)	Smooth
• Stainless steel side panel (12mm)	PNC 913004		588672 (MBHDGBHDPO)	Ribbed
<ul><li>850x700mm, left side, against wall</li><li>Back panel, 800x700mm, for tops</li></ul>	PNC 913013		Cooking surface - material:	Chromium Plated mild steel mirror
and units with backsplash	FINC 913013	_	Cooking sorrace material.	Steel Hillion
<ul> <li>Endrail kit, flush-fitting, with backsplash, left</li> </ul>	PNC 913115			
<ul> <li>Endrail kit, flush-fitting, with backsplash, right</li> </ul>	PNC 913116			
• Scraper for smooth plates (only for 588668)	PNC 913119			
• Scraper for ribbed plates (only for 588672)	PNC 913120			
• Endrail kit (12mm) for thermaline 85 units with backsplash, left	PNC 913206			
• Endrail kit (12mm) for thermaline 85 units with backsplash, right	PNC 913207			
<ul> <li>U-clamping rail for back-to-back installations with backsplash</li> </ul>	PNC 913226			
• - NOTTRANSLATED -	PNC 913231			
<ul><li>- NOTTRANSLATED -</li></ul>	PNC 913234			
<ul><li>- NOTTRANSLATED -</li></ul>	PNC 913261			
• - NOTTRANSLATED -	PNC 913262			
• - NOTTRANSLATED -	PNC 913281			
Recommended Detergents				
<ul><li>*NOTTRANSLATED*</li></ul>	PNC 0S2292			







