

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



588682 (MBLCGBHDAO) Electric solid top, 4 zones, one-side operated with backsplash

## **Short Form Specification**

#### Item No.

Unit constructed according to DIN 18860\_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, wide rounded, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Solid top made of smooth, pore-free, mild steel. 4 independently controlled heating zones with 2 electronic sensors per zone for temperature surface control and 8 power levels. Rapid plate heat up, continuously ready to use. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning. IPX5 water resistance certification.

Configuration: Free standing, one side operated with backsplash.

#### **Main Features**

- 4 heating zones independently controlled.
- Rapid heat up of the plate and continuously ready for use.
- Overheat protection: a temperature sensor switches off the supply in case of overheating.
- Pans can easily be moved from one area to another without lifting.
- Wide rounded cleaning zone around the plates for easier cleaning.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "softtouch" grip for easier handling and cleaning.
   The special design of the controls prevents infiltration of liquids or soil into vital components.
- Cooking plate and base joint profile guarantee against soil infiltration.
- Two electronic sensors per zone to control surface temperature and to protect cooking plate from overheating.
- 8 power levels.
- Solid top cooking surface made of 20 mm thick steel, DIN 1.7335, smooth pore-free and easy to clean.

#### Construction

- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth.
- IPX5 water resistance certification.
- Internal frame for heavy duty sturdiness in stainless steel.

#### Sustainability



 Standby function for energy saving and fast recovery of maximum power.

#### **Optional Accessories**

- Connecting rail kit for appliances PNC 912498 ☐ with backsplash, 850mm
- ullet Portioning shelf, 800mm width PNC 912526 ullet
- Portioning shelf, 800mm width PNC 912556 🗖
- Folding shelf, 300x850mm PNC 912579  $\Box$
- Folding shelf, 400x850mm PNC 912580 □

#### APPROVAL:






•	Fixed side shelf, 200x850mm	PNC 912586	
	Fixed side shelf, 300x850mm	PNC 912587	
•	Fixed side shelf, 400x850mm	PNC 912588	
•	Stainless steel front kicking strip, 800mm width	PNC 912634	
•	Stainless steel side kicking strip left and right, wall mounted, 850mm width	PNC 912659	
•	Stainless steel side kicking strip left and right, back-to-back, 1700mm width	PNC 912662	
•	Stainless steel plinth, against wall, 800mm width	PNC 912882	
•	Stainless steel side panel (12mm) 850x700mm, right side, against wall	PNC 913003	
•	Stainless steel side panel (12mm) 850x700mm, left side, against wall	PNC 913004	
•	Back panel, 800x700mm, for tops and units with backsplash	PNC 913013	
	Endrail kit, flush-fitting, with backsplash, left	PNC 913115	
•	Endrail kit, flush-fitting, with backsplash, right	PNC 913116	
	Endrail kit (12mm) for thermaline 85 units with backsplash, left	PNC 913206	
•	Endrail kit (12mm) for thermaline 85 units with backsplash, right	PNC 913207	
•	U-clamping rail for back-to-back installations with backsplash	PNC 913226	
•	INSERT.PROFILE,D850,TL-OTHER BRANDS	PNC 913231	
•	- NOTTRANSLATED -	PNC 913234	
	- NOTTRANSLATED -	PNC 913247	
	- NOTTRANSLATED -	PNC 913261	
	- NOTTRANSLATED -	PNC 913262	
	- NOTTRANSLATED -	PNC 913281	
	- NOTTRANSLATED -	PNC 913665	
	STAINLESS STEEL DIVIDING PANEL 850X700MM LEFT/RIGHT	PNC 913670	
•	STAINLESS STEEL SIDE COVER PANEL, FLUSH 850X700MM LEFT/ RIGHT	PNC 913686	






# 



## EI = Electrical inlet (power) EQ = Equipotential screw



#### **Electric** Supply voltage: 400 V/3N ph/50/60 Hz Electrical power max.: 12 kW **Key Information:** 100 °C Working Temperature MIN: Working Temperature MAX: 450 °C External dimensions, Width: 800 mm External dimensions, Depth: 850 mm External dimensions, Height: 700 mm **Storage Cavity Dimensions** (width): 580 mm **Storage Cavity Dimensions** 330 mm (height): **Storage Cavity Dimensions** (depth): 740 mm Net weight: 145 kg On Base;One-Side Configuration: Operated

3 - 3 kW

3 - 3 kW

670 mm

650 mm

### Sustainability

(width):

(depth):

Front Plates Power:

**Back Plates Power:** 

Solid top usable surface

Solid top usable surface

Current consumption: 26 Amps





## **Optional Accessories**

Optional Accessories		
<ul> <li>Connecting rail kit for appliances with backsplash, 850mm</li> </ul>	PNC 912498	
<ul> <li>Portioning shelf, 800mm width</li> </ul>	PNC 912526	
Portioning shelf, 800mm width	PNC 912556	
• Folding shelf, 300x850mm	PNC 912579	$\overline{\Box}$
	PNC 912580	
		_
<ul> <li>Fixed side shelf, 200x850mm</li> </ul>	PNC 912586	
<ul> <li>Fixed side shelf, 300x850mm</li> </ul>	PNC 912587	
<ul> <li>Fixed side shelf, 400x850mm</li> </ul>	PNC 912588	
<ul> <li>Stainless steel front kicking strip, 800mm width</li> </ul>	PNC 912634	
Stainless steel side kicking strip left and right, wall mounted, 850mm width	PNC 912659	
Stainless steel side kicking strip left and right, back-to-back, 1700mm width	PNC 912662	
• Stainless steel plinth, against wall, 800mm width	PNC 912882	
• Stainless steel side panel (12mm) 850x700mm, right side, against wall	PNC 913003	
• Stainless steel side panel (12mm) 850x700mm, left side, against wall	PNC 913004	
Back panel, 800x700mm, for tops and units with backsplash	PNC 913013	
Endrail kit, flush-fitting, with backsplash, left	PNC 913115	
Endrail kit, flush-fitting, with	PNC 913116	
<ul> <li>Endrail kit (12mm) for thermaline 85</li> </ul>	PNC 913206	
units with backsplash, left • Endrail kit (12mm) for thermaline 85	PNC 913207	
units with backsplash, right  • U-clamping rail for back-to-back	PNC 913226	
installations with backsplash		
<ul> <li>INSERT.PROFILE,D850,TL-OTHER BRANDS</li> </ul>	PNC 913231	
<ul><li>- NOTTRANSLATED -</li></ul>	PNC 913234	
• - NOTTRANSLATED -	PNC 913247	
• - NOTTRANSLATED -	PNC 913261	
• - NOTTRANSLATED -	PNC 913262	
	PNC 913281	
NOTTRANSLATED -		
• - NOTTRANSLATED -	PNC 913665	
• STAINLESS STEEL DIVIDING PANEL 850X700MM LEFT/RIGHT	PNC 913670	
<ul> <li>STAINLESS STEEL SIDE COVER PANEL, FLUSH 850X700MM LEFT/ RIGHT</li> </ul>	PNC 913686	

