

Modular Cooking Range Line thermaline 90 - 2 X 5 It Wells Freestanding Electric Pasta Cooker, 1 Side, H=800

ITEM #	
MODEL "	
MODEL #	
NAME #	
SIS #	
<u></u>	
AIA#	



589447 (MCKAFADDAO)

5+5lt electric pasta cooker, one-side operated

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERM

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic silicon "soft" grip for easier handling and cleaning. The special design of the controls prevent infiltration of liquids or soil into vital components.
- Constant water level refill.
- Automatic low-water level shut-off: no accidental over-heating.
- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Easy to clean basin with rounded corners.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Three safety systems protect against overtemperature and can be manually reset without the use of tools.
- Automatic water re-fill regulated by water level sensor at maximum volume.
- Water temperature controlled by electronic sensor and can be selected using 5 power levels

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Water basin in 1.4435 (AISI 316L) stainless steel is seamlessly welded into the top of the appliance.
- IPX5 water resistance certification.
- Internal frame for heavy duty sturdiness in stainless steel.

Sustainability




 Standby function for energy saving and fast recovery of maximum power.


APPROVAL:





Modular Cooking Range Line thermaline 90 - 2 X 5 It Wells Freestanding Electric Pasta Cooker, 1 Side, H=800






D Drain

ΕI Electrical inlet (power) EQ Equipotential screw

Water inlet



Electric

Supply voltage: 400 V/3N ph/50/60 Hz

Total Watts: 5 kW

Water:

Incoming Cold/hot Water line

size: 3/4"

Drain line size:

Key Information:

Number of wells:

Usable well dimensions

(width): Usable well dimensions

225 mm (height):

Usable well dimensions

345 mm (depth):

Well capacity: 4 lt MIN; 5 lt MAX Thermostat Range: 40 °C MIN; 90 °C MAX

140 mm

External dimensions, Width: 400 mm External dimensions, Depth: 900 mm External dimensions, Height: 800 mm Net weight: 65 kg

On Base;One-Side Configuration: Operated

Sustainability

Top

Current consumption: 7.2 Amps







Optional Accessories

Optional Accessories		
 Connecting rail kit, 900mm 	PNC 912502	
• Stainless steel side panel (12mm), 900x800mm, freestanding	PNC 912511	
 Portioning shelf, 400mm width 	PNC 912522	
Portioning shelf, 400mm width	PNC 912552	
 Folding shelf, 300x900mm 	PNC 912581	
• Folding shelf, 400x900mm	PNC 912582	
• Fixed side shelf, 200x900mm	PNC 912589	
• Fixed side shelf, 300x900mm	PNC 912590	
• Fixed side shelf, 400x900mm	PNC 912591	
Stainless steel front kicking strip,	PNC 912594	
400mm width		
 Stainless steel side kicking strips left and right, freestanding, 900mm width 	PNC 912621	
 Stainless steel side kicking strips left and right, back-to-back, 1800mm width 	PNC 912627	
 Stainless steel plinth, freestanding, 400mm width 	PNC 912916	
Connecting rail kit, right	PNC 912975	
Connecting rail kit, left	PNC 912976	
• 2 baskets for 2x5lt pasta cooker	PNC 913034	
Endrail kit, flush-fitting, left	PNC 913111	
• Endrail kit, flush-fitting, right	PNC 913112	
• Lid for 2x5lt pasta cooker	PNC 913150	
False bottom for 2x5lt pasta cooker basket	PNC 913158	
• Endrail kit (12mm) for thermaline 90 units, left	PNC 913202	
• Endrail kit (12mm) for thermaline 90 units, right	PNC 913203	
• Stainless steel side panel, left, H=800, flush	PNC 913224	
• Stainless steel side panel, left, H=800, flush	PNC 913225	
 T-connection rail for back to back installations without backsplash 	PNC 913227	
• - NOTTRANSLATED -	PNC 913232	
• - NOTTRANSLATED -	PNC 913244	
• - NOTTRANSLATED -	PNC 913251	
• - NOTTRANSLATED -	PNC 913252	
• - NOTTRANSLATED -	PNC 913255	
• - NOTTRANSLATED -	PNC 913256	
• - NOTTRANSLATED -	PNC 913259	
• - NOTTRANSLATED -	PNC 913277	
• - NOTTRANSLATED -	PNC 913278	
• - NOTTRANSLATED -		
• - NOTTRANSLATED -	PNC 913676	
		_

