

Modular Cooking Range Line thermaline 90 - 2 X 5 It Wells Freestanding Electric Pasta Cooker, 1 Side, H=800

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	
AIA "	



589447 (MCKAFADDAO)

5+5lt electric pasta cooker, one-side operated

# **Short Form Specification**

#### Item No.

Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERM

#### **Main Features**

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "softtouch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Constant water level refill.
- Automatic low-water level shut-off: no accidental over-heating.
- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Easy to clean basin with rounded corners.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Safety systems protect against overtemperature and can be manually reset.
- Automatic water re-fill regulated by water level sensor at maximum volume.
- Water temperature controlled by electronic sensor and can be selected using 5 power levels.

## Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Water basin in 1.4435 (AISI 316L) stainless steel is seamlessly welded into the top of the appliance.
- IPX5 water resistance certification.
- Internal frame for heavy duty sturdiness in stainless steel.

### Sustainability




 Standby function for energy saving and fast recovery of maximum power.


APPROVAL:





## **Modular Cooking Range Line** thermaline 90 - 2 X 5 It Wells Freestanding Electric Pasta Cooker, 1 Side, H=800






D Drain

ΕI Electrical inlet (power) EQ Equipotential screw

Water inlet



**Electric** 

Supply voltage: 400 V/3N ph/50/60 Hz

Total Watts: 5 kW

Water:

Incoming Cold/hot Water line

size: 3/4"

Drain line size:

**Key Information:** 

Number of wells:

Usable well dimensions 140 mm

(width): Usable well dimensions

225 mm (height):

Usable well dimensions

345 mm (depth):

Well capacity: 4 lt MIN; 5 lt MAX Thermostat Range: 40 °C MIN; 90 °C MAX

External dimensions, Width: 400 mm External dimensions, Depth: 900 mm External dimensions, Height: 800 mm Net weight: 65 kg

On Base;One-Side

Configuration: Operated

Sustainability

Top

Current consumption: 7.2 Amps











# **Optional Accessories**

Optional Accessories		
<ul> <li>Connecting rail kit, 900mm</li> </ul>	PNC 912502	
• Stainless steel side panel (12mm), 900x800mm, freestanding	PNC 912511	
<ul> <li>Portioning shelf, 400mm width</li> </ul>	PNC 912522	
<ul> <li>Portioning shelf, 400mm width</li> </ul>	PNC 912552	
Folding shelf, 300x900mm	PNC 912581	
• Folding shelf, 400x900mm	PNC 912582	
• Fixed side shelf, 200x900mm	PNC 912589	
• Fixed side shelf, 300x900mm	PNC 912590	
• Fixed side shelf, 400x900mm	PNC 912591	
• Stainless steel front kicking strip, 400mm width	PNC 912594	
<ul> <li>Stainless steel side kicking strips left and right, freestanding, 900mm width</li> </ul>	PNC 912621	
<ul> <li>Stainless steel side kicking strips left and right, back-to-back, 1800mm width</li> </ul>	PNC 912627	
Stainless steel plinth, freestanding, 400mm width	PNC 912916	
Connecting rail kit, right	PNC 912975	
Connecting rail kit, left	PNC 912976	
• 2 baskets for 2x5lt pasta cooker	PNC 913034	
Endrail kit, flush-fitting, left	PNC 913111	
• Endrail kit, flush-fitting, right	PNC 913112	
• Lid for 2x5lt pasta cooker	PNC 913150	
False bottom for 2x5lt pasta cooker basket	PNC 913158	
• Endrail kit (12mm) for thermaline 90 units, left	PNC 913202	
• Endrail kit (12mm) for thermaline 90 units, right	PNC 913203	
<ul> <li>Stainless steel side panel, left, H=800, flush</li> </ul>	PNC 913224	
<ul> <li>Stainless steel side panel, left, H=800, flush</li> </ul>	PNC 913225	
<ul> <li>T-connection rail for back to back installations without backsplash</li> </ul>	PNC 913227	
• - NOTTRANSLATED -	PNC 913232	
• - NOTTRANSLATED -	PNC 913244	
• - NOTTRANSLATED -	PNC 913251	
• - NOTTRANSLATED -	PNC 913252	
• - NOTTRANSLATED -	PNC 913255	
• - NOTTRANSLATED -	PNC 913256	
• - NOTTRANSLATED -	PNC 913259	
• - NOTTRANSLATED -	PNC 913277	
• - NOTTRANSLATED -	PNC 913278	
• - NOTTRANSLATED -	PNC 913663	
• - NOTTRANSLATED -	PNC 913673	
• - NOTTRANSLATED -	PNC 913676	
• - NOTTRANSLATED -	PNC 913689	

