

Modular Cooking Range Line thermaline 90 - 20 lt Well Freestanding Electric Pasta Cooker, 1 Side, H=800

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



589475 (MCKCFADDAO)

20lt electric pasta cooker, one-side operated

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERM

Main Features

- Constant water level refill.
- Automatic low-water level shut-off: no accidental over-heating.
- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- All major components may be easily accessed from the front.
- Easy to clean basin with rounded corners.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "softtouch" grip for easier handling and cleaning.
 The special design of the controls prevents infiltration of liquids or soil into vital components.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Automatic two-speed water refill regulated by water level sensor at maxim or minimum volume.
- Water temperature controlled by electronic sensor and can be selected as either temperature or power levels.
- Possibility of food re-generation thanks to electronic temperature control.
- Safety systems protect against overtemperature and can be manually reset.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- IPX5 water resistance certification.
- Water basin in 1.4435 (AISI 316L) stainless steel is seamlessly welded into the top of the appliance.
- Internal frame for heavy duty sturdiness in stainless steel.

Sustainability



• Standby function for energy saving and fast







recovery of maximum power.






Modular Cooking Range Line thermaline 90 - 20 It Well Freestanding Electric Pasta Cooker, 1 Side, H=800





ΕI Electrical inlet (power) Equipotential screw EQ Water inlet



Electric

Supply voltage: 400 V/3N ph/50/60 Hz

Total Watts: 6 kW

Water:

Side

Top

Incoming Cold/hot Water line

size: 3/4"

Drain line size:

Key Information:

Number of wells:

Usable well dimensions (width):

Usable well dimensions 330 mm

(height):

Usable well dimensions 400 mm (depth):

Well capacity: 18 It MIN; 20 It MAX Thermostat Range: 40 °C MIN; 90 °C MAX

250 mm

External dimensions, Width: 400 mm External dimensions, Depth: 900 mm External dimensions, Height: 800 mm Net weight: 73 kg

On Base;One-Side

Configuration: Operated

Sustainability

Current consumption: 8.7 Amps









Modular Cooking Range Line thermaline 90 - 20 lt Well Freestanding Electric Pasta Cooker, 1 Side, H=800

Optional Accessories			• - NOTTRANSLATED -	PNC 913676	
Connecting rail kit, 900mm	PNC 912502		• - NOTTRANSLATED -	PNC 913689	
• Stainless steel side panel (12mm), 900x800mm, freestanding	PNC 912511				
• Portioning shelf, 400mm width	PNC 912522				
• Portioning shelf, 400mm width	PNC 912552				
• Folding shelf, 300x900mm	PNC 912581				
• Folding shelf, 400x900mm	PNC 912582				
• Fixed side shelf, 200x900mm	PNC 912589				
• Fixed side shelf, 300x900mm					
• Fixed side shelf, 400x900mm	PNC 912591				
 Stainless steel front kicking strip, 400mm width 	PNC 912594				
 Stainless steel side kicking strips left and right, freestanding, 900mm width 	PNC 912621				
 Stainless steel side kicking strips left and right, back-to-back, 1800mm width 	PNC 912627				
 Stainless steel plinth, freestanding, 400mm width 	PNC 912916				
 Connecting rail kit, right 	PNC 912975				
 Connecting rail kit, left 	PNC 912976				
• 1 basket for 20lt pasta cooker	PNC 913036				
 Endrail kit, flush-fitting, left 	PNC 913111				
 Endrail kit, flush-fitting, right 	PNC 913112				
• 2 baskets for 20lt pasta cooker	PNC 913135				
 4 baskets for 20lt pasta cooker 	PNC 913136				
• 2 baskets for 20lt pasta cooker	PNC 913137				
 Support frame for 4 baskets for 20lt pasta cooker 	PNC 913138				
• Lid for 20lt pasta cooker	PNC 913148				
• Endrail kit (12mm) for thermaline 90 units, left	PNC 913202				
• Endrail kit (12mm) for thermaline 90 units, right	PNC 913203				
• Stainless steel side panel, left, H=800, flush	PNC 913224				
• Stainless steel side panel, left, H=800, flush	PNC 913225				
 T-connection rail for back to back installations without backsplash 	PNC 913227				
• - NOTTRANSLATED -	PNC 913232				
• - NOTTRANSLATED -	PNC 913244				
• - NOTTRANSLATED -	PNC 913251				
• - NOTTRANSLATED -	PNC 913252				
• - NOTTRANSLATED -	PNC 913255				
• - NOTTRANSLATED -	PNC 913256				
• - NOTTRANSLATED -	PNC 913259				
• - NOTTRANSLATED -	PNC 913277	_			
• - NOTTRANSLATED -	PNC 913278				
• - NOTTRANSLATED -	PNC 913663				
• - NOTTRANSLATED -	PNC 913673	u			

