

Modular Cooking Range Line thermaline 90 - 20 lt Well Freestanding Gas Pasta Cooker, 1 Side, H=800

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



589477 (MCKDFADDPO)

20lt gas pasta cooker, oneside operated

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERM

Main Features

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Safety thermostat and thermostatic control.
- All major components may be easily accessed from the front.
- Easy to clean basin with rounded corners.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic silicon "soft" grip for easier handling and cleaning. The special design of the controls prevent infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Three safety systems protect against overtemperature and can be manually reset without the use of tools.
- Electrical ignition powered by battery with thermocouple for added safety.

APPROVAL:





Modular Cooking Range Line thermaline 90 - 20 It Well Freestanding Gas Pasta Cooker, 1 Side, H=800

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- IPX4 water resistance certification.
- Water basin in 1.4435 (AISI 316L) stainless steel is seamlessly welded into the top of the appliance.
- High efficiency burners in AISI 430 stainless steel with flame failure device.
- Internal frame for heavy duty sturdiness in stainless steel.

Sustainability



• EnergyControl: unique feature for fine power adjustment to control boiling level and optimize energy consumption.


Optional Accessories


Optional Accessories		
 Connecting rail kit, 900mm 	PNC 912502	
• Stainless steel side panel (12mm),	PNC 912511	
900x800mm, freestanding		
 Portioning shelf, 400mm width 	PNC 912522	
 Portioning shelf, 400mm width 	PNC 912552	
 Folding shelf, 300x900mm 	PNC 912581	
• Folding shelf, 400x900mm	PNC 912582	
• Fixed side shelf, 200x900mm	PNC 912589	
• Fixed side shelf, 300x900mm	PNC 912590	
• Fixed side shelf, 400x900mm	PNC 912591	
Stainless steel front kicking strip,	PNC 912594	
400mm width	1110 /120/ 1	_
• Stainless steel side kicking strips left	PNC 912621	
and right, freestanding, 900mm		
width		
• Stainless steel side kicking strips left	PNC 912627	
and right, back-to-back, 1800mm		
width	DVIC 010017	
 Stainless steel plinth, freestanding, 400mm width 	PNC 912916	
	PNC 912975	
Connecting rail kit, right		
Connecting rail kit, left	PNC 912976	_
• 1 basket for 20lt pasta cooker	PNC 913036	
Endrail kit, flush-fitting, left	PNC 913111	
 Endrail kit, flush-fitting, right 	PNC 913112	
 2 baskets for 20lt pasta cooker 	PNC 913135	
 4 baskets for 20lt pasta cooker 	PNC 913136	
 2 baskets for 20lt pasta cooker 	PNC 913137	
• Support frame for 4 baskets for 20lt	PNC 913138	
pasta cooker		
 Lid for 20lt pasta cooker 	PNC 913148	
• Endrail kit (12mm) for thermaline 90	PNC 913202	
units, left		_
• Endrail kit (12mm) for thermaline 90	PNC 913203	
units, right	DNIC 017007	
 Stainless steel side panel, left, H=800, flush 	PNC 913224	
•	PNC 913225	
 Stainless steel side panel, left, H=800, flush 	PINC 913223	_
• T-connection rail for back to back	PNC 913227	
installations without backsplash	1110 710227	_
• - NOTTRANSLATED -	PNC 913232	
• - NOTTRANSLATED -	PNC 913251	
• - NOTTRANSLATED -	PNC 913252	
• - NOTTRANSLATED -	PNC 913255	
• - NOTTRANSLATED -	PNC 913256	
• - NOTTRANSLATED -	PNC 913259	
• - NOTTRANSLATED -	PNC 913277	_
• - NOTTRANSLATED -	PNC 913278	
• - NOTTRANSLATED -	PNC 913673	
• - NOTTRANSLATED -	PNC 913689	
- NOTTRANSLATED -	PNC 913698	






Modular Cooking Range Line thermaline 90 - 20 It Well Freestanding Gas Pasta Cooker, 1 Side, H=800





D = Drain
EQ = Equipotential screw
G = Gas connection

WI = Water inlet



Gas

Gas Power: 11.5 kW

Gas Type Option:

Gas Inlet: 1/2"

Water:

Side

Top

Incoming Cold/hot Water line

size: 3/4"
Drain line size: 1"

Key Information:

Number of wells:

Usable well dimensions

(width): 250 mm Usable well dimensions

(height): Usable well dimensions

(depth): 400 mm

Well capacity: 18 It MIN; 20 It MAX
Thermostat Range: 40 °C MIN; 90 °C MAX

External dimensions, Width: 400 mm
External dimensions, Depth: 900 mm
External dimensions, Height: 800 mm
Net weight: 73 kg

On Base;One-Side

330 mm

Configuration: Operated

