

## Modular Cooking Range Line thermaline 90 - 20 lt Well Freestanding Gas Pasta Cooker, 1 Side, H=800

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



589477 (MCKDFADDPO)

20lt gas pasta cooker, oneside operated

# **Short Form Specification**

#### Item No.

Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERM

#### **Main Features**

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Safety thermostat and thermostatic control.
- All major components may be easily accessed from the front.
- Easy to clean basin with rounded corners.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic silicon "soft" grip for easier handling and cleaning. The special design of the controls prevent infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Three safety systems protect against overtemperature and can be manually reset without the use of tools.
- Electrical ignition powered by battery with thermocouple for added safety.

#### APPROVAL:





## Modular Cooking Range Line thermaline 90 - 20 It Well Freestanding Gas Pasta Cooker, 1 Side, H=800

#### Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- IPX4 water resistance certification.
- Water basin in 1.4435 (AISI 316L) stainless steel is seamlessly welded into the top of the appliance.
- High efficiency burners in AISI 430 stainless steel with flame failure device.
- Internal frame for heavy duty sturdiness in stainless steel.

## Sustainability



• EnergyControl: unique feature for fine power adjustment to control boiling level and optimize energy consumption.


## **Optional Accessories**


Optional Accessories		
Connecting rail kit, 900mm	PNC 912502	
<ul> <li>Stainless steel side panel (12mm), 900x800mm, freestanding</li> </ul>	PNC 912511	
• Portioning shelf, 400mm width	PNC 912522	
• Portioning shelf, 400mm width	PNC 912552	
• Folding shelf, 300x900mm	PNC 912581	
• Folding shelf, 400x900mm	PNC 912582	
• Fixed side shelf, 200x900mm	PNC 912589	
• Fixed side shelf, 300x900mm	PNC 912590	
• Fixed side shelf, 400x900mm	PNC 912591	
	PNC 912591 PNC 912594	
Stainless steel front kicking strip, 400mm width     Stripless shall side kicking strips left.		
<ul> <li>Stainless steel side kicking strips left and right, freestanding, 900mm width</li> </ul>	PNC 912621	
<ul> <li>Stainless steel side kicking strips left and right, back-to-back, 1800mm width</li> </ul>	PNC 912627	
<ul> <li>Stainless steel plinth, freestanding, 400mm width</li> </ul>	PNC 912916	
Connecting rail kit, right	PNC 912975	
Connecting rail kit, left	PNC 912976	
• 1 basket for 20lt pasta cooker	PNC 913036	
Endrail kit, flush-fitting, left	PNC 913111	
• Endrail kit, flush-fitting, right	PNC 913112	
	PNC 913135	
• 2 baskets for 20lt pasta cooker		
4 baskets for 20lt pasta cooker     2 baskets for 20lt pasta cooker	PNC 913136	_
• 2 baskets for 20lt pasta cooker	PNC 913137	
<ul> <li>Support frame for 4 baskets for 20lt pasta cooker</li> </ul>	PNC 913138	_
Lid for 20lt pasta cooker	PNC 913148	
• Endrail kit (12mm) for thermaline 90 units, left	PNC 913202	
<ul> <li>Endrail kit (12mm) for thermaline 90 units, right</li> </ul>	PNC 913203	
<ul> <li>Stainless steel side panel, left, H=800, flush</li> </ul>	PNC 913224	
<ul> <li>Stainless steel side panel, left, H=800, flush</li> </ul>	PNC 913225	
<ul> <li>T-connection rail for back to back installations without backsplash</li> </ul>	PNC 913227	
• - NOTTRANSLATED -	PNC 913232	
• - NOTTRANSLATED -	PNC 913251	
• - NOTTRANSLATED -	PNC 913252	
• - NOTTRANSLATED -	PNC 913255	
• - NOTTRANSLATED -	PNC 913256	
• - NOTTRANSLATED -	PNC 913259	
• - NOTTRANSLATED -	PNC 913277	
• - NOTTRANSLATED -	PNC 913278	
• - NOTTRANSLATED -	PNC 913673	
• - NOTTRANSLATED -	PNC 913689	
• - NOTTRANSLATED -	PNC 913698	





# Modular Cooking Range Line thermaline 90 - 20 It Well Freestanding Gas Pasta Cooker, 1 Side, H=800





D = Drain

EQ = Equipotential screw
G = Gas connection
WI = Water inlet

Gas

Gas Power: 11.5 kW

Gas Type Option:

Gas Inlet: 1/2"

Water:

Incoming Cold/hot Water line

size: 3/4"
Drain line size: 1"

**Key Information:** 

Number of wells:

Usable well dimensions

(width): 250 mm Usable well dimensions

(height):

Usable well dimensions (depth): 400 mm

Well capacity: 18 It MIN; 20 It MAX
Thermostat Range: 40 °C MIN; 90 °C MAX

External dimensions, Width: 400 mm
External dimensions, Depth: 900 mm
External dimensions, Height: 800 mm
Net weight: 73 kg

On Base;One-Side

330 mm

Configuration: Operated



Top

