

Modular Cooking Range Line thermaline 90 - 500 mm Freestanding Electric Free-cooking Top with Smooth Plate, 1 Side, H=800

ITEM #	
MODEL "	
MODEL #	
NAME #	
SIS #	
<u></u>	
AIA#	



589576 (MCTDFAEDAO)

Electric free-cooking top, one-side operated

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Smooth electrically-heated solid plate made of 14 mm thick steel with a wide rounded cleaning zone around the plate. Rapid plate heat up, continuously ready to use; maximum reachable surface temperature of 350°C. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.

IPX5 water resistance certification.

Configuration: Freestanding, One-side operated.

Main Features

- Rapid heat up of the plate and continuously ready for use.
- Overheat protection: a temperature sensor switches off the supply in case of overheating.
- Wide rounded cleaning zone around the plates for easier cleaning.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic silicon "soft" grip for easier handling and cleaning. The special design of the controls prevent infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Cooking plate and base joint profile guarantee against soil infiltration.
- Surface temperature up to 350°C
- For direct and indirect cooking.

Construction

- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- IPX5 water resistance certification.
- Cooking surface is an electrically heated solid plate made from 20mm thick stainless steel AISI 316 - DIN 1.4404.
- 2mm thick top in stainless steel AISI 304 DIN 1,4301.
- Internal frame for heavy duty sturdiness in stainless steel.

Optional Accessories

•	Connecting rail kit, 900mm	PNC 912502	
•	Stainless steel side panel (12mm), 900x800mm, freestanding	PNC 912511	
•	Portioning shelf, 500mm width	PNC 912523	
•	Portioning shelf, 500mm width	PNC 912553	
•	Folding shelf, 300x900mm	PNC 912581	
•	Folding shelf, 400x900mm	PNC 912582	
•	Fixed side shelf, 200x900mm	PNC 912589	
•	Fixed side shelf 300x900mm	PNC 912590	

APPROVAL:








• Fixed side shelf, 400x900mm	PNC 912591		
 Stainless steel front kicking strip, 500mm width 	PNC 912595		
Stainless steel side kicking strips left and right, freestanding, 900mm width	PNC 912621		
Stainless steel side kicking strips left and right, back-to-back, 1800mm width	PNC 912627		
Stainless steel plinth, freestanding, 500mm width	PNC 912917		
Connecting rail kit, right	PNC 912975		
Connecting rail kit, left	PNC 912976		
Endrail kit, flush-fitting, left	PNC 913111	$\overline{\Box}$	
Endrail kit, flush-fitting, right	PNC 913112	_	
Scraper for smooth plates	PNC 913119		
• Endrail kit (12mm) for thermaline 90	PNC 913202	$\overline{\Box}$	
units, left	1110 710202	_	
• Endrail kit (12mm) for thermaline 90 units, right	PNC 913203		
• Stainless steel side panel, left, H=800, flush	PNC 913224		
 Stainless steel side panel, left, H=800, flush 	PNC 913225		
T-connection rail for back to back installations without backsplash	PNC 913227		
• - NOTTRANSLATED -	PNC 913232		
- NOTTRANSLATED -	PNC 913233		
- NOTTRANSLATED -	PNC 913244		
- NOTTRANSLATED -	PNC 913251		
- NOTTRANSLATED -	PNC 913252		
- NOTTRANSLATED -	PNC 913255		
- NOTTRANSLATED -	PNC 913256		
- NOTTRANSLATED -	PNC 913259		
- NOTTRANSLATED -	PNC 913277		
- NOTTRANSLATED -	PNC 913278		
• - NOTTRANSLATED -	PNC 913279		
- NOTTRANSLATED -	PNC 913664		
• - NOTTRANSLATED -	PNC 913673		
• - NOTTRANSLATED -	PNC 913676		
• - NOTTRANSLATED -	PNC 913689		
Recommended Detergents			
NOTTRANSLATED	PNC 0S2292	П	
• NOT TRANSLATED	FINC 032292		











Electrical inlet (power)

Equipotential screw

EQ

Electric

Supply voltage: 400 V/3N ph/50/60 Hz

Total Watts: 6 kW

Key Information:

Working Temperature MIN: 80 °C
Working Temperature MAX: 350 °C
External dimensions, Width: 500 mm
External dimensions, Depth: 900 mm
External dimensions, Height: 800 mm
Net weight: 98 kg

On Base;One-Side Operated

Configuration: Operated

Sustainability

Top

Current consumption: 13 Amps





Ontiona	l Accessories	
Obtiona	i Accessories	Ś

Optional Accessories		
 Connecting rail kit, 900mm 	PNC 912502	
 Stainless steel side panel (12mm), 900x800mm, freestanding 	PNC 912511	
Portioning shelf, 500mm width	PNC 912523	
Portioning shelf, 500mm width	PNC 912553	
• Folding shelf, 300x900mm	PNC 912581	
Folding shelf, 400x900mm	PNC 912582	
• Fixed side shelf, 200x900mm	PNC 912589	
 Fixed side shelf, 300x900mm 	PNC 912590	
 Fixed side shelf, 400x900mm 	PNC 912591	
 Stainless steel front kicking strip, 500mm width 	PNC 912595	
Stainless steel side kicking strips left and right, freestanding, 900mm width	PNC 912621	
Stainless steel side kicking strips left and right, back-to-back, 1800mm width	PNC 912627	
Stainless steel plinth, freestanding, 500mm width	PNC 912917	
Connecting rail kit, right	PNC 912975	
Connecting rail kit, left	PNC 912976	
Endrail kit, flush-fitting, left	PNC 913111	
Endrail kit, flush-fitting, right	PNC 913112	
Scraper for smooth plates	PNC 913119	
• Endrail kit (12mm) for thermaline 90 units, left	PNC 913202	
 Endrail kit (12mm) for thermaline 90 units, right 	PNC 913203	
 Stainless steel side panel, left, H=800, flush 	PNC 913224	
 Stainless steel side panel, left, H=800, flush 	PNC 913225	
 T-connection rail for back to back installations without backsplash 	PNC 913227	
- NOTTRANSLATED -	PNC 913232	
- NOTTRANSLATED -	PNC 913233	
- NOTTRANSLATED -	PNC 913244	
- NOTTRANSLATED -	PNC 913251	
• - NOTTRANSLATED -	PNC 913252	
• - NOTTRANSLATED -	PNC 913255	
• - NOTTRANSLATED -	PNC 913256	
• - NOTTRANSLATED -	PNC 913259	
NOTTRANSLATED -	PNC 913277	
NOTTRANSLATED -	PNC 913278	
• - NOTTRANSLATED -	PNC 913279	
NOTTRANSLATED -	PNC 913664 PNC 913673	
NOTTRANSLATED - NOTTRANSLATED	PNC 913676	
NOTTRANSLATED -NOTTRANSLATED -	PNC 913689	
	1140 /10009	_
Recommended Detergents • *NOTTRANSLATED*	PNC 0S2292	

