SkyLine PremiumS Electric Boiler Combi Oven 202 208V

ITEM #	
MODEL #	
NAME #	
SIS #	



219755 (ECOE202T3L0)

SKYLINE PremiumS 20 FULL SHEET PANS (18" X 26")TOUCH-ELECTRIC 208V-BOILER

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage, IPX5, ETL, EnergyStar, Ergocert

- Built-in BOILER (in s/s 316L) with Lambda Sensor
- OptiFlow: air distribution system with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator.
- 3 Cooking modes: Automatic, Programs, Manual
- Special functions: MultiTimer cooking, Plan-n-Save, SkyHub homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity to the cloud ready
- 6-point multi sensor core temperature probe
- Triple-glass door with double LED lights line
- Includes (10) 922076 stainless steel grids
- Includes (1) 922757 trolley

Main Features

AIA#

- Built-in steam generator: Boiler in AISI 316 steel for highly precise humidity and temperature control according to the chosen settings.
- Lambda Sensor: Real humidity control of +-1% for automatic quantity and size of food recognition to guarantee consistent cooking results
- Dry, hot convection cycle (77 °F 575 °F/25 °C 300 °C): ideal for convection cooking.
- Combi cycle (77 °F 575 °F/25 °C 300 °C): The combination of hot air and steam creating a humidity controlled cooking environment, to reduce the cooking process times and food weight loss.
- Steam cycle (77 °F 266°F/25 °C 130°C): Ideal for sous vide, re-thermalization, and Low Steaming of food and vegetables
- Automatic Cooking Mode: includes 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, pastries and sweet bakery, bread, dessert) with 100+ different pre-installed variations. The Automatic Sensory Phase of the oven optimizes the cooking process according to the size, quantity and type of food loaded in the oven. Real-time monitoring of cooking parameters. Personalize and save up to 70 variations per food family.
- Cycles+: Regeneration (ideal for banqueting on plate or rethermalizing on tray
- -Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family
- Proving cycle
- EcoDelta cooking, cooking with the difference between the food probe core temperature of the food and the cooking cavity
- Sous-vide cooking
- Static Combi (to reproduce traditional cooking from static oven)
- Pasteurization of pasta
- Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood)
- -Food safe Control and Advanced Food Safe Control: to automatically monitor safely the cooking process in compliance with HACCP hygienic standards or drive cooking with pasteurization factor Patented US6818865B2 and related family
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer: Special feature to manage up to 20 different cooking cycles at the same time in the same cavity guaranteeing even cooking results. Up to 200 MultiTimer available programs
- Reversible Fan: 7 speed fan levels from 300 to 1500 RPM with reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Automatic cool-down and pre-heat function
- Different chemical options available: solid (phosphate-

APPROVAL:



SkyLine PremiumS Electric Boiler Combi Oven 202 208V

free), liquid (requires optional accessory).

- GreaseOut: predisposed for integrated grease drain and collection for safer operations (dedicated base as optional accessory).
- Back-up mode: self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 20 full sheet pans or 40 half sheet/hotel pans.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

Construction

- Triple thermo-glazed door: with 2 hinged inside panels for easy cleaning and double LED lights line.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX 5 spray water protection certification for easy cleaning.
- Integrated door shield to avoid steam and heat dispersion from the door, when the roll-in rack is not used.
- Supplied with one full-size sheet trolley, 2 1/2" pitch.

User Interface & Data Management

- Touchscreen: High resolution interface (translated into more than 30 languages including Spanish and French) color-blind friendly panel.
- Picture Management: upload full customized images of cooking cycles or food items
- Make-it-mine: feature to allow full personalization or locking of the user interface by selecting what is visible on screen
- SkyHub:customizable homepageto allow the user to group their favorite functions for immediate access when operating.
- MyPlanner: on-screen agenda where the user can plan their daily work, set reminders for several users and receive personalized alerts for each activity
- SkyDuo: Oven and Blast Chiller automatic communication to guide the user through the cook&chill process by creating a safe controlled environment to optimize time and efficiency (requires optional accessory).
- USB port: to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity: ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- e-learning: equipment trainings, how-to guides, and technical documentation easily accessible by scanning QR-Code with any mobile device.
- Data Analytics: automatic consumption visualization at the end of the cycle.

Sustainability



- Human centered design: with 4-star certification for ergonomics and usability.
- Door handle: ergonomic wing-shaped design for handsfree door opening with elbow, to allow simple trays management (Registered Design at EPO).
- Reduced-Power Feature: To consume less energy during customized slow cooking cycles.
- SkyClean: Automatic self cleaning system with integrated

- descaling of the steam boiler. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- Plan-n-Save: the oven organizes the sequence of the chosen cooking cycles to optimize the processes in the kitchen reduxing time and energy consumption.

Included Accessories


- 10 of Aisi 304 stainless steel grid (18" x PNC 922076 26")
- 1 of 20 Tray Rack Trolley, Full Sheet PNC 922757 Pans, 2 ½" (63mm) pitch for 202 ovens and blast chillers

Optional Accessories

• 20 Tray Rack Trolley, Full Sheet Pans, 2 PNC 922757 ½" (63mm) pitch for 202 ovens and blast chillers



SkyLine PremiumS Electric Boiler Combi Oven 202 208V



44 15/16 2 15/16 " 2 11/16 39 1/2 " 1003 mm 63 1/8 " 4 11/16 "


Electrical connection

CWI2 = Cold Water Inlet 2

CWI1 = Cold Water inlet

D = Drain

DO = Overflow drain pipe



Electric

Supply voltage: 208 V/3 ph/60 Hz

65.4 kW Electrical power, max: Electrical power, default: 65.4 kW

Water:

Water Cold Supply

Connection:

219755 (ECOE202T3L0) 3/4" **Cold Water Inlet Connection:** 3/4" GHT Drain "D": 2" (50 mm)

Max inlet water supply

temperature: 86°F (30°C) Water inlet cold 1: unfiltered Water inlet cold 2: filtered

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions. Refer to manual

for details

Pressure: 15-87 psi (1-6 bar) Chlorides: <85 ppm Conductivity: >50 µS/cm

Installation:

Clearance: 2 in (5 cm) rear Clearance:

and right hand sides.

Suggested clearance for

service access: 20 in (50 cm) left hand side.

Capacity:

Max load capacity: 440 lbs (200 kg) Full-size sheet pans: 20 - 18" X 26"

Key Information:

Door hinges: Right Side External dimensions, Width: 45 3/4" (1162 mm) External dimensions, Depth: 42 " (1066 mm) External dimensions, Height: 70 5/8" (1794 mm)

Net weight: 815 lbs (369.5 kg) Shipping width: 47 3/16" (1200 mm) Shipping depth: 45 3/8" (1150 mm) 79 1/32" (2010 mm) Shipping height: Shipping weight: 1047 lbs (407.5 kg) 97.81 ft3 (2.77 m3) Shipping volume:

ISO Certificates

ISO 9001; ISO 14001; ISO ISO Standards:

45001; ISO 50001

Sustainability

Current consumption: 180.1 Amps



