Electrolux

Standard P 1000 mm Wall Cupbo Slic

reparation bard with 2	MODEL # NAME # SIS #
ling Doors	AIA #
	Main Features
	 Handles in stainless steel for better hygiene and reliability.
	 Sturdiness, stability and reliability of table accurately tested.
	Construction
	 Wall cupboard features an ergonomic handle and an internal shelf which can be positioned at three different levels.
	 Easy access to the cupboard interior on all lengths guaranteed by the use of only 2 doors.
	 Two double-walled sliding doors flush fitting to the front of the frame can easily be removed without

ITEM #

the use of tools to facilitate cleaning of the cupboard interior.

- located flush to the front of the frame.
- 100 mm upstand with 10 mm radioused corner and 13 mm deep, designed to be used against a wall.
- Scotch Brite finish to meet the highest hygiene standards.

Optional Accessories

- Lighting kit with led for wall cupboards (1000mm and 1200mm)
- Lighting kit with led for wall • cupboards (1400mm, 1600mm and 1800mm)

PNC 850710 🗆

PNC 850709 🗅

APPROVAL:

132830 (PS1000LCN)

Wall Cupboard with 2 sliding doors, 1000mm

Short Form Specification

Item No.

Constructed in stainless steel. Back and bottom are made from a single bended stainless steel sheet for easier cleaning. Upturned panel edges. Base shelf and heightadjustable intermediate shelf. Double-walled sliding doors. Loading capacity 80kg/m.

- lle and t three
- engths
- to the , without
- Sturdy sound-deadened sliding doors on tracks





Standard Preparation 1000 mm Wall Cupboard with 2 Sliding Doors



Key Information:

N°	of	dod	ors:	
1	328	830	(PSI	ດດດາ

132830 (PS1000LCN)2External dimensions, Width:1000 mmExternal dimensions, Depth:400 mmExternal dimensions, Height:650 mm

Standard Preparation 1000 mm Wall Cupboard with 2 Sliding Doors

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.