



## Cold Rooms 243x243 -2+8°C Built-in Unit

ITEM # \_\_\_\_\_  
MODEL # \_\_\_\_\_  
NAME # \_\_\_\_\_  
SIS # \_\_\_\_\_  
AIA # \_\_\_\_\_



102049 (CRR2424B16G)

Cold Room 2430x2430  
th.60mm, included Unit

### Short Form Specification

#### Item No.

Usable volume: 12.0 m<sup>3</sup>. Panel insulation in cyclopentane (60mm thickness), with injected polyurethane foam, CFC and HCFC free. Wall and internal ceiling surfaces made of galvanized plastified steel with 120 micron nontoxic pvc coating. Internal floor in non-slip, plastic coated, galvanized steel sheet. Fast-fit centering system using new fasteners made of high resistant composite material. Rounded internal and external corners. Self-closing right-hinged door with magnetic door-gaskets; handle with lock and interior safety release. Internal lighting. Built-in refrigeration unit for operation in ambient temperatures up to +43°C. Refrigerant R290. Defrosting through heated gas with automatic re-evaporation of defrosting water. Control panel with: ON/OFF switch, internal lighting switch and digital control with HACCP and failure alarms.

### Main Features

- Very short assembly time. Expert refrigeration knowledge is not required for installation.
- Anti-slip walk-in floor.
- High hygiene standards and easy to clean thanks to rounded internal / external corners and radiused edges.
- Fast-fit centering system allows perfect alignment of the panels. These new fasteners are made of high resistant composite materials and guarantee perfect grip/sealing of all components.
- Floor surface on which the cold room will be placed should be levelled if presenting irregularities or unevenness up to 1 cm.
- New vacuum injection foaming allows significant and enhanced insulation and higher quality.
- Airtight panels connection, all sides of panels have PVC gasket foamed in place to assure airtight and secure fitting; any other sealing between panels on site is eliminated.
- Semi recessed door saving space on the external side.
- Newly designed handle complete with lock and interior safety release to prevent entrapment when the door is accidentally locked from outside.
- Defrosting through heated gas with re-evaporation of defrosting water permits to reduce the total power installed, shorten defrosting time and limit the warming of the cold room. Dedicated drain hole is not needed.
- Temperature controller with touch panel.
- Control panel includes: luminous ON/OFF switch, internal light switch, cold room functioning indicator, defrost cycle indicator, temperature and thermostat control with digital display.
- The unit is ready to be connected with OnE Connectivity for 24/7 real time monitoring, increasing equipment uptime, maximum profit and optimizing your process.
- Conform to ruling European safety and hygiene standards and CE marked.

### Construction

- Panels are cladded inside and outside with anti-scratch galvanized plastified steel with 120 micron nontoxic pvc coating, polyurethane foam insulation, CFC and HCFC free.
- Whenever the cold room door is opened the microswitch switches on automatically the internal light and turns off the cooling fan.

### User Interface & Data Management

- Connectivity ready for real time access to

APPROVAL:



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)

connected appliances from remote and HACCP monitoring (requires optional accessory).



## Sustainability



- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- Right-hinged door is available as standard (left-hinged door on request) and constructed with smooth rounded profiles, cam-lift action hinges, airtight magnetic gasket and high insulation thus allowing to reduce energy and operating costs.

## Optional Accessories

• Cold room datalogger	PNC 102030	<input type="checkbox"/>
• Plastic curtain for 65cm door clearance	PNC 102120	<input type="checkbox"/>
• Door microswitch	PNC 102441	<input type="checkbox"/>
• Shelving Set, composed of aluminium uprights and 4 polyethylene louvered shelves, for 2430x2430 mm Cold Rooms	PNC 137103	<input type="checkbox"/>

**Front**

**Side**


EI = Electrical inlet (power)

**Electric**

**Supply voltage:** 220 V/1N ph/50 Hz  
**Electrical power, max:** 1.62 kW  
**Total Watts:** 1.62 kW

**Key Information:**

**External dimensions, Width:** 2550 mm  
**External dimensions, Depth:** 2550 mm  
**External dimensions, Height:** 2150 mm  
**Internal Dimensions, Width:** 2430 mm  
**Internal Dimensions, Depth:** 2430 mm  
**Internal Dimensions, Height:** 2030 mm  
**Net weight:** 513 kg

**Connectivity**

**Connection type:** Cable-RS485  
**Protocol type:** Modbus

**Sustainability**

**Current consumption:** 4.62 Amps  
**Refrigerant type:** R290  
**Refrigerant weight (unit 1):** 120 g


**Cold Rooms**  
**243x243 -2+8°C Built-in Unit**

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.02.13