



## Cold Rooms 283x203 -18-20°C Split Unit

ITEM # \_\_\_\_\_  
MODEL # \_\_\_\_\_  
NAME # \_\_\_\_\_  
SIS # \_\_\_\_\_  
AIA # \_\_\_\_\_



102118 (CRF2028SG20N)

Cold/Freezer Room  
2830x2030 th.100mm, split  
Unit

### Short Form Specification

#### Item No.

Usable volume: 11.7 m<sup>3</sup>. Panel insulation in cyclopentane (100mm thickness), with injected polyurethane foam, CFC and HCFC free. Wall and internal ceiling surfaces made of galvanized plastified steel with 120 micron nontoxic pvc coating. Internal floor in non-slip, plastic coated, galvanized steel sheet. Fast-fit centering system using new fasteners made of high resistant composite material. Rounded internal and external corners. Self-closing right-hinged door with magnetic door-gaskets; handle with lock and interior safety release. Internal lighting. Split unit for operation in ambient temperatures up to +43°C. Refrigerant R452a. Defrosting through heated gas with automatic re-evaporation of defrosting water. Control panel with: ON/OFF switch, internal lighting switch and digital control with HACCP and failure alarms.

### Main Features

- Anti-slip walk-in floor.
- High hygiene standards and easy to clean thanks to rounded internal / external corners and radiused edges.
- Fast-fit centering system allows perfect alignment of the panels. These new fasteners are made of high resistant composite materials and guarantee perfect grip/sealing of all components.
- Floor surface on which the cold room will be placed should be levelled if presenting irregularities or unevenness up to 1 cm.
- New vacuum injection foaming allows significant and enhanced insulation and higher quality.
- Airtight panels connection, all sides of panels have PVC gasket foamed in place to assure airtight and secure fitting; any other sealing between panels on site is eliminated.
- Semi recessed door saving space on the external side.
- Newly designed handle complete with lock and interior safety release to prevent entrapment when the door is accidentally locked from outside.
- Temperature controller with touch panel.
- Control panel includes: luminous ON/OFF switch, internal light switch, cold room functioning indicator, defrost cycle indicator, temperature and thermostat control with digital display.
- The unit is ready to be connected with OnE Connectivity for 24/7 real time monitoring, increasing equipment uptime, maximum profit and optimizing your process.
- Conform to ruling European safety and hygiene standards and CE marked.
- All split units are tropicalized (+43°C), use R452 refrigerant and are supplied with a high/low temperature alarm.
- Easy to assemble panels and room.
- Defrosting through heating element with re-evaporation of defrosting water shorten defrosting time and limit the warming of the cold room. Dedicated drain hole is not needed.

### Construction

- Panels are cladded inside and outside with anti-scratch galvanized plastified steel with 120 micron nontoxic pvc coating, polyurethane foam insulation, CFC and HCFC free.
- Whenever the cold room door is opened the microswitch switches on automatically the internal light and turns off the cooling fan.
- Split remote unit provided with 6m of

APPROVAL:



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)

precharged pipe.

### User Interface & Data Management

- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).




### Sustainability

- Right-hinged door is available as standard (left-hinged door on request) and constructed with smooth rounded profiles, cam-lift action hinges, airtight magnetic gasket and high insulation thus allowing to reduce energy and operating costs.

### Optional Accessories

• Cold room datalogger	PNC 102030	<input type="checkbox"/>
• Plastic curtain for 65cm door clearance	PNC 102120	<input type="checkbox"/>
• Door microswitch	PNC 102441	<input type="checkbox"/>
• Shelving Set, composed of aluminium uprights and 4 polyethylene louvered shelves, for 2830x2030 mm Cold Rooms	PNC 137106	<input type="checkbox"/>


**Electric**

Supply voltage: 400 V/3N ph/50 Hz  
 Electrical power, max: 2.98 kW  
 Total Watts: 2.98 kW

**Key Information:**

External dimensions, Width: 3030 mm  
 External dimensions, Depth: 2230 mm  
 External dimensions, Height: 2230 mm  
 Internal Dimensions, Width: 2830 mm  
 Internal Dimensions, Depth: 2030 mm  
 Internal Dimensions, Height: 2030 mm  
 Net weight: 563 kg

**Connectivity**

Connection type: Cable-RS485  
 Protocol type: Modbus

**Sustainability**

Current consumption: 4.78 Amps  
 Refrigerant type: R452A  
 Refrigerant weight (unit 1): 1600 g

