

Modular Preparation 1200 mm Ambient Unit with 2 Sliding Doors

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



121924 (TE2S12)

Ambient Unit with 2 sliding doors, 1200mm

Short Form Specification

Item No.

Constructed entirely in 304 AISI stainless steel. Front and rear longitudinal stainless steel c-channel reinforcement. Internal and external side panels with sound deadening reinforcements to strengthen structure. Sliding doors incorporate sound deadening internal panels. 150mm height-adjustable (0/+90mm) oversized feet (65x65mm) can be removed for masonry installation. 45° degree internal side corner junction system. 304 AISI middle shelf, with inner double fold to eliminate gaps between sides and back, height-adjustable in 3 positions with a stainless steel support to avoid twisting.

Main Features

- Masonry installation possible by simply removing feet.
- Extremely easy to clean thanks to the smooth edges.

Construction

- Front and rear lengthwise stainless steel c-channel reinforcement, 15/10 (16 gauges).
- Sound deadening reinforcements between internal and external side panels to strengthen structure.
- Mounted on 150 mm height adjustable (0/+90 mm) oversized (65x65 mm) feet.
- Internal sides supporting the structure to have 45° degrees internal side corners junction system.
- 30 mm high middle-shelf in AISI 304 stainless steel, height-adjustable in 3 positions, with inner double fold to eliminate gaps between sides and back.
- Made in 304 AISI CrNi 18/10 stainless steel with Scotch Brite finish.
- Sliding doors, with sound deadening internal and external panels, run on the upper part on the s/s bearings and on the lower part on a hidden runner. Doors are easy to remove thus facilitating cleaning procedures.

APPROVAL:





Modular Preparation 1200 mm Ambient Unit with 2 Sliding Doors

Key Information:	
Cabinet width: 121924 (TE2S12) Cabinet depth: Cabinet height: N° of doors: Door Type: External dimensions, Width: External dimensions, Depth: External dimensions, Height: Net weight:	1030 mm 620 mm 645 mm 2 Sliding 1200 mm 680 mm 860 mm