

## Standard Preparation 1200 mm Cupboard Sink for Dishwasher with 1 Bowl & Right Drainer

ITEM # \_\_\_\_\_  
 MODEL # \_\_\_\_\_  
 NAME # \_\_\_\_\_  
 SIS # \_\_\_\_\_  
 AIA # \_\_\_\_\_



132928 (MARMDXN)

Cupboard Sink for  
Dishwasher with 1 bowl and 1  
right hand drainer, 1200mm

### Short Form Specification

#### Item No. \_\_\_\_\_

Made entirely from stainless steel. Inner welded frame in stainless steel. Unique connection of panels to inner frame. The 50mm high worktop in 304 AISI stainless steel, 1mm in thickness, incorporates a layer of sound deadening material and has upturned edges. Upstand (h=100mm) with 8mm rounded edge. Drainage area suitable for drying operations. Additional space under drainer for undercounter dishwasher. Sound-deadened hinged door. Base panel in 304 AISI stainless steel and height-adjustable intermediate shelf. Sink bowl in 304 AISI stainless steel with overflow pipe and drain hole. Mounted on feet, adjustable in height.

### Main Features

- Sturdiness, stability and reliability of table accurately tested.

### Construction

- 50 mm worktop in 304 AISI stainless steel with upturned edges, incorporates an 18 mm layer of sound deadening material.
- Reinforced side and base panel in 304 AISI stainless steel.
- 304 AISI stainless steel feet, 200 mm high and 54 mm in diameter, adjustable by -50/+30 mm.
- Inner welded frame in stainless steel to guarantee superior strength and stability.
- Drainage area suitable for drying operations
- 100 mm upstand with 10 mm radiused corner and 13 mm deep, designed to be used against a wall.
- Constructed entirely in stainless steel to offer maximum durability.
- Bottom part of drain left free to house an undercounter dishwasher.
- Hinged door with sound deadening internal panels, fitted with 304 AISI stainless steel hinges on the inner sides.
- Wide range of taps are available to suit every need.

### Optional Accessories

- Wheel kit for cupboards, 4 wheels (2 with brakes), D=1000 mm PNC 855299 ☐
- Elbow operated mixer tap with PNC 855322 ☐  
spout 3/4", single hole
- Elbow operated mixer tap with PNC 855323 ☐  
short spout 3/4", single hole
- Foot operated mixer tap (hot and cold) with spout 3/4" PNC 855328 ☐
- Single plastic drain syphon 2 " for Sinks PNC 895313 ☐

APPROVAL: \_\_\_\_\_



<b>Cabinet width:</b>	1145 mm
<b>Cabinet depth:</b>	645 mm
<b>Cabinet height:</b>	385 mm
<b>External dimensions, Width:</b>	1200 mm
<b>External dimensions, Depth:</b>	700 mm
<b>External dimensions, Height:</b>	1000 mm
<b>Upstand Dimensions, Height:</b>	100 mm
<b>Upstand Dimensions, Depth:</b>	13 mm
<b>Upstand Dimensions, Radius:</b>	R=10
<b>Bowls number</b>	1
<b>Bowl dimensions</b>	400x500xH300
<b>Number and type of doors:</b>	1 Hinged
<b>Worktop thickness:</b>	50 mm
<b>Net weight:</b>	55 kg

Technical drawing of the front view of a cabinet. The overall height is 900. The overall width is 601. The width of the cabinet body is 500, with 49 units of overhang on each side. The depth of the cabinet is 150, with a tolerance of +25/-34. The distance from the top edge to the top of the cabinet body is 1. The distance from the bottom edge to the bottom of the cabinet body is 49. The distance from the side edge to the side of the cabinet body is 49. The distance from the top edge to the top of the cabinet body is 1. The distance from the bottom edge to the bottom of the cabinet body is 49. The distance from the side edge to the side of the cabinet body is 49. The distance from the top edge to the top of the cabinet body is 1. The distance from the bottom edge to the bottom of the cabinet body is 49. The distance from the side edge to the side of the cabinet body is 49. The distance from the top edge to the top of the cabinet body is 1. The distance from the bottom edge to the bottom of the cabinet body is 49. The distance from the side edge to the side of the cabinet body is 49.

Technical drawing of a rectangular box with dimensions and a red dashed outline of internal components. The overall dimensions are 689 (width) x 900 (height) x 102,6 (depth). The box has a top flange of 50 and a bottom flange of 102,6. The internal components are outlined in red dashed lines, showing a complex internal structure with a central vertical section and horizontal sections. The dimensions for the internal components are: 13 (top left corner), 100 (top left corner), 5,5 (top left corner), 552 (central vertical section), 199 (bottom left corner), 77,5 (bottom left corner), 508,8 (bottom center), and 102,6 (bottom right corner). A red dashed line also indicates a curved internal feature with a radius of R 10.

2025.07.04