

PLUS - Static Preparation 1200 mm Soaking Sink with 1 Bowl with Shelf

| ITEM # | |
|---------|--|
| MODEL # | |
| NAME # | |
| SIS # | |
| AIA# | |
| 71171 | |



134121 (LSGVLP1201)

Soaking Sink Unit with 1 bowl and lower shelf, 1200mm

Short Form Specification

Item No.

Enhanced stability and solid construction thanks to the welded frame and legs. The 50mm high worktop in 304 AISI stainless steel, with Scotch Brite finishing 10/10 mm in thickness, has antidrip edges, welded corners and overflow rim along the top. Welded and polish sink bowl in 304 AISI stainless steel supplied with overflow pipe and 2" drain hole. Upstand h=100mm with 10mm radius corner covered on the back with AISI 304 stainless steel spot welded profile. Square section legs and height adjustable feet (-20 +30 mm) in 304 AISI stainless steel. 40 mm-thick lower welded shelf in AISI 304 stainless steel slots easily into place at a height of 200 mm from the floor (compulsory toinstall the chest of drawers). Square section legs and height adjustable feet (-20 +30 mm) in 304 AISI stainless steel.

Main Features

- Enhanced stability and solid construction. Stability, loading and stress tests by external certified body.
- Product range suitable for international tenders requirements for intense usage installations.

Construction

- Welded frame and legs.
- Worktop with 50mm high profile, is in stainless steel Scotch Brite finishing, 10/10 in thickness with anti-drip edges and welded corners and overflow rim along the top.
- Constructed entirely in 304 AISI stainless steel.
- Sink bowl is sound-deadened, in polish stainless steel overflow pipe and 2" drain hole.
- Drainers are sound-deadened with stainless steel reinforcement bars.
- Upstand back completely covered with Stainless Steel welded profile.
- Square section legs (40x40mm, 10/10 in thickness) and height-adjustable feet (-20/+30mm).
- Lower shelf has 40mm high profile, is 8/10 in thickness with upturned edges and bar reinforcement welded to legs for further structure reinforcement.
- Accessories:-set of castors as alternative to the feet, can be fitted as optional.

Optional Accessories

• Double plastic drain syphon 2

| | " for sinks | | _ |
|---|--|------------|---|
| • | Set of 4 wheels (2 with brake), diameter=100mm | PNC 855205 | |
| • | Single plastic drain syphon 1,5 " for work tables with bowl | PNC 855306 | |
| • | Single plastic drain syphon 2" for Sinks | PNC 895313 | |


PNC 850022 □

APPROVAL:





PLUS - Static Preparation 1200 mm Soaking Sink with 1 Bowl with Shelf



Key Information:

External dimensions, Width:

134121 (LSGVLP1201)

External dimensions, Depth: 700 mm

External dimensions, Height: 1000 mm

Upstand Dimensions, Height: 13 mm

Upstand Dimensions, Radius: R=10

Bowls number 1

Bowl dimensions 1060x500xH350

Worktop thickness: 50 mm Net weight: 34 kg