

Modular Preparation 1200 mm Work Top with Upstand

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



121138 (TPLA12A)

 Work Top with upstand
1200mm

Short Form Specification

Item No. _____

The 40mm high worktop in 304 AISI stainless steel, incorporates an 18mm under panel made of sound deadening material. Front and rear longitudinal stainless steel c-channel reinforcement. Special shaped front profile, without burrs, to avoid water leakage. Fully welded and shapely polished corners. 100mm boxed heavy duty splash back with a 45° top angle and fully welded sides. Work tops can be mounted on brackets, legs or bases in order to obtain a work height of 900mm.

Main Features

- Special shaped front and rear profiles without burrs to avoid water leakage on modules below.
- Extremely easy to clean thanks to the large and smooth seamless surface with Scotch-Brite finishing.


Construction

- 304 AISI stainless steel worktop (CrNi 18/10) 40 mm high, 15/10 (16 gauges) thickness.
- 18mm under panel made of sound deadening material according to E1 European specifications.
- Front and rear lengthwise stainless steel c-channel reinforcement, 15/10 (16 gauges).
- For a work height of 900 mm, worktops can be mounted on: solid bracket, solid bracket plus 50x50mm legs, 710 mm ambient, hot, refrigerated or freezer units with hinged doors or telescopic drawers, placed on oversized (65x65mm) or 150mm high feet (0/+90mm adjustable in height).
- Fully welded and polished corners.
- 100 mm boxed heavy duty splashback with a 45° degrees top angle, folded directly from the worktop, has fully welded sides and rear part completely covered by stainless steel profile to avoid water spillage on modules below.

Optional Accessories

- | | |
|--|-------------------------------------|
| • Double plastic drain syphon 2" for sinks | PNC 850022 ☐ |
| • Drop-in soaking unit 800x500x350mm | PNC 855216 ☐ |
| • Single plastic drain syphon 1,5" for work tables with bowl | PNC 855306 ☐ |
| • Drop-in Bowl and right-hand drainage 400x400x200mm | PNC 855800 ☐ |
| • Drop-in Bowl and right-hand drainage 600x500x250mm | PNC 855801 ☐ |
| • Side upstand, h=100mm | PNC 855802 ☐ |
| • Bowl Skirting (400x400x200) for cantilever execution | PNC 855806 ☐ |
| • Bowl Skirting (600x500x250) for cantilever execution | PNC 855807 ☐ |
| • Bowl Skirting (2x600x500x250) for cantilever execution | PNC 855808 ☐ |
| • Stainless steel square tube wall bracket | PNC 855814 ☐ |
| • Stainless steel wall bracket with squared leg 50x50mm | PNC 855815 ☐ |
| • Drop-in Bowl and left-hand drainage 400x400x200mm | PNC 855816 ☐ |
| • Drop-in Bowl and left-hand drainage 600x500x250mm | PNC 855817 ☐ |
| • False bottom for right hand 600x500mm Bowl | PNC 895100 ☐ |
| • False bottom for left hand 600x500mm Bowl | PNC 895110 ☐ |
| • Single plastic drain syphon 2" for Sinks | PNC 895313 ☐ |

APPROVAL: _____



Key Information:

External dimensions, Width:	
121138 (TPLA12A)	1200 mm
External dimensions, Depth:	700 mm
External dimensions, Height:	140 mm
Upstand Dimensions, Height:	100 mm
Upstand Dimensions, Radius:	90°
Worktop thickness:	40 mm
Net weight:	41 kg