



## Standard Preparation 1200 mm Soaking Sink for Dishwasher with 1 Bowl

ITEM # \_\_\_\_\_  
MODEL # \_\_\_\_\_  
NAME # \_\_\_\_\_  
SIS # \_\_\_\_\_  
AIA # \_\_\_\_\_



133194 (NSBD1417L)

Sink Unit for Undercounter  
Dishwasher with 1 bowl  
600x500x320mm and left  
hand drainer, 1400mm

### Short Form Specification

#### Item No.

Made from 304 AISI stainless steel. The 50mm high worktop in 304 AISI stainless steel, 1mm in thickness, is sound-deadened and has an overflow rim and welded corners. Integral rear upstand, h=100mm, with 10mm radius. Allround apron. Square section legs 40x40mm on 1" height-adjustable feet (+/-20mm). Bowl mm600x500x300h with overflow pipe and 2"drain hole; left hand drainer. An undercounter dishwasher can be placed under the drainer.

### Main Features

• Sturdiness, stability and reliability of table accurately tested.

### Construction

- Sink tops easily slotted onto the legs and taps are easily installed from the rear.
- Square section legs and 40 mm height-adjustable feet in 304 AISI stainless steel.
- 100 mm upstand with 8 mm radiused corner and 13 mm deep, designed to be used against a wall.
- 50 mm worktop in 304 AISI stainless steel, 10/10 in thickness with overflow rim along the top.
- Bottom part of drain left free to house an undercounter dishwasher.
- Wide range of taps are available to suit every need.
- Drainage area suitable for drying operations
- 100 mm upstand with 10 mm radiused corner and 13 mm deep, designed to be used against a wall.

### Optional Accessories


- Set of 4 wheels (2 with brake) PNC 855150  d. 100mm for tables and sinks (total height on wheels= 993 mm)
- Elbow operated mixer tap with PNC 855322  spout 3/4", single hole
- Elbow operated mixer tap with PNC 855323  short spout 3/4", single hole
- Foot operated mixer tap (hot and cold) with spout 3/4" PNC 855328
- Lower shelf for 800 mm tables PNC 855363  and sinks
- Elbow operated mixer tap with PNC 855374  spout, 3/4" single hole
- Elbow operated mixer tap with PNC 855375  short spout, 3/4" single hole
- Single hole deck mounted PNC 855382  mixing temperature monoblock faucet
- Single hole deck mounted PNC 855383  extra robust pot filling mixing temperature faucet
- Single hole deck mounted PNC 855384  mixing temperature faucet with short spout
- Single hole deck mounted PNC 855385  mixing temperature pre-rinse unit
- Single hole deck mounted PNC 855386  elbow operated mixing temperature faucet with pre-rinse unit
- Single hole deck mounted PNC 855387  riser add-on mixing temperature faucet with pre-rinse unit

APPROVAL:



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)

- Single hole deck mounted elbow operated mixing temperature faucet with short pre-rinse unit PNC 855388
- Single hole deck mounted riser add-on mixing temperature faucet with pre-rinse unit PNC 855389
- Single hole deck mounted mixing temperature faucet with pre-rinse unit PNC 855390
- Floor fastening kit for 2 square legs PNC 865386
- Single plastic drain siphon 2" for Sinks PNC 895313


**Key Information:**
**External dimensions, Width:**
**133194 (NSBD1417L)** 1400 mm

**External dimensions, Depth:** 700 mm

**External dimensions, Height:** 1000 mm

**Upstand Dimensions, Height:** 100 mm

**Upstand Dimensions, Depth:** 13 mm

**Upstand Dimensions, Radius:** R=13

**Bowls number**
**Bowl dimensions**
**Net weight:** 60 kg
