

# Eco Preparation 1600 mm Hot Cupboard

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



132873 (MSR1607N)

Hot Cupboard, 1600mm

# **Short Form Specification**

#### Item No.

Made entirely from stainless steel. Inner welded frame in stainless steel. Unique connection of panels to inner frame. Worktop in 304 AISI stainless steel (50mm high) incorporates a layer of sound deadening material and has upturned edges. Sound-deadened

#### **Main Features**

- Ideal for central positioning in the kitchen, either as island installation or back to back.
- Digital display thermostat to control the internal temperature.
- Model specific to keep dishes warm.
- Handles in stainless steel for better hygiene and reliability.
- Sturdiness, stability and reliability of table accurately tested.

#### Construction

- 40 mm worktop in 304 AISI stainless steel.
- Inner welded frame in stainless steel to guarantee superior strength and stability.
- Handles directly built into the sliding doors.
- Equipped with intermediate shelf which can be positioned at three different heights.
- Intermediate shelf in stainless steel with riveted corners and trasversal reinforcement in stainless steel.
- Sturdy sound-deadened sliding doors on tracks located flush to the front of the frame.
- Easy access to the cupboard interior on all lengths guaranteed by the use of only 2 doors.
- Constructed entirely in stainless steel to offer maximum durability.
- Constructed entirely in stainless steel to offer maximum durability.
- Base panel has 40mm high profile, is 8/10 in thickness with upturned edges and bar reinforcement. It is welded to legs for further structure reinforcement.
- 304 AISI stainless steel feet, 150 mm high and 54 mm in diameter, adjustable by -35/+25 mm.

## **Optional Accessories**

 Wheel kit for cupboards, 4 wheels (2 with brakes), D=1000

#### APPROVAL:





# Eco Preparation 1600 mm Hot Cupboard

	l		•
-	$\sim$	rr	-
_	ec	u	ı

Supply voltage: 220-240 V/1N ph/50/60 Hz **Total Watts:** 2.4 kW

### **Key Information:**

Cabinet width: 1430 mm Cabinet depth: 645 mm 610 mm Cabinet height: 50-75 °C Cabinet temperature: External dimensions, Width: 1600 mm 700 mm External dimensions, Depth: External dimensions, Height: 900 mm Worktop thickness: 50 mm Net weight: 65 kg

