

# Eco Preparation 1800 mm Hot Cupboard with Upstand

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



132879 (MSR1817N)

Hot Cupboard, with 100mm upstand, 1800mm

# **Short Form Specification**

### Item No.

Made entirely from stainless steel. Inner welded frame in stainless steel. Unique connection of panels to inner frame. Worktop in 304 AISI stainless steel (50mm high) incorporates a layer of sound deadening material and has upturned edges. Upstand (h=100m

### **Main Features**

- Digital display thermostat to control the internal temperature.
- Model specific to keep dishes warm.
- Handles in stainless steel for better hygiene and reliability.
- Sturdiness, stability and reliability of table accurately tested.
- 100 mm upstand with 13mm depth and 10 mm radioused corner, designed to be used against a wall

#### Construction

- 40 mm worktop in 304 AISI stainless steel.
- Inner welded frame in stainless steel to guarantee superior strength and stability.
- Handles directly built into the sliding doors.
- Equipped with intermediate shelf which can be positioned at three different heights.
- Intermediate shelf in stainless steel with riveted corners and trasversal reinforcement in stainless steel.
- Sturdy sound-deadened sliding doors on tracks located flush to the front of the frame.
- Easy access to the cupboard interior on all lengths guaranteed by the use of only 2 doors.
- Constructed entirely in stainless steel to offer maximum durability.
- Constructed entirely in stainless steel to offer maximum durability.
- Base panel has 40mm high profile, is 8/10 in thickness with upturned edges and bar reinforcement. It is welded to legs for further structure reinforcement.
- 304 AISI stainless steel feet, 150 mm high and 54 mm in diameter, adjustable by -35/+25 mm.

## **Optional Accessories**

 Wheel kit for cupboards, 4 wheels (2 with brakes), D=1000 mm

### APPROVAL:





# Eco Preparation 1800 mm Hot Cupboard with Upstand

**Electric** 

**Supply voltage:** 220-240 V/1N ph/50/60 Hz

Total Watts: 2.4 kW

**Key Information:** 

Cabinet width: 1630 mm Cabinet depth: 645 mm Cabinet height: 610 mm Cabinet temperature: 50-75 °C External dimensions, Width: 1800 mm External dimensions, Depth: 700 mm External dimensions, Height: 1000 mm Upstand Dimensions, Height: 100 mm Upstand Dimensions, Depth: 13 mm Upstand Dimensions, Radius: R=10 Worktop thickness: 50 mm Net weight: 70 kg

