Electrolux PROFESSIONAL

Warewashing Large Pot & Pan Washer with Drain Pump & Detergent Dispenser - Marine



190400 (EPPWELGM5)

Electric Pot&Pan Washer with electronic control, drain pump, detergent and rinse aid dispenser - marine

Short Form Specification

Item No.

304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms. Double skinned insulated door divided in 2 parts with 180° frontal opening. N. 4 washing cycles.

Built-in atmospheric, insulated water boiler (10,5 kW), 18-liter capacity, combined with rinse booster pump guarantee a constant hot rinse temperature of 84°C. Boiler with 304 welding for protection against corrosion. Wash Safe Control assures the correct water temperature and pressure during the rinse phase to guarantee a perfect rinsing performance independent from the water pressure in the network (min. 0,5 bar).

High efficiency air gap (class A) in water inlet circuit to avoid water being syphoned back into the network as a result of a sudden drop in mains pressure. Fault auto-diagnosis system. Self-cleaning cycle. Drain pump, rinse aid and detergent dispenser included.

Pre-arrangements for connection to an Energy Management device and to an automatic detergent dispenser. WRC compliant components.

Cell dimensions mm1340x710x570h.

Load capacity: n.6x1/1 GN.

For front-feed loading. IPX5 water protection.

Supplied with: n. 1 basket in stainless steel and n. 2 racks for containers and trays.

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	

Main Features

- Atmospheric insulated boiler combined with the rinse booster pump for perfect rinsing results (water temperature and pressure always constant during rinsing cycles), independent from the inlet water pressure.
- Green light of "WASH SAFE CONTROL" confirms that items have been rinsed properly.
- Available upon request, pre-arranged model for HACCP implementation (both basic as well as integrated system).
- High efficiency air gap (class A) in water inlet circuit to avoid water being siphoned back into the network as a result of a sudden drop in main pressures.
- Open air gap in compliance with WRC regulations.
- 4 washing programs (one program is continual).
- Equipped with drain pump and built-in detergent dispenser for easy and quick installation without opening the machine.
- Easier access to the washing chamber thanks to the 180° frontal opening door.
- Requires limited space for opening thanks to the door divided in 2 sections.
- Self-cleaning cycle.
- Low noise level.
- Simple electronic control panel.
- Fault auto-diagnosis system.
- Simple service from the front.

Construction

- 304 stainless steel boiler with higher welding protection to increase resistance to corrosion.
- Only one cable for electrical connection.
- External connecting board protected by a waterproof plastic box.
- Unit to feature smooth surfaces to facilitate cleaning.
- Easy to remove pump and tank filters.
- Large strainer box above the water surface for frequent cleaning operations.
- Equipped with side washing arms in addition to upper and lower wash arms.
- 304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms.
- Unit to feature rinse aid dispenser pump.

Sustainability

- Finished in top quality materials to ensure durability.
- Double skin insulated door to reduce heat dispersion.
- Pre-arranged to be connected to Energy Management device.

APPROVAL:





Included Accessories

 2 of Extra rack for containers and trays 	PNC 864182
 1 of Stainless steel basket for pot washer, 1351mm 	PNC 864192
Optional Accessories	
 Filter for total demineralization 	PNC 864015
Filter for partial demineralization	PNC 864017

• Kit to measure total and partial PNC 864050 D water hardness

- Extra rack for containers and trays PNC 864182
 Stainless steel basket for pot washer, PNC 864192
- 1351mm● Filter for total demineralizationPNC 864367 □

Electrolux PROFESSIONAL





WRAS

Supply voltage: Electrical power, max: Default Installed Power: Wash pump power:

400 V/3 ph/50 Hz 26 kW 17 kW 5 kW

14001

Water:

Electric

Pressure, min-max:	0.5-7 bar
Washing cycle electrical elements:	10,5 kW
Hot rinse cycle duration (sec.):	ISO 9001; ISO
Water supply temperature*:	50 °C
Washing tank capacity (It):	150
Boiler Capacity (It):	18

Key Information:

Rinsing water consumption (per cycle): Washing cycle temperature: Hot rinse cycle temperature: N° of working cycles: Cell dimensions - width: Cell dimensions - depth: Cell dimensions - height: External dimensions, Width: External dimensions, Depth: External dimensions, Height: Net weight: Shipping weight: Shipping height: Shipping width: Shipping depth: Shipping volume:

12 It 55-65 °C 84 °C 4 (180/360/540/inf) 1340 mm 710 mm 570 mm 1552 mm 900 mm 1791 mm 300 kg 340 kg 2030 mm 1100 mm 1800 mm 4.02 m³

Warewashing - Large Pot & Pan Washer with Drain Pump & Detergent Dispenser Marine The company reserves the right to make modifications to the products

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.