Door Dual Digital Stainless Steel Freezer, 1430lt (-22/-15) - Remote

ecostore 2 Door Dual Digital Stainless Steel Freezer, 1430lt (-22/-15) - Remote

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	

727476 (RE4142FFR)

2-door Freezer 1430lt, -22-15°C, digital, remote, stainless steel

Short Form Specification

Item No.

Two full door freezer with internal and external structure in 430 AISI stainless steel; external back panel in galvanized steel and bottom panel in anticorrosive material. Digital control with cabinet temperature display and setting and manual activation of defrost cycle. Fully compliant HACCP digital controls include visible alarms. Optimized back to front forced air flow provides even temperature distribution and fast cooling in any conditions. Fitted with 75 mm-thick cyclopentane insulating foam. Door features lock and door microswitch to switch off the fan when the door is opened. Hidden evaporator to guarantee higher storage capacity and less corrosion problems. Remote refrigeration unit; ventilated operation; automatic defrost and evaporation of defrost water. Dual operating temperature: -22/-15°C. For ambient temperatures up to 43 °C

Supplied with n. 6x2/1GN Rilsan coated grids and n. 6 sets of 2 stainless steel arid runners.

Main Features

- Digital control with cabinet temperature display and setting and manual activation of defrost cycle. Fully compliant HACCP digital controls include visible alarms.
- Large storage area suitable to contain 2/1 GN grids or shelves on anti-tilt runners.
- Optimized back to front forced air flow provide even temperature distribution and fast cooling in any conditions.
- Automatic defrost.
- Internal structure with numerous charging positions available to host grids, ensuring higher net capacity and a greater storage space.
- Cabinet fitted with up to 75 mm thickness of cyclopentane insulation for best insulating with 100% performance environmental protection (thermal conductivity: 0,020 W/m*
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.
- covering mm-thick insulation evaporator can be easily removed with a single operation.
- Rilsan coated grids for improved protection.
- Hidden evaporator thus guaranteeing higher storage capacity and less corrosion problems.
- Freezer model has operating temperatures that can be adjusted from -22 to -15 °C.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).

Construction

- Interior base with rounded corners, pressed from a single sheet.
- Stainless steel runners and supports easily disassembled.
- Anti-corrosion bottom avoids any damage that may be caused to the cabinet by aggressive detergents employed to clean the floors.
- Lockable door.
- Door switch stops the fan when door is opened to avoid cold air exiting the cell, thus saving energy.
- CFC and HCFC-free insulation.
- Mounted on adjustable Stainless steel feet, with castors as an option.
- Doors are self-closing and can be fully opened up to 180°.
- The rounded internal corners, the easily

APPROVAL:







removable runners and grids allow for ease of cleaning and high hygiene standards.

- Remote refrigeration unit.
- Refrigerant type: R404a.
- External back panel in galvanized steel.
- AISI 430 stainless steel internal structure and external panels.

Included Accessories


remote models


 6 of 2/1GN grey rilsan grid with 2 runners 	PNC 881020	
Optional Accessories		
 Remote unit -22-15°C for 1430lt refrigerated cabinets 	PNC 880233	
• 2 stainless steel runners for refrigerated cabinets - (Marine)	PNC 880242	
 Set of 8 GN1/1 PVC containers for fish 	PNC 880243	
 Spacer for 670 lt and 1430 lt refrigerated cabinets 	PNC 880248	
 Ethernet connector for IR33 (CAREL) Refrigerated Cabinets and Counters 	PNC 880252	
 Kit 20 pair runners and trays to fit pastry trays (400x600mm) 	PNC 880333	
1/1GN plastic container with false bottom	PNC 880705	
• 2/1GN grey rilsan grid	PNC 881004	
• 2/1GN aisi 304 stainless steel grid	PNC 881016	
• 2/1GN 304 AISI stainless steel grid with 2 runners	PNC 881018	
• 2/1GN grey rilsan grid with 2 runners	PNC 881020	
 Set of 2 stainless steel runners for 670/1430lt refrigerators and freezers 	PNC 881021	
 Pedal opening for 1430lt refrigerator 	PNC 881033	
 2/1GN pvc container with lid and 2 runners 	PNC 881039	
 2/1GN perforated shelf 	PNC 881042	
• 1/1GN rilsan steel wire basket h=150mm	PNC 881043	
 3 grey rilsan central grids for 1430lt (not for glass door) 	PNC 881044	
• 2/1GN grey rilsan basket+2 runners h=150mm	PNC 881047	
• 5 swivelling wheels (2 with brake), diam 125mm, for 1430 It refrigerators, NOT for	PNC 881294	






ecostore 2 Door Dual Digital Stainless Steel Freezer, 1430lt (-22/-15) - Remote





Electrical inlet (power) Refrigerant Inlet RO Refrigerant Outlet



CE FECEE UK

Electric

Supply voltage:

727476 (RE4142FFR) 220-240 V/1 ph/50/60 Hz

Electrical power max.: 0.305 kW

Key Information:

Gross capacity: 1430 lt Door hinges: 1 Left+1 Right External dimensions, Width: 1441 mm External dimensions, Depth: 835 mm

External dimensions, Depth

with Doors Open: 1480 mm External dimensions, Height: 2050 mm Number and type of doors: 2 Full

Number and type of grids (included):

6 - GN 2/1 Type of external material: Stainless Steel Type of internal material: Stainless Steel Internal panels material: Stainless Steel Number of positions & pitch: 44; 30 mm

Refrigeration Data

Control type: Digital Refrigeration type: R404A;R452A

Suggested refrigeration

965 W power:

Condition at evaporation temperature:

-30 °C

Condition at condensation temperature:

Condition at ambient 32 °C temperature:

Connection pipes (remote) -

outlet:

*Note:

Side

Connection pipes (remote) -

inlet:

9.5 mm 6 mm

55 °C

Ref. Power calculated at a linear distance of 15 mt

(piping)