



## Eco Preparation 2000 mm Hot Cupboard with Upstand



132880 (MSR2017N)

Hot Cupboard, with 100mm upstand, 2000mm

### Short Form Specification

#### Item No.

Made entirely from stainless steel. Inner welded frame in stainless steel. Unique connection of panels to inner frame. Worktop in 304 AISI stainless steel (50mm high) incorporates a layer of sound deadening material and has upturned edges. Upstand (h=100m

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_

### Main Features

- Digital display thermostat to control the internal temperature.
- Model specific to keep dishes warm.
- Handles in stainless steel for better hygiene and reliability.
- Sturdiness, stability and reliability of table accurately tested.
- 100 mm upstand with 13mm depth and 10 mm radioused corner, designed to be used against a wall.

### Construction

- Inner welded frame in stainless steel to guarantee superior strength and stability.
- Handles directly built into the sliding doors.
- Equipped with intermediate shelf which can be positioned at three different heights.
- Intermediate shelf in stainless steel with riveted corners and trasversal reinforcement in stainless steel.
- Sturdy sound-deadened sliding doors on tracks located flush to the front of the frame.
- Easy access to the cupboard interior on all lengths guaranteed by the use of only 2 doors.
- Constructed entirely in stainless steel to offer maximum durability.
- Constructed entirely in stainless steel to offer maximum durability.
- Base panel has 40mm high profile, is 8/10 in thickness with upturned edges and bar reinforcement. It is welded to legs for further structure reinforcement.
- 304 AISI stainless steel feet, 150 mm high and 54 mm in diameter, adjustable by -35/+25 mm.
- 50 mm worktop in 304 AISI stainless steel.


### Optional Accessories

- Wheel kit for cupboards, 4 wheels (2 with brakes), D=100 mm PNC 855299

APPROVAL: \_\_\_\_\_



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)


**Electric**

**Supply voltage:** 220-240 V/1N ph/50/60 Hz  
**Total Watts:** 2.4 kW

**Key Information:**

**Cabinet width:** 1830 mm  
**Cabinet depth:** 645 mm  
**Cabinet height:** 610 mm  
**Cabinet temperature:** 50-75 °C  
**External dimensions, Width:** 2000 mm  
**External dimensions, Depth:** 700 mm  
**External dimensions, Height:** 1000 mm  
**Upstand Dimensions, Height:** 100 mm  
**Upstand Dimensions, Depth:** 13 mm  
**Upstand Dimensions, Radius:** R=10  
**Worktop thickness:** 50 mm  
**Net weight:** 75 kg