

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



217737 (ECOG101T3G30)

SkyLine PremiumS Combi Boiler Oven with touch screen control, 10x1/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, 3-glass door

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 4 automatic cycles (short, medium, intensive, rinse) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings
- Connectivity for real time access, remote software update, HACCP, recipe and energy management (optional)
- 6-point multi sensor core temperature probe
- Triple-glass door with double LED lights line.
- Stainless steel construction throughout
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- 6-point multi sensor core temperature probe for maximum precision and food safety (optional accessory).
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse) and integrated descale of the steam generator.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
 Steam cycle (100 °C): seafood and vegetables.

High temperature steam (101 °C - 130 °C).

- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) with 100+ different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants per family.
- Cycles
- Regeneration (ideal for banqueting on plate or rethermalizing on tray),
- Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,
- Proving cycle,
- EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,
- Sous-vide cooking,
- Static Combi (to reproduce traditional cooking from static oven),
- Pasteurization of pasta,
- Dehydration cycle (ideal for drying fruits, vegetables, meats, seafood),
- Food Safe Control (to automatically monitor safety of cooking process in compliance with







HACCP hygienic standards) Patented US6818865B2 and related family,

- Advanced Food Safe Control (to drive the cooking with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be grouped in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 60 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Automatic fast cool down and pre-heat function.
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- GreaseOut: integrated grease drain and collection kit (to use the kit, the oven must be ordered as special code).
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.

Construction


- Integrated spray gun with automatic retracting system for fast rinsing.
- Triple thermo-glazed door with 2 hinged inside panels for easy cleaning and double LED lights line.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Boiler in 316L AISI to protect against corrosion.
- IPX5 spray water protection certification for easy cleaning.

User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- Automatic consumption visualization at the end of the cycle.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Pictures upload for full customization of cooking cycles.

Sustainability

 Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).



- Reduced power function for customized slow cooking cycles.
- The outer cardboard packaging is made from 70% recycled materials and FSC*-certified paper, printed with ecofriendly, water-based ink to support sustainability and environmental responsibility.

(*Forest Stewardship Council is the world's leading organization for sustainable forest management).

• Triple-glass door minimize your energy loss.*

*Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20

- Uses 33% less water and 22% less detergent while cleaning, as compared to previous model.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.
- Zero Waste provides chefs with useful tips for minimizing food waste.

Zero Waste is a library of Automatic recipes that aims to:
-give a second life to raw food close to expiration date (e. g., from milk to yogurt)

- -öbtain genuine and tasty dishes from overripe fruit/ vegetables (usually considered not appropriate for sale)
 -promote the use of typically discarded food items (e.g., carrot peels).
- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.

Optional Accessories

grid 400x600mm

Optional Accessories		
• External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens	PNC 864388	
 Water filter with cartridge and flow meter for low steam usage (less than 2 hours of full steam per day) 	PNC 920004	
 Water filter with cartridge and flow meter for medium steam usage 	PNC 920005	
 Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one) 	PNC 922003	
 Pair of AISI 304 stainless steel grids, GN 1/1 	PNC 922017	
 Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922036	
• AISI 304 stainless steel grid, GN 1/1	PNC 922062	
 Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2 	PNC 922086	
 External side spray unit (needs to be mounted outside and includes support to be mounted on the oven) 	PNC 922171	
 Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm 	PNC 922189	
• Baking tray with 4 edges in perforated aluminum, 400x600x20mm	PNC 922190	
 Baking tray with 4 edges in aluminum, 400x600x20mm 	PNC 922191	
Pair of frying baskets	PNC 922239	
AISI 304 stainless steel bakery/pastry	PNC 922264	

SkyLine PremiumS Natural Gas Combi Oven 10GN1/1

















	Double stop door opening kit	PNC 922265		•	Trolley for mobile rack for 6 GN 1/1 on 6	PNC 922630	
	Double-step door opening kit Grid for whole chicken (8 per grid -	PNC 922266		(or 10 GN 1/1 ovens		
	1,2kg each), GN 1/1	1110 722200	_		Stainless steel drain kit for 6 & 10 GN oven, dia=50mm	PNC 922636	
	USB probe for sous-vide cooking	PNC 922281			Plastic drain kit for 6 &10 GN oven,	PNC 922637	
•	Grease collection tray, GN 1/1, H=100	PNC 922321			dia=50mm	1110 722007	_
	mm Kit universal skewer rack and 4 long	PNC 922324		• \	Wall support for 10 GN 1/1 oven	PNC 922645	
•	skewers for Lenghtwise ovens	FINC 922324	_		Banquet rack with wheels holding 30	PNC 922648	
•	Universal skewer rack	PNC 922326			plates for 10 GN 1/1 oven and blast chiller freezer, 65mm pitch		
•	4 long skewers	PNC 922327			Banquet rack with wheels 23 plates for	PNC 922649	
•	Grease collection tray, GN 1/1, H=40 mm	PNC 922329		1	10 GN 1/1 oven and blast chiller freezer, 85mm pitch	1110 /2204/	_
	Multipurpose hook	PNC 922348		•	Dehydration tray, GN 1/1, H=20mm	PNC 922651	
•	4 flanged feet for 6 & 10 GN , 2",	PNC 922351		•	Flat dehydration tray, GN 1/1	PNC 922652	
_	100-130mm	PNC 922362			Open base for 6 & 10 GN 1/1 oven,	PNC 922653	
	Grid for whole duck (8 per grid - 1,8kg each), GN 1/1			ſ	disassembled - NO accessory can be fitted with the exception of 922382		
	Thermal cover for 10 GN 1/1 oven and blast chiller freezer	PNC 922364		(Bakery/pastry rack kit for 10 GN 1/1 oven with 8 racks 400x600mm and	PNC 922656	
•	Tray support for 6 & 10 GN 1/1 disassembled open base	PNC 922382			80mm pitch Heat shield for stacked ovens 6 GN 1/1	PNC 922661	
	Wall mounted detergent tank holder	PNC 922386			on 10 GN 1/1	FINC 922001	_
	USB single point probe	PNC 922390	ā		Heat shield for 10 GN 1/1 oven	PNC 922663	
	4 service feet for 6 & 10 GN Oven,	PNC 922394		•	Kit to convert from natural gas to LPG	PNC 922670	
	100mm - Marine			•	Kit to convert from LPG to natural gas	PNC 922671	
•	loT module for OnE Connected (Combi	PNC 922421		•	Flue condenser for gas oven	PNC 922678	
	Ovens, Blast chiller/freezers, Rack Type DW) and SkyDuo (one IoT board per appliance - to connect oven to blast				Fixed tray rack for 10 GN 1/1 and 400x600mm grids	PNC 922685	
	chiller for Cook&Chill process).				Kit to fix oven to the wall	PNC 922687	
•	Connectivity router (WiFi and LAN)	PNC 922435			Tray support for 6 & 10 GN 1/1 oven	PNC 922690	
•	SkyDuo Kit - to connect oven and blast chiller freezer for Cook&Chill process.	PNC 922439		•	base 4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm	PNC 922693	
	The kit includes 2 boards and cables. Not for OnE Connected				Reinforced tray rack with wheels, lowest	PNC 922694	
	Grease collection kit for GN 1/1-2/1	PNC 922451			support dedicated to a grease	1110 /220/4	_
	open base (2 tanks, open/close device for drain)		_	-	collection tray for 10 GN 1/1 oven, 64mm pitch		
•	Grease collection kit for ovens GN 1/1 &	PNC 922452			Detergent tank holder for open base	PNC 922699	
	2/1 (2 plastic tanks, connection valve with pipe for drain)				Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base	PNC 922702	
•	Tray rack with wheels 10 GN 1/1, 65mm	PNC 922601			Wheels for stacked ovens	PNC 922704	
•	pitch Tray rack with wheels, 8 GN 1/1, 80mm	PNC 922602		• ;	Spit for lamb or suckling pig (up to 12kg) for GN 1/1 ovens	PNC 922709	
	pitch	DVIC 000 (00			Mesh grilling grid, GN 1/1	PNC 922713	
•	Bakery/pastry tray rack with wheels holding 400x600mm grids for 10 GN 1/1	PNC 922608			Probe holder for liquids	PNC 922714	
	oven and blast chiller freezer, 80mm pitch (8 runners)			(ovens ,	PNC 922728	
•	Slide-in rack with handle for 6 & 10 GN 1/1 oven	PNC 922610		(or 6+10 GN 1/1 ovens	PNC 922732	
•	Open base with tray support for 6 & 10 GN 1/1 oven	PNC 922612		1	Exhaust hood without fan for 6&10 1/1GN ovens	PNC 922733	
•	Cupboard base with tray support for 6 & 10 GN 1/1 oven	PNC 922614		(Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens	PNC 922737	
•	Hot cupboard base with tray support	PNC 922615			Fixed tray rack, 8 GN 1/1, 85mm pitch	PNC 922741 PNC 922742	
	for 6 & 10 GN 1/1 oven holding GN 1/1 or 400x600mm trays			• 4	Fixed tray rack, 8 GN 2/1, 85mm pitch 4 high adjustable feet for 6 & 10 GN	PNC 922742 PNC 922745	
•	External connection kit for liquid detergent and rinse aid	PNC 922618		•	ovens, 230-290mm Tray for traditional static cooking,	PNC 922746	
•	Stacking kit for 6 GN 1/1 oven placed on gas 10 GN 1/1 oven	PNC 922623			H=100mm Double-face griddle, one side ribbed	PNC 922747	
	Trolley for slide-in rack for 6 & 10 GN 1/1	PNC 922626			and one side smooth, 400x600mm		=
	oven and blast chiller freezer						













SkyLine PremiumS Natural Gas Combi Oven 10GN1/1



 Hood Hopper to directly connect the Hood to the centralized ventilation system, for Standard Hoods (with fan motor) and Hoods without fan motor 	PNC	922751	
Trolley for grease collection kit	PNC	922752	\Box
Water inlet pressure reducer		922773	$\overline{\Box}$
Extension for condensation tube, 37cm		922776	
•			
 Non-stick universal pan, GN 1/1, H=20mm 	PNC	925000	_
 Non-stick universal pan, GN 1/1, H=40mm 	PNC	925001	
 Non-stick universal pan, GN 1/1, H=60mm 	PNC	925002	
Double-face griddle, one side ribbed and one side smooth, GN 1/1	PNC	925003	
Aluminum grill, GN 1/1	PNC	925004	
 Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1 	PNC	925005	
• Flat baking tray with 2 edges, GN 1/1	PNC	925006	
Baking tray for 4 baguettes, GN 1/1	PNC	925007	
 Potato baker for 28 potatoes, GN 1/1 	PNC	925008	
Non-stick universal pan, GN 1/2, H=20mm		925009	
 Non-stick universal pan, GN 1/2, H=40mm 	PNC	925010	
 Non-stick universal pan, GN 1/2, H=60mm 	PNC	925011	
• Kit of 6 non-stick universal pans, GN 1/1, H=20mm	PNC	925012	
 Kit of 6 non-stick universal pans, GN 1/1, H=40mm 	PNC	925013	
• Kit of 6 non-stick universal pan GN 1/1, H=60mm	PNC	925014	
 Compatibility kit for installation on previous base GN 1/1 	PNC	930217	


















37 11/16 ° CWI1 CWI2 EI 13/16 a 15/16 "

CWII Cold Water inlet 1 (cleaning)

Drain DO Overflow drain pipe

= Cold Water Inlet 2 (steam generator) CWI2

> 20 15/16 ^s 532 mm D CWI1 **₹**000 ΕI 1 15/16 " 50 mm 1 15/16 ' 65 mm Ġ

Electric

Front

Side

Supply voltage: 220-240 V/1 ph/50 Hz

Electrical power, max: 1.1 kW Electrical power, default: 1.1 kW

Gas

Total thermal load: 105679 BTU (31 kW)

Natural Gas G20

Gas Power: 31 kW

Standard gas delivery: ISO 7/1 gas connection

1/2" MNPT diameter:

Water:

30 °C Inlet water temperature, max:

Inlet water pipe size (CWII,

3/4" CWI2): Pressure, min-max: 1-6 bar Chlorides: <17 ppm Conductivity: >50 µS/cm Drain "D": 50mm

Capacity:

Trays type: 10 (GN 1/1) Max load capacity: 50 kg

Key Information:

Right Side Door hinges: External dimensions, Width: 867 mm External dimensions, Depth: 775 mm 1058 mm External dimensions, Height: 159 kg Weight: 159 kg Net weight: Shipping weight: 177 kg Shipping volume: 1.11 m³

ISO Certificates

ISO 9001; ISO 14001; ISO ISO Standards: 45001; ISO 50001

Top

Electrical inlet (power)

Gas connection

