

SkyLine Premium Electric Combi Oven 10GN2/1, 230V

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



217809 (ECOE102B3C30)

SkyLine Premium Combi Boiler Oven with digital control, 10x2/1GN, electric, programmable, automatic cleaning, boiler in AISI 316L, 3-glass door - 230V

Short Form Specification

Item No.

Combi oven with digital interface with guided selection.

- Built-in steam generator (in s/s 316L) with real humidity control based upon Lambda Sensor.
- OptiFlow air distribution system to achieve maximum performance with 5 fan speed levels.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. metterei 4 automatic cycles (short, medium, intensive, rinse) .
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual (steam, combi and convection cycles); EcoDelta cooking cycle; Regeneration cycle.
- Automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings
- Connectivity for real time access, HACCP, recipe and energy management (optional)
- Single sensor core temperature probe.
- Triple-glass door with double LED lights line.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 2/1 GN, 67 mm pitch.

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (101 °C - 130 °C).
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse) and integrated descale of the steam generator.
- 6-point multi sensor core temperature probe for maximum precision and food safety (optional accessory).
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Pre-set program for Regeneration, ideal for banqueting on plate or rethermalizing on tray.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Automatic fast cool down and pre-heat function.
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- GreaseOut: integrated grease drain and collection kit (to use the kit, the oven must be ordered as special code).
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.

Construction

- Boiler in 316L AISI to protect against corrosion.
- Triple thermo-glazed door with 2 hinged inside panels for easy cleaning and double LED lights line.

APPROVAL:





SkyLine Premium Electric Combi Oven 10GN2/1, 230V

Pair of AISI 304 stainless steel grids,

perforated aluminum with silicon

Baking tray with 4 edges in perforated

Baking tray with 4 edges in aluminum,

AISI 304 stainless steel bakery/pastry

Grid for whole chicken (8 per grid -

• Kit universal skewer rack and 6 short

skewers for Lengthwise and Crosswise

• Baking tray for 5 baguettes in

coating, 400x600x38mm

aluminum, 400x600x20mm

Double-step door opening kit

4 flanged feet for 6 & 10 GN , 2",

Tray support for 6 & 10 GN 2/1

Wall mounted detergent tank holder

• IoT module for OnE Connected (Combi

appliance - to connect oven to blast

chiller for Cook&Chill process).

detergent and rinse aid

Connectivity router (WiFi and LAN)

Grease collection kit for GN 1/1-2/1

open base (2 tanks, open/close device

Ovens, Blast chiller/freezers, Rack Type DW) and SkyDuo (one IoT board per

disassembled open base

USB single point probe

Steam optimizer

for drain)

Grease collection tray, GN 2/1, H=60

Grid for whole duck (8 per grid - 1,8kg

Thermal cover for 10 GN 2/1 oven and

400x600x20mm

grid 400x600mm

1,2kg each), GN 1/1

• Universal skewer rack

· 6 short skewers

100-130mm

each), GN 1/1

blast chiller freezer

Multipurpose hook

• Pair of frying baskets

GN 2/1

 \Box

PNC 922175

PNC 922189

PNC 922190

PNC 922191

PNC 922239

PNC 922264

PNC 922265

PNC 922266

PNC 922325

PNC 922326

PNC 922328

PNC 922348

PNC 922351

PNC 922357

PNC 922362

PNC 922366

PNC 922384

PNC 922386

PNC 922390

PNC 922421

PNC 922435

PNC 922440

PNC 922451

- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.

User Interface & Data Management

- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).
- Digital interface with LED backlight buttons with guided selection.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).

Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related
- Energy Star 2.0 certified product.
- The outer cardboard packaging is made from 70% recycled materials and FSC*-certified paper, printed with eco-friendly, water-based ink to support sustainability and environmental responsibility.

(*Forest Stewardship Council is the world's leading organization for sustainable forest management).

- Triple-glass door minimize your energy loss.*
 - *Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20
- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.
- Reduced powerfunction for customized slow cooking cycles.

Optional Accessories		• Grease collection kit for ovens GN 1/1 &	DNC 022/52	
External reverse osmosis filter for single tank Dishwashers with atmosphere	PNC 864388	2/1 (2 plastic tanks, connection valve with pipe for drain)	1110 722432	•
boiler and Ovens	D110 000007	• Tray rack with wheels 10 GN 2/1, 65mm	PNC 922603	
Water filter with cartridge and flow mater for high stagm users (sombi	PNC 920003	pitch		
meter for high steam usage (combi used mainly in steaming mode)		 Tray rack with wheels, 8 GN 2/1, 80mm pitch 	PNC 922604	
 Water filter with cartridge and flow meter for medium steam usage 	PNC 920005	• Slide-in rack with handle for 6 & 10 GN 2/1 oven	PNC 922605	
 Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one) 	PNC 922003	Bakery/pastry tray rack with wheels 400x600mm for 10 GN 2/1 oven and blast chiller freezer, 80mm pitch (8)	PNC 922609	
 Pair of AISI 304 stainless steel grids, 	PNC 922017	runners)		
GN 1/1		• Open base with tray support for 6 & 10	PNC 922613	
 Pair of grids for whole chicken (8 per 	PNC 922036	GN 2/1 oven		
grid - 1,2kg each), GN 1/1		• Cupboard base with tray support for 6	PNC 922616	
 AISI 304 stainless steel grid, GN 1/1 	PNC 922062	& 10 GN 2/1 oven		
 AISI 304 stainless steel grid, GN 2/1 	PNC 922076	External connection kit for liquid	PNC 922618	





External side spray unit (needs to be

to be mounted on the oven)

mounted outside and includes support









PNC 922171



SkyLine Premium Electric Combi Oven 10GN2/1, 230V

 Stacking kit for 6 GN 2/1 oven placed on electric 10 GN 2/1 oven 	PNC 922621	 Non-stick universal pan, GN 1/1, H=40mm 	
Trolley for slide-in rack for 10 GN 2/1 oven and blast chiller freezer	PNC 922627	 Non-stick universal pan, GN 1/1, H=60mm PNC 925002 	
 Trolley for mobile rack for 6 GN 2/1 on 6 or 10 GN 2/1 ovens 	PNC 922631	 Double-face griddle, one side ribbed and one side smooth, GN 1/1 	
 Stainless steel drain kit for 6 & 10 GN oven, dia=50mm 	PNC 922636	 Aluminum grill, GN 1/1 PNC 925004 Frying pan for 8 eggs, pancakes, PNC 925005 	
 Plastic drain kit for 6 &10 GN oven, dia=50mm 	PNC 922637	hamburgers, GN 1/1 • Flat baking tray with 2 edges, GN 1/1 PNC 925006	
 Banquet rack with wheels holding 51 plates for 10 GN 2/1 oven and blast chiller freezer, 75mm pitch 	PNC 922650	 Potato baker for 28 potatoes, GN 1/1 PNC 925008 Kit of 6 non-stick universal pans, GN 1/1, PNC 925012 H=20mm 	
 Dehydration tray, GN 1/1, H=20mm 	PNC 922651	Kit of 6 non-stick universal pans, GN 1/1, PNC 925013	
 Flat dehydration tray, GN 1/1 	PNC 922652	H=40mm	
 Open base for 6 & 10 GN 2/1 oven, disassembled - NO accessory can be fitted with the exception of 922384 	PNC 922654	 Kit of 6 non-stick universal pan GN 1/1, H=60mm Compatibility kit for installation on PNC 930218 	
Heat shield for 10 GN 2/1 oven	PNC 922664	previous base GN 2/1	_
 Heat shield-stacked for ovens 6 GN 2/1 on 10 GN 2/1 	PNC 922667	'	
 Kit to fix oven to the wall 	PNC 922687		
 Tray support for 6 & 10 GN 2/1 oven base 	PNC 922692		
 4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm 	PNC 922693		
Detergent tank holder for open base	PNC 922699		
Mesh grilling grid, GN 1/1	PNC 922713		
Probe holder for liquids	PNC 922714		
 Odour reduction hood with fan for 6 & 10 GN 2/1 electric ovens 	PNC 922719		
 Odour reduction hood with fan for 6+6 or 6+10 GN 2/1 electric ovens 	PNC 922721		
 Condensation hood with fan for 6 & 10 GN 2/1 electric oven 	PNC 922724		
 Condensation hood with fan for stacking 6+6 or 6+10 GN 2/1 electric ovens 	PNC 922726		
 Exhaust hood with fan for 6 & 10 GN 2/1 GN ovens 			
 Exhaust hood with fan for stacking 6+6 or 6+10 GN 2/1 ovens 			
 Exhaust hood without fan for 6&10x2/1 GN oven 			
 Exhaust hood without fan for stacking 6+6 or 6+10 GN 2/1 ovens 	PNC 922736		
 4 high adjustable feet for 6 & 10 GN ovens, 230-290mm 	PNC 922745		
 Tray for traditional static cooking, H=100mm 	PNC 922746		
 Double-face griddle, one side ribbed and one side smooth, 400x600mm 	PNC 922747		
 Hood Hopper to directly connect the Hood to the centralized ventilation system, for Standard Hoods (with fan motor) and Hoods without fan motor 	PNC 922751		
Trolley for grease collection kit	PNC 922752		
 Water inlet pressure reducer 	PNC 922773		
 Kit for installation of electric power peak management system for 6 & 10 GN Oven 	PNC 922774		
• Extension for condensation tube, 37cm	PNC 922776		
 Non-stick universal pan, GN 1/1, H=20mm 	PNC 925000		

















SkyLine Premium Electric Combi Oven 10GN2/1, 230V






CWII Cold Water inlet 1 (cleaning) CWI2

= Cold Water Inlet 2 (steam generator)

DO Overflow drain pipe





220-240 V/3 ph/50-60 Hz Supply voltage:

30 °C

Electrical power, max: 40.1 kW Electrical power, default: 37.4 kW

Water:

Inlet water temperature, max:

Inlet water pipe size (CWI1, CWI2):

3/4" Pressure, min-max: 1-6 bar Chlorides: <85 ppm

Conductivity: >50 µS/cm Drain "D": 50mm

Capacity:

Trays type: 10 (GN 2/1) 100 kg Max load capacity:

Key Information:

Door hinges: Right Side External dimensions, Width: 1090 mm External dimensions, Depth: 971 mm External dimensions, Height: 1058 mm 179 kg Weight: Net weight: 179 kg Shipping weight: 313 kg Shipping volume: 1.59 m³

ISO Certificates

ISO 9001; ISO 14001; ISO 45001; ISO 50001 ISO Standards:











El = Electrical inlet (power)

