

SkyLine Premium Electric Combi Oven 10GN1/1 with left-hinged door

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



217829 (ECO101B2AL)

SkyLine Premium Combi Boiler Oven with digital control, 10x1/1GN, electric, programmable, automatic cleaning, left-hinged door

Short Form Specification

Item No.

- Combi oven with digital interface with guided selection.
- Built-in steam generator with real humidity control based upon Lambda Sensor.
 - OptiFlow air distribution system to achieve maximum performance with 5 fan speed levels.
 - SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
 - Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual (steam, combi and convection cycles); EcoDelta cooking cycle; Regeneration cycle.
 - Automatic backup mode to avoid downtime.
 - USB port to download HACCP data, programs and settings. Connectivity ready.
 - Single sensor core temperature probe.
 - Double-glass door with LED lights.
 - Stainless steel construction throughout.
 - Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C - 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C - 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C - 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
Steam cycle (100 °C): seafood and vegetables.
High temperature steam (101 °C - 130 °C).
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Pre-set program for Regeneration, ideal for banqueting on plate or rethermalizing on tray.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Automatic fast cool down and pre-heat function.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 10 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber.

APPROVAL: _____

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

User Interface & Data Management

- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Digital interface with LED backlight buttons with guided selection.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).

Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Reduced powerfunction for customized slow cooking cycles.

Optional Accessories

- | | | |
|--|------------|--------------------------|
| • External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens | PNC 864388 | ☐ |
| • Water filter with cartridge and flow meter for low steam usage (less than 2 hours of full steam per day) | PNC 920004 | ☐ |
| • Water filter with cartridge and flow meter for medium steam usage | PNC 920005 | ☐ |
| • Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one) | PNC 922003 | ☐ |
| • Pair of AISI 304 stainless steel grids, GN 1/1 | PNC 922017 | ☐ |
| • Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922036 | ☐ |
| • AISI 304 stainless steel grid, GN 1/1 | PNC 922062 | ☐ |
| • Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2 | PNC 922086 | ☐ |
| • External side spray unit (needs to be mounted outside and includes support to be mounted on the oven) | PNC 922171 | ☐ |
| • Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm | PNC 922189 | ☐ |
| • Baking tray with 4 edges in perforated aluminum, 400x600x20mm | PNC 922190 | ☐ |
| • Baking tray with 4 edges in aluminum, 400x600x20mm | PNC 922191 | ☐ |
| • Pair of frying baskets | PNC 922239 | ☐ |
| • AISI 304 stainless steel bakery/pastry grid 400x600mm | PNC 922264 | ☐ |
| • Double-step door opening kit | PNC 922265 | ☐ |

- | | | |
|--|------------|--------------------------|
| • Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922266 | ☐ |
| • Grease collection tray, GN 1/1, H=100 mm | PNC 922321 | ☐ |
| • Kit universal skewer rack and 4 long skewers for Lenghtwise ovens | PNC 922324 | ☐ |
| • Universal skewer rack | PNC 922326 | ☐ |
| • 4 long skewers | PNC 922327 | ☐ |
| • Multipurpose hook | PNC 922348 | ☐ |
| • 4 flanged feet for 6 & 10 GN , 2", 100-130mm | PNC 922351 | ☐ |
| • Grid for whole duck (8 per grid - 1,8kg each), GN 1/1 | PNC 922362 | ☐ |
| • Thermal cover for 10 GN 1/1 oven and blast chiller freezer | PNC 922364 | ☐ |
| • Tray support for 6 & 10 GN 1/1 disassembled open base | PNC 922382 | ☐ |
| • Wall mounted detergent tank holder | PNC 922386 | ☐ |
| • USB single point probe | PNC 922390 | ☐ |
| • IoT module for OnE Connected and SkyDuo (one IoT board per appliance - to connect oven to blast chiller for Cook&Chill process). | PNC 922421 | ☐ |
| • Connectivity router (WiFi and LAN) | PNC 922435 | ☐ |
| • Grease collection kit for ovens GN 1/1 & 2/1 (2 plastic tanks, connection valve with pipe for drain) | PNC 922438 | ☐ |
| • Tray rack with wheels 10 GN 1/1, 65mm pitch | PNC 922601 | ☐ |
| • Tray rack with wheels, 8 GN 1/1, 80mm pitch | PNC 922602 | ☐ |
| • Bakery/pastry tray rack with wheels holding 400x600mm grids for 10 GN 1/1 oven and blast chiller freezer, 80mm pitch (8 runners) | PNC 922608 | ☐ |
| • Slide-in rack with handle for 6 & 10 GN 1/1 oven | PNC 922610 | ☐ |
| • Open base with tray support for 6 & 10 GN 1/1 oven | PNC 922612 | ☐ |
| • Cupboard base with tray support for 6 & 10 GN 1/1 oven | PNC 922614 | ☐ |
| • Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or 400x600mm trays | PNC 922615 | ☐ |
| • External connection kit for liquid detergent and rinse aid | PNC 922618 | ☐ |
| • Grease collection kit for GN 1/1-2/1 cupboard base (trolley with 2 tanks, open/close device for drain) | PNC 922619 | ☐ |
| • Stacking kit for 6+6 GN 1/1 ovens on electric 6+10 GN 1/1 GN ovens | PNC 922620 | ☐ |
| • Trolley for slide-in rack for 6 & 10 GN 1/1 oven and blast chiller freezer | PNC 922626 | ☐ |
| • Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens | PNC 922630 | ☐ |
| • Stainless steel drain kit for 6 & 10 GN oven, dia=50mm | PNC 922636 | ☐ |
| • Plastic drain kit for 6 & 10 GN oven, dia=50mm | PNC 922637 | ☐ |
| • Trolley with 2 tanks for grease collection | PNC 922638 | ☐ |
| • Grease collection kit for GN 1/1-2/1 open base (2 tanks, open/close device for drain) | PNC 922639 | ☐ |

• Wall support for 10 GN 1/1 oven	PNC 922645	☐	• Kit for installation of electric power peak management system for 6 & 10 GN Oven	PNC 922774	☐
• Banquet rack with wheels holding 30 plates for 10 GN 1/1 oven and blast chiller freezer, 65mm pitch	PNC 922648	☐	• Extension for condensation tube, 37cm	PNC 922776	☐
• Banquet rack with wheels 23 plates for 10 GN 1/1 oven and blast chiller freezer, 85mm pitch	PNC 922649	☐	• Non-stick universal pan, GN 1/1, H=20mm	PNC 925000	☐
• Dehydration tray, GN 1/1, H=20mm	PNC 922651	☐	• Non-stick universal pan, GN 1/1, H=40mm	PNC 925001	☐
• Flat dehydration tray, GN 1/1	PNC 922652	☐	• Non-stick universal pan, GN 1/1, H=60mm	PNC 925002	☐
• Open base for 6 & 10 GN 1/1 oven, disassembled - NO accessory can be fitted with the exception of 922382	PNC 922653	☐	• Double-face griddle, one side ribbed and one side smooth, GN 1/1	PNC 925003	☐
• Bakery/pastry rack kit for 10 GN 1/1 oven with 8 racks 400x600mm and 80mm pitch	PNC 922656	☐	• Aluminum grill, GN 1/1	PNC 925004	☐
• Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1	PNC 922661	☐	• Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1	PNC 925005	☐
• Heat shield for 10 GN 1/1 oven	PNC 922663	☐	• Flat baking tray with 2 edges, GN 1/1	PNC 925006	☐
• Fixed tray rack for 10 GN 1/1 and 400x600mm grids	PNC 922685	☐	• Baking tray for 4 baguettes, GN 1/1	PNC 925007	☐
• Kit to fix oven to the wall	PNC 922687	☐	• Potato baker for 28 potatoes, GN 1/1	PNC 925008	☐
• Tray support for 6 & 10 GN 1/1 oven base	PNC 922690	☐	• Non-stick universal pan, GN 1/2, H=20mm	PNC 925009	☐
• 4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm	PNC 922693	☐	• Non-stick universal pan, GN 1/2, H=40mm	PNC 925010	☐
• Reinforced tray rack with wheels, lowest support dedicated to a grease collection tray for 10 GN 1/1 oven, 64mm pitch	PNC 922694	☐	• Non-stick universal pan, GN 1/2, H=60mm	PNC 925011	☐
• Detergent tank holder for open base	PNC 922699	☐	• Compatibility kit for installation on previous base GN 1/1	PNC 930217	☐
• Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base	PNC 922702	☐			
• Wheels for stacked ovens	PNC 922704	☐			
• Spit for lamb or suckling pig (up to 12kg) for GN 1/1 ovens	PNC 922709	☐			
• Mesh grilling grid, GN 1/1	PNC 922713	☐			
• Probe holder for liquids	PNC 922714	☐			
• Odour reduction hood with fan for 6 & 10 GN 1/1 electric ovens	PNC 922718	☐			
• Odour reduction hood with fan for 6+6 or 6+10 GN 1/1 electric ovens	PNC 922722	☐			
• Condensation hood with fan for 6 & 10 GN 1/1 electric oven	PNC 922723	☐			
• Condensation hood with fan for stacking 6+6 or 6+10 GN 1/1 electric ovens	PNC 922727	☐			
• Exhaust hood with fan for 6 & 10 GN 1/1 ovens	PNC 922728	☐			
• Exhaust hood with fan for stacking 6+6 or 6+10 GN 1/1 ovens	PNC 922732	☐			
• Exhaust hood without fan for 6&10 1/1GN ovens	PNC 922733	☐			
• Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens	PNC 922737	☐			
• Fixed tray rack, 8 GN 1/1, 85mm pitch	PNC 922741	☐			
• Fixed tray rack, 8 GN 2/1, 85mm pitch	PNC 922742	☐			
• 4 high adjustable feet for 6 & 10 GN ovens, 230-290mm	PNC 922745	☐			
• Tray for traditional static cooking, H=100mm	PNC 922746	☐			
• Double-face griddle, one side ribbed and one side smooth, 400x600mm	PNC 922747	☐			
• Trolley for grease collection kit	PNC 922752	☐			
• Water inlet pressure reducer	PNC 922773	☐			

Front




Side



CWI1 = Cold Water inlet 1 (cleaning) EI = Electrical inlet (power)
 CWI2 = Cold Water Inlet 2 (steam generator)
 D = Drain
 DO = Overflow drain pipe

Top



Electric

Circuit breaker required

Supply voltage: 380-415 V/3N ph/50-60 Hz
Electrical power, max: 20.3 kW
Electrical power, default: 19 kW

Gas

Natural gas:

Default power corresponds to factory test conditions. When supply voltage is declared as a range the test is performed at the average value. According to the country, the installed power may vary within the range.

Water:

Inlet water temperature, max: 30 °C
Inlet water pipe size (CWI1, CWI2): 3/4"
Pressure, min-max: 1-6 bar
Chlorides: <45 ppm
Conductivity: 0 µS/cm
Drain "D": 50mm
Electrolux Professional recommends the use of treated water, based on testing of specific water conditions. Please refer to user manual for detailed water quality information.

Installation:

Clearance: Clearance: 5 cm rear and right hand sides.
Suggested clearance for service access: 50 cm left hand side.

Capacity:

Trays type: 10 (GN 1/1)
Max load capacity: 50 kg

Key Information:

Door hinges: Left Side
External dimensions, Width: 867 mm
External dimensions, Depth: 775 mm
External dimensions, Height: 1058 mm
Weight: 138 kg
Net weight: 138 kg
Shipping weight: 154 kg
Shipping volume: 1.11 m³