

SkyLine Premium Natural Gas Combi Oven 10GN1/1, boiler AISI 316L

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		

217866	(ECOG101B3	G31)
--------	------------	------

SkyLine Premium Combi Boiler Oven with digital control, 10x1/1GN, gas, programmable, automatic cleaning, boiler in AISI 316L, 3-glass door

Short Form Specification

Item No.

Combi oven with digital interface with guided selection.

- Built-in steam generator (in s/s 316L) with real humidity control based upon Lambda Sensor.
- OptiFlow air distribution system to achieve maximum performance with 5 fan speed levels.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. metterei 4 automatic cycles (short, medium, intensive, rinse) .
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual (steam, combi and convection cycles); EcoDelta cooking cycle; Regeneration cycle.
- Automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings
- Connectivity for real time access, HACCP, recipe and energy management (optional)
- Single sensor core temperature probe.
- Triple-glass door with double LED lights line.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- Single sensor core temperature probe included.
- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (101 °C 130 °C).
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse) and integrated descale of the steam generator.
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Pre-set program for Regeneration, ideal for banqueting on plate or rethermalizing on tray.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Automatic fast cool down and pre-heat function.
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- GreaseOut: integrated grease drain and collection kit (to use the kit, the oven must be ordered as special code).
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.

Construction

- Boiler in 316L AISI to protect against corrosion.
- Triple thermo-glazed door with 2 hinged inside panels for easy cleaning and double LED lights line.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.

APPROVAL:





SkyLine Premium Natural Gas Combi Oven 10GN1/1, boiler AISI 316L

Baking tray with 4 edges in perforated PNC 922190

- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.

User Interface & Data Management

- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).
- Digital interface with LED backlight buttons with guided selection.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).

Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related
- Reduced powerfunction for customized slow cooking cycles.
- The outer cardboard packaging is made from 70% recycled materials and FSC*-certified paper, printed with ecofriendly, water-based ink to support sustainability and environmental responsibility.

(*Forest Stewardship Council is the world's leading organization for sustainable forest management).

- Triple-glass door minimize your energy loss.*
 - *Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20
- Uses 33% less water and 22% less detergent while cleaning, as compared to previous model.
- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.

Optional Accessories

• External reverse osmosis filter for single PNC 864388 tank Dishwashers with atmosphere boiler and Ovens • Water filter with cartridge and flow PNC 920004 meter for low steam usage (less than 2 hours of full steam per day) PNC 920005 Water filter with cartridge and flow meter for medium steam usage Wheel kit for 6 & 10 GN 1/1 and 2/1 GN PNC 922003 oven base (not for the disassembled one) • Pair of AISI 304 stainless steel grids, PNC 922017 GN 1/1 Pair of grids for whole chicken (8 per PNC 922036 grid - 1,2kg each), GN 1/1 AISI 304 stainless steel grid, GN 1/1 PNC 922062 Grid for whole chicken (4 per grid -PNC 922086 1,2kg each), GN 1/2 • External side spray unit (needs to be PNC 922171 mounted outside and includes support

 Baking tray with 4 edges in perforated aluminum, 400x600x20mm 	PNC 922190	П
Baking tray with 4 edges in aluminum, 400x600x20mm	PNC 922191	
 Pair of frying baskets 	PNC 922239	
 AISI 304 stainless steel bakery/pastry grid 400x600mm 	PNC 922264	
Double-step door opening kit	PNC 922265	
 Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922266	
Grease collection tray, GN 1/1, H=100 mm	PNC 922321	
 Kit universal skewer rack and 4 long skewers for Lenghtwise ovens 	PNC 922324	
Universal skewer rack	PNC 922326	
• 4 long skewers	PNC 922327	
Grease collection tray, GN 1/1, H=40 mm	PNC 922329	
Multipurpose hook	PNC 922348	
 4 flanged feet for 6 & 10 GN , 2", 100-130mm 	PNC 922351	
 Grid for whole duck (8 per grid - 1,8kg each), GN 1/1 	PNC 922362	
 Thermal cover for 10 GN 1/1 oven and blast chiller freezer 	PNC 922364	
 Tray support for 6 & 10 GN 1/1 disassembled open base 	PNC 922382	
Wall mounted detergent tank holder	PNC 922386	
 USB single point probe 	PNC 922390	
 4 service feet for 6 & 10 GN Oven, 	PNC 922394	
 100mm - Marine 10T module for OnE Connected and SkyDuo (one 10T board per appliance - to connect oven to blast chiller for 	PNC 922421	
Cook&Chill process).		
 Connectivity router (WiFi and LAN) 	PNC 922435	
 Grease collection kit for ovens GN 1/1 & 2/1 (2 plastic tanks, connection valve with pipe for drain) 	PNC 922438	
Steam optimizer	PNC 922440	
 GREASE COLLECTION KIT FOR OVEN OPEN BASE GN 1/1-2/1 (2 TANKS, 	PNC 922451	
 OPEN/CLOSE DEVICE FOR DRAIN) GREASE COLLECTION KIT FOR OVENS GN 1/1-2/1 (2 PLASTIC TANKS, CONNECTION VALVE WITH PIPE FOR 	PNC 922452	
DRAIN) Tray rack with wheels 10 GN 1/1, 65mm	PNC 922601	
pitch • Tray rack with wheels, 8 GN 1/1, 80mm	PNC 922602	
pitch • Bakery/pastry tray rack with wheels	PNC 922608	
 Bakery/pastry tray rack with wheels holding 400x600mm grids for 10 GN 1/1 oven and blast chiller freezer, 80mm pitch (8 runners) 	1 140 722000	J
 Slide-in rack with handle for 6 & 10 GN 1/1 oven 	PNC 922610	
• Open base with tray support for 6 & 10 GN 1/1 oven	PNC 922612	
• Cupboard base with tray support for 6	PNC 922614	







to be mounted on the oven) • Baking tray for 5 baguettes in

perforated aluminum with silicon coating, 400x600x38mm









PNC 922189

SkyLine Premium Natural Gas Combi Oven 10GN1/1, boiler AISI 316L

& 10 GN 1/1 oven



SkyLine Premium Natural Gas Combi Oven 10GN1/1, boiler AISI 316L

•	Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or	PNC 922615		• Exhaust hood with fan for stacking 6+6 PNC 922732 or 6+10 GN 1/1 ovens	
•	400x600mm trays External connection kit for liquid	PNC 922618		• Exhaust hood without fan for 6&10 PNC 922733 1/1GN ovens	
	detergent and rinse aid Grease collection kit for GN 1/1-2/1	PNC 922619	_	• Exhaust hood without fan for stacking PNC 922737 6+6 or 6+10 GN 1/1 ovens	
•	cupboard base (trolley with 2 tanks,	1110 /2201/	_	• Fixed tray rack, 8 GN 1/1, 85mm pitch PNC 922741	
	open/close device for drain)			• Fixed tray rack, 8 GN 2/1, 85mm pitch PNC 922742	ū
•	Stacking kit for 6 GN 1/1 oven placed on gas 10 GN 1/1 oven	PNC 922623		4 high adjustable feet for 6 & 10 GN Ovens, 230-290mm PNC 922745	
•	Trolley for slide-in rack for 6 & 10 GN 1/1 oven and blast chiller freezer	PNC 922626		• Tray for traditional static cooking, PNC 922746 H=100mm	
•	Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens	PNC 922630		Double-face griddle, one side ribbed PNC 922747 and one side smooth, 400x600mm	
•	Stainless steel drain kit for 6 & 10 GN oven, dia=50mm	PNC 922636		Hood Hopper to directly connect the Hood to the centralized ventilation	
•	Plastic drain kit for 6 &10 GN oven, dia=50mm	PNC 922637		system, for Standard Hoods (with fan motor) and Hoods without fan motor	
•	Grease collection kit for GN 1/1-2/1	PNC 922639		• Trolley for grease collection kit PNC 922752	
	open base (2 tanks, open/close device			• Water inlet pressure reducer PNC 922773	
	for drain)			• Extension for condensation tube, 37cm PNC 922776	
•	Wall support for 10 GN 1/1 oven	PNC 922645		• Non-stick universal pan, GN 1/1, PNC 925000	
•	Banquet rack with wheels holding 30	PNC 922648		H=20mm	_
	plates for 10 GN 1/1 oven and blast chiller freezer, 65mm pitch			Non-stick universal pan, GN 1/1, PNC 925001 H=40mm	
•	Banquet rack with wheels 23 plates for 10 GN 1/1 oven and blast chiller freezer, 85mm pitch	PNC 922649		• Non-stick universal pan, GN 1/1, PNC 925002 H=60mm	
_	Dehydration tray, GN 1/1, H=20mm	PNC 922651		• Double-face griddle, one side ribbed PNC 925003	
				and one side smooth, GN 1/1	
	Flat dehydration tray, GN 1/1	PNC 922652		• Aluminum grill, GN 1/1 PNC 925004	
•	Open base for 6 & 10 GN 1/1 oven, disassembled - NO accessory can be fitted with the exception of 922382	PNC 922653		• Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1 PNC 925005	
•	Bakery/pastry rack kit for 10 GN 1/1	PNC 922656		• Flat baking tray with 2 edges, GN 1/1 PNC 925006	
	oven with 8 racks 400x600mm and	1110 722000	_	• Baking tray for 4 baguettes, GN 1/1 PNC 925007	
	80mm pitch			• Potato baker for 28 potatoes, GN 1/1 PNC 925008	
•	Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1	PNC 922661		• Non-stick universal pan, GN 1/2, PNC 925009 H=20mm	
•	Heat shield for 10 GN 1/1 oven	PNC 922663		• Non-stick universal pan, GN 1/2, PNC 925010	
•	Kit to convert from natural gas to LPG	PNC 922670		H=40mm	
	Kit to convert from LPG to natural gas	PNC 922671		 Non-stick universal pan, GN 1/2, PNC 925011 	
	•	PNC 922678		H=60mm	
	Flue condenser for gas oven			• Kit of 6 non-stick universal pans, GN 1/1, PNC 925012	
	Fixed tray rack for 10 GN 1/1 and 400x600mm grids	PNC 922685		H=20mm • Kit of 6 non-stick universal pans, GN 1/1, PNC 925013	
	Kit to fix oven to the wall	PNC 922687		H=40mm	
	Tray support for 6 & 10 GN 1/1 oven base	PNC 922690		• Kit of 6 non-stick universal pan GN 1/1, PNC 925014 H=60mm	
	4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm			 Compatibility kit for installation on previous base GN 1/1 	
•	Reinforced tray rack with wheels, lowest support dedicated to a grease collection tray for 10 GN 1/1 oven, 64mm pitch				
•	Detergent tank holder for open base	PNC 922699			
	Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base	PNC 922702			
•	Wheels for stacked ovens	PNC 922704			
	Spit for lamb or suckling pig (up to 12kg) for GN 1/1 ovens	PNC 922709			
•	Mesh grilling grid, GN 1/1	PNC 922713			
	Probe holder for liquids	PNC 922714			
	Exhaust hood with fan for 6 & 10 GN 1/1				
•	ovens	1110 722/20	J		

















SkyLine Premium Natural Gas Combi Oven 10GN1/1, boiler AISI 316L





CWII Cold Water inlet 1 (cleaning) CWI2

= Cold Water Inlet 2 (steam generator) Drain

DO Overflow drain pipe

> 20 15/16 ^s 532 mm D CWI1 **₹**000 CWI2 ΕI 1 15/16 " 50 mm 1 15/16 ' 65 mm Ġ



Front

Side

Top

Supply voltage: 220-240 V/1 ph/50 Hz

Electrical power, max: 1.1 kW Electrical power, default: 1.1 kW

Gas

Total thermal load: 124538 BTU (31 kW)

Gas Power: 31 kW

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection

1/2" MNPT diameter:

Water:

Inlet water temperature, max: 30 °C

Inlet water pipe size (CWII,

3/4" CWI2):

Pressure, min-max: 1-6 bar Chlorides: <20 ppm Conductivity: >50 µS/cm Drain "D": 50mm

Capacity:

Trays type: 10 (GN 1/1) Max load capacity: 50 kg

Key Information:

Right Side Door hinges: External dimensions, Width: 867 mm External dimensions, Depth: 775 mm 1058 mm External dimensions, Height: 156 kg Weight: 156 kg Net weight: Shipping weight: 194 kg

Shipping volume: **ISO Certificates**

ISO 9001; ISO 14001; ISO ISO Standards:

45001; ISO 50001

1.11 m³













Gas connection

