

SkyLine Premium Natural Gas Combi Oven 10GN2/1, 60 Hz

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


225969 (ECOG102B3V30)

SkyLine Premium Combi Boiler Oven with digital control, 10x2/1GN, gas, programmable, automatic cleaning, 3-glass door - 60Hz

Short Form Specification

Item No. _____

Combi oven with digital interface with guided selection.

- Built-in steam generator with real humidity control based upon Lambda Sensor.
- OptiFlow air distribution system to achieve maximum performance with 5 fan speed levels.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. metterei 4 automatic cycles (short, medium, intensive, rinse) .
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual (steam, combi and convection cycles); EcoDelta cooking cycle; Regeneration cycle.
- Automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings - Connectivity for real time access, HACCP, recipe and energy management (optional)
- Single sensor core temperature probe.
- Triple-glass door with double LED lights line.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 2/1 GN, 67 mm pitch.

Main Features

- Single sensor core temperature probe included.
- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C - 300 °C): ideal for low humidity cooking.
- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.
- Combination cycle (25 °C - 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C - 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
Steam cycle (100 °C): seafood and vegetables.
High temperature steam (101 °C - 130 °C).
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse) and integrated descale of the steam generator.
- 6-point multi sensor core temperature probe for maximum precision and food safety (optional accessory).
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Pre-set program for Regeneration, ideal for banqueting on plate or rethermalizing on tray.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Automatic fast cool down and pre-heat function.
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- GreaseOut: integrated grease drain and collection kit (to use the kit, the oven must be ordered as special code).
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.

Construction

- Triple thermo-glazed door with 2 hinged inside panels for easy cleaning and double LED lights line.
- Hygienic internal chamber with all rounded corners for easy cleaning.

APPROVAL: _____

- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.

User Interface & Data Management

- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).
- Digital interface with LED backlight buttons with guided selection.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).

Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Energy Star 2.0 certified product.
- The outer cardboard packaging is made from 70% recycled materials and FSC*-certified paper, printed with eco-friendly, water-based ink to support sustainability and environmental responsibility.

(*Forest Stewardship Council is the world's leading organization for sustainable forest management).

- Triple-glass door minimize your energy loss.*

*Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20

- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.
- Reduced powerfunction for customized slow cooking cycles.

Optional Accessories

- | | | |
|---|------------|--------------------------|
| • External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens | PNC 864388 | ☐ |
| • Water filter with cartridge and flow meter for high steam usage (combi used mainly in steaming mode) | PNC 920003 | ☐ |
| • Water filter with cartridge and flow meter for medium steam usage | PNC 920005 | ☐ |
| • Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one) | PNC 922003 | ☐ |
| • Pair of AISI 304 stainless steel grids, GN 1/1 | PNC 922017 | ☐ |
| • Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922036 | ☐ |
| • AISI 304 stainless steel grid, GN 1/1 | PNC 922062 | ☐ |
| • AISI 304 stainless steel grid, GN 2/1 | PNC 922076 | ☐ |
| • External side spray unit (needs to be mounted outside and includes support to be mounted on the oven) | PNC 922171 | ☐ |
| • Pair of AISI 304 stainless steel grids, GN 2/1 | PNC 922175 | ☐ |

- | | | |
|--|------------|--------------------------|
| • Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm | PNC 922189 | ☐ |
| • Baking tray with 4 edges in perforated aluminum, 400x600x20mm | PNC 922190 | ☐ |
| • Baking tray with 4 edges in aluminum, 400x600x20mm | PNC 922191 | ☐ |
| • Pair of frying baskets | PNC 922239 | ☐ |
| • AISI 304 stainless steel bakery/pastry grid 400x600mm | PNC 922264 | ☐ |
| • Double-step door opening kit | PNC 922265 | ☐ |
| • Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922266 | ☐ |
| • Kit universal skewer rack and 6 short skewers for Lengthwise and Crosswise ovens | PNC 922325 | ☐ |
| • Universal skewer rack | PNC 922326 | ☐ |
| • 6 short skewers | PNC 922328 | ☐ |
| • Multipurpose hook | PNC 922348 | ☐ |
| • 4 flanged feet for 6 & 10 GN , 2", 100-130mm | PNC 922351 | ☐ |
| • Grease collection tray, GN 2/1, H=60 mm | PNC 922357 | ☐ |
| • Grid for whole duck (8 per grid - 1,8kg each), GN 1/1 | PNC 922362 | ☐ |
| • Thermal cover for 10 GN 2/1 oven and blast chiller freezer | PNC 922366 | ☐ |
| • Tray support for 6 & 10 GN 2/1 disassembled open base | PNC 922384 | ☐ |
| • Wall mounted detergent tank holder | PNC 922386 | ☐ |
| • USB single point probe | PNC 922390 | ☐ |
| • IoT module for OnE Connected (Combi Ovens, Blast chiller/freezers, Rack Type DW) and SkyDuo (one IoT board per appliance - to connect oven to blast chiller for Cook&Chill process). | PNC 922421 | ☐ |
| • Connectivity router (WiFi and LAN) | PNC 922435 | ☐ |
| • Steam optimizer | PNC 922440 | ☐ |
| • Grease collection kit for GN 1/1-2/1 open base (2 tanks, open/close device for drain) | PNC 922451 | ☐ |
| • Grease collection kit for ovens GN 1/1 & 2/1 (2 plastic tanks, connection valve with pipe for drain) | PNC 922452 | ☐ |
| • Tray rack with wheels 10 GN 2/1, 65mm pitch | PNC 922603 | ☐ |
| • Tray rack with wheels, 8 GN 2/1, 80mm pitch | PNC 922604 | ☐ |
| • Slide-in rack with handle for 6 & 10 GN 2/1 oven | PNC 922605 | ☐ |
| • Bakery/pastry tray rack with wheels 400x600mm for 10 GN 2/1 oven and blast chiller freezer, 80mm pitch (8 runners) | PNC 922609 | ☐ |
| • Open base with tray support for 6 & 10 GN 2/1 oven | PNC 922613 | ☐ |
| • External connection kit for liquid detergent and rinse aid | PNC 922618 | ☐ |
| • Stacking kit for 6 GN 2/1 oven placed on gas 6 GN 2/1 oven | PNC 922625 | ☐ |
| • Trolley for slide-in rack for 10 GN 2/1 oven and blast chiller freezer | PNC 922627 | ☐ |




• Trolley for mobile rack for 6 GN 2/1 on 6 or 10 GN 2/1 ovens	PNC 922631	☐	• Kit of 6 non-stick universal pans, GN 1/1, H=20mm	PNC 925012	☐
• Stainless steel drain kit for 6 & 10 GN oven, dia=50mm	PNC 922636	☐	• Kit of 6 non-stick universal pans, GN 1/1, H=40mm	PNC 925013	☐
• Plastic drain kit for 6 & 10 GN oven, dia=50mm	PNC 922637	☐	• Kit of 6 non-stick universal pan GN 1/1, H=60mm	PNC 925014	☐
• Banquet rack with wheels holding 51 plates for 10 GN 2/1 oven and blast chiller freezer, 75mm pitch	PNC 922650	☐	Recommended Detergents		
• Dehydration tray, GN 1/1, H=20mm	PNC 922651	☐	• C25 Rinse & Descale Tabs, phosphate-free, phosphorous-free, maleic acid-free, 50 tabs bucket	PNC 0S2394	☐
• Flat dehydration tray, GN 1/1	PNC 922652	☐	• C22 Cleaning Tabs, phosphate-free, phosphorous-free, 100 bags bucket	PNC 0S2395	☐
• Open base for 6 & 10 GN 2/1 oven, disassembled - NO accessory can be fitted with the exception of 922384	PNC 922654	☐			
• Heat shield for 10 GN 2/1 oven	PNC 922664	☐			
• Heat shield-stacked for ovens 6 GN 2/1 on 10 GN 2/1	PNC 922667	☐			
• Kit to convert from natural gas to LPG	PNC 922670	☐			
• Kit to convert from LPG to natural gas	PNC 922671	☐			
• Flue condenser for gas oven	PNC 922678	☐			
• Kit to fix oven to the wall	PNC 922687	☐			
• Tray support for 6 & 10 GN 2/1 oven base	PNC 922692	☐			
• 4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm	PNC 922693	☐			
• Detergent tank holder for open base	PNC 922699	☐			
• Mesh grilling grid, GN 1/1	PNC 922713	☐			
• Probe holder for liquids	PNC 922714	☐			
• Exhaust hood with fan for 6 & 10 GN 2/1 GN ovens	PNC 922729	☐			
• Exhaust hood with fan for stacking 6+6 or 6+10 GN 2/1 ovens	PNC 922731	☐			
• Exhaust hood without fan for 6&10x2/1 GN oven	PNC 922734	☐			
• Exhaust hood without fan for stacking 6+6 or 6+10 GN 2/1 ovens	PNC 922736	☐			
• 4 high adjustable feet for 6 & 10 GN ovens, 230-290mm	PNC 922745	☐			
• Tray for traditional static cooking, H=100mm	PNC 922746	☐			
• Double-face griddle, one side ribbed and one side smooth, 400x600mm	PNC 922747	☐			
• Hood Hopper to directly connect the Hood to the centralized ventilation system, for Standard Hoods (with fan motor) and Hoods without fan motor	PNC 922751	☐			
• Trolley for grease collection kit	PNC 922752	☐			
• Water inlet pressure reducer	PNC 922773	☐			
• Extension for condensation tube, 37cm	PNC 922776	☐			
• Non-stick universal pan, GN 1/1, H=20mm	PNC 925000	☐			
• Non-stick universal pan, GN 1/1, H=40mm	PNC 925001	☐			
• Non-stick universal pan, GN 1/1, H=60mm	PNC 925002	☐			
• Double-face griddle, one side ribbed and one side smooth, GN 1/1	PNC 925003	☐			
• Aluminum grill, GN 1/1	PNC 925004	☐			
• Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1	PNC 925005	☐			
• Flat baking tray with 2 edges, GN 1/1	PNC 925006	☐			
• Potato baker for 28 potatoes, GN 1/1	PNC 925008	☐			




Electrolux
PROFESSIONAL

SkyLine Premium Natural Gas Combi Oven 10GN2/1, 60 Hz

Front




Side



- CW1 = Cold Water Inlet 1 (cleaning) EI = Electrical inlet (power)
 CW2 = Cold Water Inlet 2 (steam generator) G = Gas connection
 D = Drain
 DO = Overflow drain pipe

Top



Electric

Supply voltage:	220-230 V/1 ph/60 Hz
Electrical power, max:	1.5 kW
Electrical power, default:	1.5 kW

Gas

Total thermal load:	189025 BTU (47 kW)
Gas Power:	47 kW
Standard gas delivery:	Natural Gas G20
ISO 7/1 gas connection diameter:	1/2" MNPT

Water:

Inlet water temperature, max:	30 °C
Inlet water pipe size (CW1, CW2):	3/4"
Pressure, min-max:	1-6 bar
Chlorides:	<17 ppm
Conductivity:	0 µS/cm
Drain "D":	50mm

Capacity:

Trays type:	10 (GN 2/1)
Max load capacity:	100 kg

Key Information:

Door hinges:	Right Side
External dimensions, Width:	1090 mm
External dimensions, Depth:	971 mm
External dimensions, Height:	1058 mm
Weight:	223 kg
Net weight:	198 kg
Shipping weight:	223 kg
Shipping volume:	1.59 m ³

ISO Certificates

ISO Standards:	ISO 9001; ISO 14001; ISO 45001; ISO 50001
----------------	---

SkyLine Premium
Natural Gas Combi Oven 10GN2/1, 60 Hz

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.01.11

