

## SkyLine PremiumS Electric Combi Oven 10GN1/1

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_


**229747 (ECOE10IT3C30)**

SkyLine PremiumS Combi Boiler Oven with touch screen control, 10x1/1GN, electric, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, boiler in AISI 316L, 3-glass door - 230V

### Short Form Specification

#### Item No. \_\_\_\_\_

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator (in s/s 316L) with real humidity control based upon Lambda Sensor.
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 4 automatic cycles (short, medium, intensive, rinse) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings
- Connectivity for real time access, remote software update, HACCP, recipe and energy management (optional)
- 6-point multi sensor core temperature probe
- Triple-glass door with double LED lights line
- Stainless steel construction throughout
- Supplied with n.1 tray rack 1/1GN, 67mm pitch

### Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Dry, hot convection cycle (25 °C - 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C - 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse) and integrated descale of the steam generator.
- Low temperature Steam cycle (25 °C - 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.  
Steam cycle (100 °C): seafood and vegetables.  
High temperature steam (101 °C - 130 °C).
- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) with 100+ different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants per family.
- Cycles :
  - Regeneration (ideal for banqueting on plate or rethermalizing on tray),
  - Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,
  - Proving cycle,
  - EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,
  - Sous-vide cooking,
  - Static Combi (to reproduce traditional cooking from static oven),
  - Pasteurization of pasta,
  - Dehydration cycle (ideal for drying fruits, vegetables, meats, seafood),
  - Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family,
  - Advanced Food Safe Control (to drive the cooking

**APPROVAL:** \_\_\_\_\_

with pasteurization factor).

- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be grouped in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 60 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Automatic fast cool down and pre-heat function.
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- GreaseOut: integrated grease drain and collection kit (to use the kit, the oven must be ordered as special code).
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.

### Construction

- Integrated spray gun with automatic retracting system for fast rinsing.
- Boiler in 316L AISI to protect against corrosion.
- Triple thermo-glazed door with 2 hinged inside panels for easy cleaning and double LED lights line.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.

### User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).
- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).
- Pictures upload for full customization of cooking cycles.

### Sustainability

- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Reduced powerfunction for customized slow cooking cycles.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a

time and energy efficiency point of view.

- Energy Star 2.0 certified product.
- Zero Waste provides chefs with useful tips for minimizing food waste.  
Zero Waste is a library of Automatic recipes that aims to:  
- give a second life to raw food close to expiration date (e.g., from milk to yogurt)  
- obtain genuine and tasty dishes from overripe fruit/vegetables (usually considered not appropriate for sale)  
- promote the use of typically discarded food items (e.g., carrot peels).
- The outer cardboard packaging is made from 70% recycled materials and FSC\*-certified paper, printed with eco-friendly, water-based ink to support sustainability and environmental responsibility.

(\*Forest Stewardship Council is the world's leading organization for sustainable forest management).

- Triple-glass door minimize your energy loss.\*

\*Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20

- Save up to 50% on running costs with Eco cleaning cycles!\*

\*Based on Internal tests done in Electrolux Professional Laboratory in a SkyLine PremiumS Combi Oven electric 10 GN 1/1 comparing Standard Intensive cycle versus Eco Intensive cycle with all green features activated. Test performed using Italy 2025 as case for water, energy and detergent cost.

- Uses 33% less water and 22% less detergent while cleaning, as compared to previous model.
- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.

### Optional Accessories

|                                                                                                                                    |            |                          |
|------------------------------------------------------------------------------------------------------------------------------------|------------|--------------------------|
| • External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens                                     | PNC 864388 | <input type="checkbox"/> |
| • Water filter with cartridge and flow meter for low steam usage (less than 2 hours of full steam per day)                         | PNC 920004 | <input type="checkbox"/> |
| • Water filter with cartridge and flow meter for medium steam usage                                                                | PNC 920005 | <input type="checkbox"/> |
| • Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one)                                                  | PNC 922003 | <input type="checkbox"/> |
| • Pair of AISI 304 stainless steel grids, GN 1/1                                                                                   | PNC 922017 | <input type="checkbox"/> |
| • Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1                                                                | PNC 922036 | <input type="checkbox"/> |
| • AISI 304 stainless steel grid, GN 1/1                                                                                            | PNC 922062 | <input type="checkbox"/> |
| • Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2                                                                         | PNC 922086 | <input type="checkbox"/> |
| • External side spray unit (needs to be mounted outside and includes support to be mounted on the oven)                            | PNC 922171 | <input type="checkbox"/> |
| • Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm                                            | PNC 922189 | <input type="checkbox"/> |
| • Baking tray with 4 edges in perforated aluminum, 400x600x20mm                                                                    | PNC 922190 | <input type="checkbox"/> |
| • Baking tray with 4 edges in aluminum, 400x600x20mm                                                                               | PNC 922191 | <input type="checkbox"/> |
| • Pair of frying baskets                                                                                                           | PNC 922239 | <input type="checkbox"/> |
| • AISI 304 stainless steel bakery/pastry grid 400x600mm                                                                            | PNC 922264 | <input type="checkbox"/> |
| • Double-step door opening kit                                                                                                     | PNC 922265 | <input type="checkbox"/> |
| • Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1                                                                         | PNC 922266 | <input type="checkbox"/> |
| • USB probe for sous-vide cooking                                                                                                  | PNC 922281 | <input type="checkbox"/> |
| • Grease collection tray, GN 1/1, H=100 mm                                                                                         | PNC 922321 | <input type="checkbox"/> |
| • Kit universal skewer rack and 4 long skewers for Lenghtwise ovens                                                                | PNC 922324 | <input type="checkbox"/> |
| • Universal skewer rack                                                                                                            | PNC 922326 | <input type="checkbox"/> |
| • 4 long skewers                                                                                                                   | PNC 922327 | <input type="checkbox"/> |
| • Grease collection tray, GN 1/1, H=40 mm                                                                                          | PNC 922329 | <input type="checkbox"/> |
| • Multipurpose hook                                                                                                                | PNC 922348 | <input type="checkbox"/> |
| • 4 flanged feet for 6 & 10 GN , 2", 100-130mm                                                                                     | PNC 922351 | <input type="checkbox"/> |
| • Grid for whole duck (8 per grid - 1,8kg each), GN 1/1                                                                            | PNC 922362 | <input type="checkbox"/> |
| • Thermal cover for 10 GN 1/1 oven and blast chiller freezer                                                                       | PNC 922364 | <input type="checkbox"/> |
| • Tray support for 6 & 10 GN 1/1 disassembled open base                                                                            | PNC 922382 | <input type="checkbox"/> |
| • Wall mounted detergent tank holder                                                                                               | PNC 922386 | <input type="checkbox"/> |
| • USB single point probe                                                                                                           | PNC 922390 | <input type="checkbox"/> |
| • 4 service feet for 6 & 10 GN Oven, 100mm - Marine                                                                                | PNC 922394 | <input type="checkbox"/> |
| • IoT module for OnE Connected and SkyDuo (one IoT board per appliance - to connect oven to blast chiller for Cook&Chill process). | PNC 922421 | <input type="checkbox"/> |
| • Connectivity router (WiFi and LAN)                                                                                               | PNC 922435 | <input type="checkbox"/> |
| • Grease collection kit for ovens GN 1/1 & 2/1 (2 plastic tanks, connection valve with pipe for drain)                             | PNC 922438 | <input type="checkbox"/> |



**Electrolux**  
PROFESSIONAL

## SkyLine PremiumS Electric Combi Oven 10GN1/1

|                                                                                                                                                   |            |   |
|---------------------------------------------------------------------------------------------------------------------------------------------------|------------|---|
| • Steam optimizer                                                                                                                                 | PNC 922440 | □ |
| • GREASE COLLECTION KIT FOR OVEN OPEN BASE GN 1/1-2/1 (2 TANKS, OPEN/CLOSE DEVICE FOR DRAIN)                                                      | PNC 922451 | □ |
| • GREASE COLLECTION KIT FOR OVENS GN 1/1-2/1 (2 PLASTIC TANKS, CONNECTION VALVE WITH PIPE FOR DRAIN)                                              | PNC 922452 | □ |
| • Tray rack with wheels 10 GN 1/1, 65mm pitch                                                                                                     | PNC 922601 | □ |
| • Tray rack with wheels, 8 GN 1/1, 80mm pitch                                                                                                     | PNC 922602 | □ |
| • Bakery/pastry tray rack with wheels holding 400x600mm grids for 10 GN 1/1 oven and blast chiller freezer, 80mm pitch (8 runners)                | PNC 922608 | □ |
| • Slide-in rack with handle for 6 & 10 GN 1/1 oven                                                                                                | PNC 922610 | □ |
| • Open base with tray support for 6 & 10 GN 1/1 oven                                                                                              | PNC 922612 | □ |
| • Cupboard base with tray support for 6 & 10 GN 1/1 oven                                                                                          | PNC 922614 | □ |
| • Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or 400x600mm trays                                                    | PNC 922615 | □ |
| • External connection kit for liquid detergent and rinse aid                                                                                      | PNC 922618 | □ |
| • Grease collection kit for GN 1/1-2/1 cupboard base (trolley with 2 tanks, open/close device for drain)                                          | PNC 922619 | □ |
| • Stacking kit for 6+6 GN 1/1 ovens on electric 6+10 GN 1/1 GN ovens                                                                              | PNC 922620 | □ |
| • Trolley for slide-in rack for 6 & 10 GN 1/1 oven and blast chiller freezer                                                                      | PNC 922626 | □ |
| • Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens                                                                                    | PNC 922630 | □ |
| • Stainless steel drain kit for 6 & 10 GN oven, dia=50mm                                                                                          | PNC 922636 | □ |
| • Plastic drain kit for 6 & 10 GN oven, dia=50mm                                                                                                  | PNC 922637 | □ |
| • Trolley with 2 tanks for grease collection                                                                                                      | PNC 922638 | □ |
| • Grease collection kit for GN 1/1-2/1 open base (2 tanks, open/close device for drain)                                                           | PNC 922639 | □ |
| • Wall support for 10 GN 1/1 oven                                                                                                                 | PNC 922645 | □ |
| • Banquet rack with wheels holding 30 plates for 10 GN 1/1 oven and blast chiller freezer, 65mm pitch                                             | PNC 922648 | □ |
| • Banquet rack with wheels 23 plates for 10 GN 1/1 oven and blast chiller freezer, 85mm pitch                                                     | PNC 922649 | □ |
| • Dehydration tray, GN 1/1, H=20mm                                                                                                                | PNC 922651 | □ |
| • Flat dehydration tray, GN 1/1                                                                                                                   | PNC 922652 | □ |
| • Open base for 6 & 10 GN 1/1 oven, disassembled - NO accessory can be fitted with the exception of 922382                                        | PNC 922653 | □ |
| • Bakery/pastry rack kit for 10 GN 1/1 oven with 8 racks 400x600mm and 80mm pitch                                                                 | PNC 922656 | □ |
| • Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1                                                                                             | PNC 922661 | □ |
| • Heat shield for 10 GN 1/1 oven                                                                                                                  | PNC 922663 | □ |
| • Fixed tray rack for 10 GN 1/1 and 400x600mm grids                                                                                               | PNC 922685 | □ |
| • Kit to fix oven to the wall                                                                                                                     | PNC 922687 | □ |
| • Tray support for 6 & 10 GN 1/1 oven base                                                                                                        | PNC 922690 | □ |
| • 4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm                                                                               | PNC 922693 | □ |
| • Reinforced tray rack with wheels, lowest support dedicated to a grease collection tray for 10 GN 1/1 oven, 64mm pitch                           | PNC 922694 | □ |
| • Detergent tank holder for open base                                                                                                             | PNC 922699 | □ |
| • Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base                                                                                     | PNC 922702 | □ |
| • Wheels for stacked ovens                                                                                                                        | PNC 922704 | □ |
| • Spit for lamb or suckling pig (up to 12kg) for GN 1/1 ovens                                                                                     | PNC 922709 | □ |
| • Mesh grilling grid, GN 1/1                                                                                                                      | PNC 922713 | □ |
| • Probe holder for liquids                                                                                                                        | PNC 922714 | □ |
| • Odour reduction hood with fan for 6 & 10 GN 1/1 electric ovens                                                                                  | PNC 922718 | □ |
| • Odour reduction hood with fan for 6+6 or 6+10 GN 1/1 electric ovens                                                                             | PNC 922722 | □ |
| • Condensation hood with fan for 6 & 10 GN 1/1 electric oven                                                                                      | PNC 922723 | □ |
| • Condensation hood with fan for stacking 6+6 or 6+10 GN 1/1 electric ovens                                                                       | PNC 922727 | □ |
| • Exhaust hood with fan for 6 & 10 GN 1/1 ovens                                                                                                   | PNC 922728 | □ |
| • Exhaust hood with fan for stacking 6+6 or 6+10 GN 1/1 ovens                                                                                     | PNC 922732 | □ |
| • Exhaust hood without fan for 6&10 1/1GN ovens                                                                                                   | PNC 922733 | □ |
| • Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens                                                                                  | PNC 922737 | □ |
| • Fixed tray rack, 8 GN 1/1, 85mm pitch                                                                                                           | PNC 922741 | □ |
| • Fixed tray rack, 8 GN 2/1, 85mm pitch                                                                                                           | PNC 922742 | □ |
| • 4 high adjustable feet for 6 & 10 GN ovens, 230-290mm                                                                                           | PNC 922745 | □ |
| • Tray for traditional static cooking, H=100mm                                                                                                    | PNC 922746 | □ |
| • Double-face griddle, one side ribbed and one side smooth, 400x600mm                                                                             | PNC 922747 | □ |
| • Hood Hopper to directly connect the Hood to the centralized ventilation system, for Standard Hoods (with fan motor) and Hoods without fan motor | PNC 922751 | □ |
| • Trolley for grease collection kit                                                                                                               | PNC 922752 | □ |
| • Water inlet pressure reducer                                                                                                                    | PNC 922773 | □ |
| • Kit for installation of electric power peak management system for 6 & 10 GN Oven                                                                | PNC 922774 | □ |
| • Extension for condensation tube, 37cm                                                                                                           | PNC 922776 | □ |
| • Non-stick universal pan, GN 1/1, H=20mm                                                                                                         | PNC 925000 | □ |
| • Non-stick universal pan, GN 1/1, H=40mm                                                                                                         | PNC 925001 | □ |
| • Non-stick universal pan, GN 1/1, H=60mm                                                                                                         | PNC 925002 | □ |
| • Double-face griddle, one side ribbed and one side smooth, GN 1/1                                                                                | PNC 925003 | □ |
| • Aluminum grill, GN 1/1                                                                                                                          | PNC 925004 | □ |
| • Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1                                                                                             | PNC 925005 | □ |
| • Flat baking tray with 2 edges, GN 1/1                                                                                                           | PNC 925006 | □ |
| • Baking tray for 4 baguettes, GN 1/1                                                                                                             | PNC 925007 | □ |
| • Potato baker for 28 potatoes, GN 1/1                                                                                                            | PNC 925008 | □ |
| • Non-stick universal pan, GN 1/2, H=20mm                                                                                                         | PNC 925009 | □ |
| • Non-stick universal pan, GN 1/2, H=40mm                                                                                                         | PNC 925010 | □ |
| • Non-stick universal pan, GN 1/2, H=60mm                                                                                                         | PNC 925011 | □ |
| • Kit of 6 non-stick universal pans, GN 1/1, H=20mm                                                                                               | PNC 925012 | □ |
| • Kit of 6 non-stick universal pans, GN 1/1, H=40mm                                                                                               | PNC 925013 | □ |
| • Kit of 6 non-stick universal pan GN 1/1, H=60mm                                                                                                 | PNC 925014 | □ |
| • Compatibility kit for installation on previous base GN 1/1                                                                                      | PNC 930217 | □ |


SkyLine PremiumS  
Electric Combi Oven 10GN1/1



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.09.09

Front




Side



CWI1 = Cold Water inlet 1 (cleaning)      EI = Electrical inlet (power)  
 CWI2 = Cold Water Inlet 2 (steam generator)  
 D = Drain  
 DO = Overflow drain pipe

Top



### Electric

Supply voltage: 220-240 V/3 ph/50-60 Hz  
 Electrical power, max: 20.3 kW  
 Electrical power, default: 19 kW

### Water:

Inlet water temperature, max: 30 °C  
 Inlet water pipe size (CWI1, CWI2): 3/4"  
 Pressure, min-max: 1-6 bar  
 Chlorides: <85 ppm  
 Conductivity: >50 µS/cm  
 Drain "D": 50mm

### Capacity:

Trays type: 10 (GN 1/1)  
 Max load capacity: 50 kg

### Key Information:

Door hinges: Right Side  
 External dimensions, Width: 867 mm  
 External dimensions, Depth: 775 mm  
 External dimensions, Height: 1058 mm  
 Weight: 147 kg  
 Net weight: 147 kg  
 Shipping weight: 150 kg  
 Shipping volume: 1.06 m<sup>3</sup>

### ISO Certificates

ISO Standards: ISO 9001; ISO 14001; ISO 45001; ISO 50001