

SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, 60 Hz

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



229822 (ECOG202T3V30)

SkyLine PremiumS Combi Boiler Oven with touch screen control, 20x2/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, 3-glass door -60Hz

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 4 automatic cycles (short, medium, intensive, rinse) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity ready
- 6-point multi sensor core temperature probe
- Triple-glass door with double LED lights line
- Stainless steel construction throughout
- Supplied with n.1 trolley rack 2/1 GN, 63 mm pitch.
- Adjustable levelling feet.

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse) and integrated descale of the steam generator.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (101 °C - 130 °C).
- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) with 100+ different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants per family.
- Cycles :
- Regeneration (ideal for banqueting on plate or rethermalizing on tray),
- Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,
- Proving cycle,
- EcoDella cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,
- Sous-vide cooking,
- Static Combi (to reproduce traditional cooking from static oven),
- Pasteurization of pasta,
- Dehydration cycle (ideal for drying fruits, vegetables, meats, seafood),
- Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family,
- Advanced Food Safe Control (to drive the cooking







SkyLine PremiumS Natural Gas Combi Oven 20GN2/1,

with pasteurization factor).

- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be grouped in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 60 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer
- Automatic fast cool down and pre-heat function.
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- GreaseOut: integrated grease drain and collection kit (to use the kit, the oven must be ordered as special code).
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.

Construction

- Integrated spray gun with automatic retracting system for fast rinsing.
- Triple thermo-glazed door with 2 hinged inside panels for easy cleaning and double LED lights line.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.

User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- Automatic consumption visualization at the end of the cycle.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Pictures upload for full customization of cooking cycles.

Sustainability



crosswise oven

- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related
- Energy Star 2.0 certified product.
- Reduced powerfunction for customized slow cooking cycles.
- The outer cardboard packaging is made from 70% recycled materials and FSC*-certified paper, printed with eco-

friendly, water-based ink to support sustainability and environmental responsibility.

(*Forest Stewardship Council is the world's leading organization for sustainable forest management).

- Triple-glass door minimize your energy loss.
 - *Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.
- Zero Waste provides chefs with useful tips for minimizing food waste
- Zero Waste is a library of Automatic recipes that aims to: -give a second life to raw food close to expiration date (e. g., from milk to yogurt)
- -obtain genuine and tasty dishes from overripe fruit/ vegetables (usually considered not appropriate for sale)
- -promote the use of typically discarded food items (e.g., carrot peels).
- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.

Included Accessories

• 1 of Trolley with tray rack 20 GN 2/1, PNC 922757 63mm pitch

Optional Accessories		
• External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens	PNC 864388	
 Water filter with cartridge and flow meter for high steam usage (combi used mainly in steaming mode) 	PNC 920003	
 Water filter with cartridge and flow meter for medium steam usage 	PNC 920005	
 Pair of AISI 304 stainless steel grids, GN 1/1 	PNC 922017	
 Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922036	
 AISI 304 stainless steel grid, GN 1/1 	PNC 922062	
 External side spray unit (needs to be mounted outside and includes support to be mounted on the oven) 	PNC 922171	
 Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm 	PNC 922189	
 Baking tray with 4 edges in perforated aluminum, 400x600x20mm 	PNC 922190	
 Baking tray with 4 edges in aluminum, 400x600x20mm 	PNC 922191	
 Pair of frying baskets 	PNC 922239	
 AISI 304 stainless steel bakery/pastry grid 400x600mm 	PNC 922264	
 Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922266	
 USB probe for sous-vide cooking 	PNC 922281	
 Universal skewer rack 	PNC 922326	
• 6 short skewers	PNC 922328	
 Volcano Smoker for lengthwise and 	PNC 922338	

SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, 60 Hz

















SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, 60 Hz

	DVIC 2227:	_	• Water inlet pressure reducer PNC 922773	
Multipurpose hook Consequently a live of the control of t	PNC 922348		• Extension for condensation tube, 37cm PNC 922776	٥
Grease collection tray, GN 2/1, H=60 mm Grid for whole duck (9 per grid 1969).	PNC 922357		Non-stick universal pan, GN 1/ 1, PNC 925001 H=40mm	٥
Grid for whole duck (8 per grid - 1,8kg each), GN 1/1 The grant of a 20 GN 2/1 averaged and a 20 GN 2/1 averaged an	PNC 922362		• Non-stick universal pan, GN 1/1, PNC 925002 H=60mm	
 Thermal cover for 20 GN 2/1 oven and blast chiller freezer 	PNC 922367	_	• Double-face griddle, one side ribbed PNC 925003	
Wall mounted detergent tank holder	PNC 922386		and one side smooth, GN 1/1 • Aluminum grill, GN 1/1 • PNC 925004	
USB single point probe	PNC 922390		• Frying pan for 8 eggs, pancakes, PNC 925005	
 IoT module for OnE Connected (Combi Ovens, Blast chiller/freezers, Rack Type DW) and SkyDuo (one IoT board per appliance - to connect oven to blast 	PNC 922421		hamburgers, GN 1/1 Flat baking tray with 2 edges, GN 1/1 PNC 925006 Potato baker for 28 potatoes, GN 1/1 PNC 925008	_
chiller for Cook&Chill process).			• Kit of 6 non-stick universal pans, GN 1/1, PNC 925012	_
 Connectivity router (WiFi and LAN) 	PNC 922435		H=20mm	_
 Elevating kit with trolley height extension for 20 GN 2/1 oven 	PNC 922447		• Kit of 6 non-stick universal pans, GN 1/1, PNC 925013 H=40mm	
 External connection kit for liquid detergent and rinse aid 	PNC 922618		• Kit of 6 non-stick universal pan GN 1/1, PNC 925014 H=60mm	
• Dehydration tray, GN 1/1, H=20mm	PNC 922651			
• Flat dehydration tray, GN 1/1	PNC 922652			
 Heat shield for 20 GN 2/1 oven 	PNC 922658			
 Kit to convert from natural gas to LPG 	PNC 922670			
• Kit to convert from LPG to natural gas	PNC 922671			
 Flue condenser for gas oven 	PNC 922678			
• Trolley with tray rack, 15 GN 2/1, 84mm pitch	PNC 922686			
 Kit to fix oven to the wall 	PNC 922687			
• Adjustable wheels for 20 GN 1/1 and 20 GN 2/1 ovens	PNC 922701			
 4 flanged feet for 20 GN , 2", 100-130mm 	PNC 922707			
 Mesh grilling grid, GN 1/1 	PNC 922713			
 Probe holder for liquids 	PNC 922714			
 Levelling entry ramp for 20 GN 2/1 oven 	PNC 922716			
 Stainless steel drain kit for 20 GN oven, dia=50mm 	PNC 922738			
 Plastic drain kit for 20 GN oven, dia=50mm 	PNC 922739			
 Holder for trolley handle (when trolley is in the oven) for 20 GN oven 				
 Tray for traditional static cooking, H=100mm 	PNC 922746			
 Double-face griddle, one side ribbed and one side smooth, 400x600mm 	PNC 922747			
 Trolley with tray rack 20 GN 2/1, 63mm pitch 	PNC 922757			
 Trolley with tray rack, 16 GN 2/1, 80mm pitch 	PNC 922758			
 Banquet trolley with rack holding 92 plates for 20 GN 2/1 oven and blast chiller freezer, 85mm pitch 	PNC 922760			
 Bakery/pastry trolley with rack holding 400x600mm grids for 20 GN 2/1 oven and blast chiller freezer, 80mm pitch (16 runners) 	PNC 922762			
 Banquet trolley with rack holding 116 plates for 20 GN 2/1 oven and blast chiller freezer, 66mm pitch 	PNC 922764			
 Kit compatibility for aos/easyline trolley (produced till 2019) with SkyLine/ Magistar 20 GN 2/1 combi oven 	PNC 922770			
 Kit compatibility for aos/easyline 20 GN oven with SkyLine/Magistar trolleys 	PNC 922771			

















SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, 60 Hz

Electric

220-230 V/1 ph/60 Hz Supply voltage:

Electrical power, max: 2.5 kW Electrical power, default: 2.5 kW

Gas

Total thermal load: 402275 BTU (100 kW)

Natural Gas G20

50mm

Gas Power: 100 kW

Standard gas delivery: ISO 7/1 gas connection

1" MNPT diameter:

Water:

Inlet water temperature, max: 30 °C

Inlet water pipe size (CWI1,

3/4" CWI2): Pressure, min-max: 1-6 bar Chlorides: <17 ppm Conductivity: >50 µS/cm

Drain "D": Capacity:

20 (GN 2/1) Trays type: Max load capacity: 200 kg

Key Information:

Right Side Door hinges: External dimensions, Width: 1162 mm External dimensions, Depth: 1066 mm 1794 mm External dimensions, Height: 446 kg Weight: Net weight: 408 kg Shipping weight: 446 kg Shipping volume: 2.77 m³

ISO Certificates

ISO 9001; ISO 14001; ISO

ISO Standards: 45001; ISO 50001











