

| ITEM # | | |
|---------|--|--|
| MODEL # | | |
| NAME # | | |
| | | |
| SIS # | | |
| AIA# | | |



237301 (ECOE201T3A3B)

SkyLine PremiumS Combi Boiler Oven with touch screen control, 16 600x400mm, electric, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, boiler in AISI 316L, 3-glass door, for bakery/pastry, pitch 80mm

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator (in s/s 316L) with real humidity control based upon Lambda Sensor.
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 4 automatic cycles (short, medium, intensive, rinse) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings
- Connectivity for real time access, remote software update, HACCP, recipe and energy management (optional)
- 6-point multi sensor core temperature probe
- Triple-glass door with double LED lights line.
- Stainless steel construction throughout
- Supplied with n.1 pastry tray rack 600x400 mm, 80 mm pitch..

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- SkyClean: Automatic and built-in self cleaning system with 4 automatic cycles (short, medium, intensive, rinse) and integrated descale of the steam generator.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (101 °C - 130 °C).
- Short cleaning cycle: optimized cleaning cycle with a duration of just 33 minutes, improving efficiency and reducing downtime.
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) with 100+ different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants per family.
- Cycles :
- Regeneration (ideal for banqueting on plate or rethermalizing on tray),
- Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,
- Proving cycle,
- EcoDella cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,
- Sous-vide cooking,
- Static Combi (to reproduce traditional cooking from static oven),
- Pasteurization of pasta,
- Dehydration cycle (ideal for drying fruits, vegetables, meats, seafood),
- Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family,
- Advanced Food Safe Control (to drive the cooking







with pasteurization factor).

- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be grouped in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 60 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Automatic fast cool down and pre-heat function.
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- GreaseOut: integrated grease drain and collection kit (to use the kit, the oven must be ordered as special code).
- Electrolux Professional recommends the use of treated water to guarantee optimal cooking results and extend the life of the appliance. Check local water condition to select the appropriate water filter. More info available on the website.

Construction

- Integrated spray gun with automatic retracting system for fast rinsing.
- Boiler in 316L AISI to protect against corrosion.
- Triple thermo-glazed door with 2 hinged inside panels for easy cleaning and double LED lights line.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.

User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.
- Connectivity for remote real time access, easy HACCP management, equipment uptime increase, consumption tracking and energy management (requires optional accessory).
- Pictures upload for full customization of cooking cycles.

Sustainability



- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Reduced powerfunction for customized slow cooking cycles.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a

time and energy efficiency point of view.

- Zero Waste provides chefs with useful tips for minimizing food waste.
 - Zero Waste is a library of Automatic recipes that aims to:
 -give a second life to raw food close to expiration date (e. g., from milk to yogurt)
 - -obtain genuine and tasty dishes from overripe fruit/ vegetables (usually considered not appropriate for sale)
- -promote the use of typically discarded food items (e.g., carrot peels).
- The outer cardboard packaging is made from 70% recycled materials and FSC*-certified paper, printed with ecofriendly, water-based ink to support sustainability and environmental responsibility.

(*Forest Stewardship Council is the world's leading organization for sustainable forest management).

- Triple-glass door minimize your energy loss.
- *Approx. -10% of idle energy consumption in convection based on test in compliance with ASTM Standard F2861-20
- Save energy, water, detergent and rinse aid with SkyClean green functions.
- C22 and C25 detergents are formulated without phosphates and phosphorus (C25 is also maleic acid-free), making them safe for both the environment and human health.













| | | | | | | _ |
|--|--------------------------|---|---------------------------------|---|--------------------------|---|
| Included Accessories | | | | rnal connection kit for liquid ergent and rinse aid | PNC 922618 | |
| | PNC 922761 | | Deh | ydration tray, GN 1/1, H=20mm | PNC 922651 | |
| holding 600x400mm grids for 20 GN 1/1 oven and blast chiller freezer, 80mm | | | | dehydration tray, GN 1/1 | PNC 922652 | |
| pitch (16 runners) | | | | t shield for 20 GN 1/1 oven | PNC 922659 | |
| Optional Accessories | | | Troll pitch | ey with tray rack, 15 GN 1/1, 84mm 1 | PNC 922683 | |
| • External reverse osmosis filter for single | PNC 864388 | | • Kit to | o fix oven to the wall | PNC 922687 | |
| tank Dishwashers with atmosphere boiler and Ovens | | | | inged feet for 20 GN , 2", 130mm | PNC 922707 | |
| Water filter with cartridge and flow | PNC 920003 | | Mes | h grilling grid, GN 1/1 | PNC 922713 | |
| meter for high steam usage (combi used mainly in steaming mode) | | | | e holder for liquids | PNC 922714 | |
| Water filter with cartridge and flow | PNC 920005 | | | elling entry ramp for 20 GN 1/1 oven our reduction hood with fan for 20 | PNC 922715 PNC 922720 | |
| meter for medium steam usagePair of AISI 304 stainless steel grids, | PNC 922017 | | | 1/1 electric oven | | _ |
| GN 1/1 | | | | densation hood with fan for 20 GN lectric oven | PNC 922725 | |
| Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922036 | | | aust hood with fan for 20 GN 1/1 | PNC 922730 | |
| AISI 304 stainless steel grid, GN 1/1 | PNC 922062 | | ovei | | DNC 000775 | |
| Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2 | PNC 922086 | | • Exno | aust hood without fan for 20 1/1GN n | PNC 922735 | |
| External side spray unit (needs to be | PNC 922171 | | | nless steel drain kit for 20 GN oven, 50mm | PNC 922738 | |
| mounted outside and includes support to be mounted on the oven) | | _ | | tic drain kit for 20 GN oven, 50mm | PNC 922739 | |
| Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm | PNC 922189 | | • Hold | der for trolley handle (when trolley is e oven) for 20 GN oven | PNC 922743 | |
| Baking tray with 4 edges in perforated aluminum, 400x600x20mm | PNC 922190 | | | for traditional static cooking, 10mm | PNC 922746 | |
| Baking tray with 4 edges in aluminum, 400x600x20mm | PNC 922191 | | | ble-face griddle, one side ribbed one side smooth, 400x600mm | PNC 922747 | |
| Pair of frying baskets | PNC 922239 | | | d Hopper to directly connect the | PNC 922751 | |
| AISI 304 stainless steel bakery/pastry grid 400x600mm | PNC 922264 | | syste | d to the centralized ventilation em, for Standard Hoods (with fan or) and Hoods without fan motor | | |
| • Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922266 | | | ey with tray rack, 20 GN 1/1, 63mm | PNC 922753 | |
| USB probe for sous-vide cooking | PNC 922281 | | | ey with tray rack, 16 GN 1/1, 80mm | PNC 922754 | |
| • Grease collection tray, GN 1/1, H=100 | PNC 922321 | | pitch | | 1110 /22/54 | _ |
| Mit universal skewer rack and 4 long skewers for Lenghtwise ovens | PNC 922324 | | plate | quet trolley with rack holding 54 es for 20 GN 1/1 oven and blast er freezer, 74mm pitch | PNC 922756 | |
| Universal skewer rack | PNC 922326 | | | ery/pastry trolley with rack holding | PNC 922761 | |
| 4 long skewers | PNC 922327 | | 600 | x400mm grids for 20 GN 1/1 oven | | |
| Grease collection tray, GN 1/1, H=40 mm | PNC 922329 | | runn | | | |
| Volcano Smoker for lengthwise and crosswise oven | PNC 922338 | | plate | quet trolley with rack holding 45 es for 20 GN 1/1 oven and blast | PNC 922763 | |
| Multipurpose hook | PNC 922348 | | | er freezer, 90mm pitch compatibility for aos/easyline trolley | DNIC 022760 | |
| Grid for whole duck (8 per grid - 1,8kg each), GN 1/1 | PNC 922362 | | (pro | duced till 2019) with SkyLine/ gistar 20 GN 1/1 combi oven | PINC 922/09 | _ |
| Thermal cover for 20 GN 1/1 oven and blast chiller freezer | PNC 922365 | | • Kit c | compatibility for aos/easyline 20 GN n with SkyLine/Magistar trolleys | PNC 922771 | |
| Wall mounted detergent tank holder | PNC 922386 | | | er inlet pressure reducer | PNC 922773 | |
| USB single point probe | PNC 922390 | | | • | PNC 922776 | _ |
| IoT module for OnE Connected (Combi Ovens, Blast chiller/freezers, Rack Type DW) and SkyDuo (one IoT board per | PNC 922421 | | • Kit fo | or installation of electric power k management system for 20 GN | PNC 922778 | ā |
| appliance - to connect oven to blast chiller for Cook&Chill process). | | _ | | -stick universal pan, GN 1/ 1, Omm | PNC 925001 | |
| Connectivity router (WiFi and LAN) Elevating kit with trolley height extension for 20 GN 1/1 oven | PNC 922435 PNC 922446 | | • Non | -stick universal pan, GN 1/1, 0mm | PNC 925002 | |
| | | | | | | |













| Double-face griddle, one side ribbed and one side smooth, GN 1/1 | PNC | 925003 | |
|--|-----|--------|--|
| Aluminum grill, GN 1/1 | PNC | 925004 | |
| Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1 | PNC | 925005 | |
| • Flat baking tray with 2 edges, GN 1/1 | PNC | 925006 | |
| Baking tray for 4 baguettes, GN 1/1 | PNC | 925007 | |
| Potato baker for 28 potatoes, GN 1/1 | PNC | 925008 | |
| • Non-stick universal pan, GN 1/2, H=20mm | PNC | 925009 | |
| Non-stick universal pan, GN 1/2, H=40mm | PNC | 925010 | |
| Non-stick universal pan, GN 1/2, H=60mm | PNC | 925011 | |
| • Kit of 6 non-stick universal pans, GN 1/1, H=20mm | PNC | 925012 | |
| • Kit of 6 non-stick universal pans, GN 1/1, H=40mm | PNC | 925013 | |
| • Kit of 6 non-stick universal pan GN 1/1, H=60mm | PNC | 925014 | |
| Recommended Detergents | | | |
| C25 Rinse & Descale Tabs, phosphate- free, phosphorous-free, maleic acid- free, 50 tabs bucket | PNC | 0S2394 | |
| C22 Cleaning Tabs, phosphate-free, phosphorous-free, 100 bags bucket | PNC | 0S2395 | |




















CWII Cold Water inlet 1 (cleaning) CWI2

= Cold Water Inlet 2 (steam generator)

DO Overflow drain pipe



Electric

Supply voltage: 380-415 V/3N ph/50-60 Hz

40.4 kW Electrical power, max: Electrical power, default: 37.7 kW

Water:

Inlet water temperature, max:

30 °C

Inlet water pipe size (CWI1, CWI2):

3/4" 1-6 bar <85 ppm

Conductivity: >50 µS/cm Drain "D": 50mm

Capacity:

Chlorides:

Trays type: 16 (400x600 mm)

100 kg Max load capacity:

Key Information:

Pressure, min-max:

Door hinges: Right Side External dimensions, Width: 911 mm External dimensions, Depth: 864 mm External dimensions, Height: 1794 mm 311 kg Weight: Net weight: 278 kg Shipping weight: 311 kg Shipping volume: 1.83 m³

ISO Certificates

ISO 9001; ISO 14001; ISO 45001; ISO 50001 ISO Standards:







