

MultiSlim Electric Compact Digital Oven 6GN 1/1 with Cleaning System

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



260638 (ECD061WL)

Compact electric Oven, 6x1/1GN, with direct steam and 11 humidity level settings, with automatic cleaning, left-hinged door

260658 (ECD061WR)

Compact electric Oven, 6x1/1GN, with direct steam and 11 humidity level settings, with automatic cleaning, right-hinged door

Short Form Specification

Item No.

Compact electric Oven with direct steam: 90% steam saturation. Cooking cycles: hot air (max 280 °C) combined with 11 different humidity settings, ranging from browning to baking and par-steaming. Programmability: 99 free recipes with 9-step cooking. Variable fan speed with 3 levels. Double-glass door with book-like opening maintains a cool external temperature and incorporates a drip pan to collect excess condensation avoiding wet floors. Halogen lighting in the cooking chamber. Door, front panel and interior in AISI 304 stainless steel.

Supplied with n.1 tray rack 1/1GN, 30mm pitch.

Main Features

- Dry hot convection cycle (max 280 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation:
 - -0 = no additional moisture (browning, au gratin, baking, pre-cooked food)
 - -1-2 = low moisture (small portions of meat and fish) -3-4 = medium low moisture (large pieces of meat,
 - reheating, roasted chicken and proving)
 -5-6 = medium moisture (roasted vegetable and first step of roasted meat & fish)
 - -7-8 = medium-high moisture (stewed vegetables)-9-10 = high moisture (poached meat and jacket potatoes)
- Programmability: a maximum of 99 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 9-step cooking programs also available.
- Exhaust valve electronically controlled to extract humidity in excess for extra crispy results.
- Eco-delta: the temperature inside the cooking cell is higher than the temperature of the food and rises accordingly.
- Automatic cleaning system: 3 different pre-set cycles to clean the cooking cell, according to the actual requirements. The cleaning system is builtin (no need for add-ons).
- Automatic and manual rapid cooling activation when going from a higher to a lower temperature.
- USB connection: to download HACCP data, upload/download the recipes.
- Variable fan speed with 3 levels.

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- Swing hinged front panel for easy service access to main components.
- IPx4 water protection.
- Water consumption during steaming cycle is 2.6 litres per hour.

APPROVAL:





MultiSlim Electric Compact Digital Oven 6GN 1/1 with Cleaning System

Optional Accessories

 Pair of AISI 304 stainless steel grids, GN 1/1 (only for 260638) 	PNC 922017	
 Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2 (only for 260638) 	PNC 922086	
 Pair of frying baskets (only for 260638) 	PNC 922239	
 Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 (only for 260638) 	PNC 922266	
Base support for stacked compact ovens (only for 260638)	PNC 922368	
Open base for compact 6x1/1GN oven (only for 260638)	PNC 922369	
 Tray support for compact 6x1/1GN oven - open base (only for 260638) 	PNC 922370	
 Stacking kit for compact 6x1/1GN oven (only for 260638) 	PNC 922371	
 External spray unit for compact 6x1/1GN oven (only for 260638) 	PNC 922372	
 1-sensor core probe for compact 6x1/1GN oven (only for 260638) 	PNC 922373	
 Right-hinged door for compact 6x1/1GN oven (only for 260638) 	PNC 922374	
Double-step door for opening compact 6x1/1GN oven (only for 260638)	PNC 922377	
 Kit to front air filter for compact 6x1/1GN oven (only for 260638) 	PNC 922379	
 Water inlet pressure reducer (only for 260638) 	PNC 922773	
• Non-stick universal pan, GN 1/1, H=20mm (only for 260638)	PNC 925000	
• Non-stick universal pan, GN 1/1, H=40mm (only for 260638)	PNC 925001	
• Non-stick universal pan, GN 1/1, H=60mm (only for 260638)	PNC 925002	
Double-face griddle, one side ribbed and one side smooth, GN 1/1 (only for 260638)	PNC 925003	
 Aluminum grill, GN 1/1 (only for 260638) 	PNC 925004	
 Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1 (only for 260638) 	PNC 925005	
• Flat baking tray with 2 edges, GN 1/1 (only for 260638)	PNC 925006	
Baking tray for 4 baguettes, GN 1/1 (only for 260638)	PNC 925007	
• Non-stick universal pan, GN 1/2, H=20mm (only for 260638)	PNC 925009	
• Non-stick universal pan, GN 1/2, H=40mm (only for 260638)	PNC 925010	
 Non-stick universal pan, GN 1/2, H=60mm (only for 260638) 	PNC 925011	













MultiSlim Electric Compact Digital Oven 6GN 1/1 with Cleaning System

Front

Top






Cold Water inlet 1 (cleaning) = Cold Water Inlet 2 (steam generator) CWI2

D Drain

Electrical inlet (power)



Electric

Supply voltage: 400 V/3N ph/50/60 Hz 230V 3ph 50/60Hz; Predisposed for:

230V 50/60Hz

6.9 kW Electrical power, max:

Circuit breaker required

Water:

Total hardness: 5-50 ppm

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions. Please refer to user manual for detailed water quality

information.

1.5-3 bar Pressure, min-max: Drain "D": 40mm Water inlet "CW" connection: 3/4"

Installation:

5 cm rear and right hand Clearance:

sides.

Suggested clearance for

service access: 50 cm left hand side.

Capacity:

Max load capacity: 12 kg Trays type: 6 (GN 1/1)

Key Information:

External dimensions, Width: 519 mm External dimensions, Depth: 803 mm 770 mm External dimensions, Height: Net weight: 72 kg

Shipping weight:

260638 (ECD061WL) 84 kg 83 kg 260658 (ECD061WR)

Shipping volume:

260638 (ECD061WL) 0.66 m³ 260658 (ECD061WR) 0.65 m³









