

## MultiSlim

### Electric Compact Digital Oven 6GN 1/1 with Cleaning System

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_


**260638 (ECD061WL)**

 Compact electric Oven,  
 6x1/1GN, with direct steam  
 and 11 humidity level  
 settings, with automatic  
 cleaning, left-hinged door

**260658 (ECD061WR)**

 Compact electric Oven,  
 6x1/1GN, with direct steam  
 and 11 humidity level  
 settings, with automatic  
 cleaning, right-hinged door

### Short Form Specification

#### Item No.

Compact electric Oven with direct steam: 90% steam saturation.  
 Cooking cycles: hot air (max 280 °C) combined with 11 different  
 humidity settings, ranging from browning to baking and par-steaming.  
 Programmability: 99 free recipes with 9-step cooking. Variable fan  
 speed with 3 levels. Double-glass door with book-like opening  
 maintains a cool external temperature and incorporates a drip pan  
 to collect excess condensation avoiding wet floors. Halogen lighting  
 in the cooking chamber. Door, front panel and interior in AISI 304  
 stainless steel.  
 Supplied with n.1 tray rack 1/1GN, 30mm pitch.

### Main Features

- Dry hot convection cycle (max 280 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation: -0 = no additional moisture (browning, au gratin, baking, pre-cooked food) -1-2 = low moisture (small portions of meat and fish) -3-4 = medium low moisture (large pieces of meat, reheating, roasted chicken and proving) -5-6 = medium moisture (roasted vegetable and first step of roasted meat & fish) -7-8 = medium-high moisture (stewed vegetables) -9-10 = high moisture (poached meat and jacket potatoes)
- Programmability: a maximum of 99 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 9-step cooking programs also available.
- Exhaust valve electronically controlled to extract humidity in excess for extra crispy results.
- Eco-delta: the temperature inside the cooking cell is higher than the temperature of the food and rises accordingly.
- Automatic cleaning system: 3 different pre-set cycles to clean the cooking cell, according to the actual requirements. The cleaning system is built-in (no need for add-ons).
- Automatic and manual rapid cooling activation when going from a higher to a lower temperature.
- USB connection: to download HACCP data, upload/download the recipes.
- Variable fan speed with 3 levels.

### Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- Swing hinged front panel for easy service access to main components.
- IPx4 water protection.
- Water consumption during steaming cycle is 2.6 litres per hour.

APPROVAL: \_\_\_\_\_



**Electrolux**  
PROFESSIONAL


**MultiSlim**  
**Electric Compact Digital Oven 6GN**  
**1/1 with Cleaning System**




**MultiSlim**  
**Electric Compact Digital Oven 6GN 1/1 with Cleaning System**  
The company reserves the right to make modifications to the products  
without prior notice. All information correct at time of printing.

2026.06.29

Front




Side



CWI1 = Cold Water inlet 1 (cleaning)  
 CWI2 = Cold Water Inlet 2 (steam generator)  
 D = Drain  
 EI = Electrical inlet (power)

Top



## Electric

**Supply voltage:** 400 V/3N ph/50/60 Hz  
 230V 3ph 50/60Hz;  
**Predisposed for:** 230V 50/60Hz  
**Electrical power, max:** 6.9 kW  
**Circuit breaker required**

## Water:

**Total hardness:** 5-50 ppm  
**Electrolux Professional** recommends the use of treated water, based on testing of specific water conditions. Please refer to user manual for detailed water quality information.

**Pressure, min-max:** 1.5-3 bar  
**Drain "D":** 40mm  
**Water inlet "CW" connection:** 3/4"

## Installation:

**Clearance:** 5 cm rear and right hand sides.  
**Suggested clearance for service access:** 50 cm left hand side.

## Capacity:

**Max load capacity:** 12 kg  
**Trays type:** 6 (GN 1/1)

## Key Information:

**External dimensions, Width:** 519 mm  
**External dimensions, Depth:** 803 mm  
**External dimensions, Height:** 770 mm  
**Net weight:** 72 kg  
**Shipping weight:**  
 260638 (ECD061WL) 84 kg  
 260658 (ECD061WR) 83 kg  
**Shipping volume:**  
 260638 (ECD061WL) 0.66 m<sup>3</sup>  
 260658 (ECD061WR) 0.65 m<sup>3</sup>