

## Ventilation Equipment 304 S/S Wall Hood+Filters 4000X1100mm

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_


**642337 (BP1140DT)**

304 stainless steel Wall Hood with filters

### Short Form Specification

**Item No.** \_\_\_\_\_

Constructed in 304 AISI stainless steel. Equipped with labyrinth filters in 304 AISI stainless steel, blind panels in 304 AISI stainless steel, grease collecting trough all around and condensate collecting tray.

### Main Features

- External panels with upturned edges to avoid injuries.
- Prearranged for installation of lighting.
- Low noise level.

### Construction


- Eyebolts and screw anchors for ceiling installation.
- 304 AISI stainless steel condensation collection tray.
- Labyrinth filters guarantee constant filtration to avoid clogging and to protect against fire.
- 304 AISI stainless steel blind panels for a correct exhaustion.
- Outlet holes are sized in order to minimize drops in pressure.
- Perimetral gutter with drain hole to transfer grease into a 304 AISI container.
- Entirely constructed in 304 AISI stainless steel.
- 304 AISI stainless steel labyrinth filters easily removable for cleaning.

### Optional Accessories

- Drain for hoods, diam.1/2" (m), PNC 640409  with plug
- Speed variator for motors up to 1,7 kW PNC 640686

**APPROVAL:** \_\_\_\_\_

Front


**Key Information:**
**External dimensions, Width:**

642337 (BP1140DT) 4000 mm

**External dimensions, Depth:** 1100 mm


**External dimensions, Height:** 500 mm

**Net weight:**

ISO 9001; ISO 14001; ISO 45001; ISO 50001 kg

**Air Emission:**
**Air capacity:** 5700 mc/h

Side



Top

