

Flexy Compact Cashier Unit with wheels and two stainless steel tray sliders, H=900mm

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



322073 (F30N0AW00S)

Cashier Unit with wheels and two stainless steel tray sliders, H=900mm

Short Form Specification

Item No.

Compact design, ideal for space saving environments. AISI 304 Foldable tray sliders on long sides. Unit mounted on 125 mm wheels 2 swivel and 2 with brakes. Sturdy body construction with laminated panelings on 4 sides. 900mm worktop height. Unit has protective panelling and is designed to accomodate a cash-register with enough room for the operator's chair. Supplied as standard with a drawer with a lock and key. Available in left or right configuration.

Main Features


- Perfect compact design makes it ideal for space saving environments.
- CB and CE certifed by a third party notified body.
- Available options with online configurator: colors, tray sliders, overshelves, feet/wheels with desired diameter, height 750mm for kids.
- Optional plinth can be installed to cover the feet or the wheels.
- Unit has protective panelling and is designed to accomodate a cash-register with enough room for the operator's chair.
- Supplied as standard with a drawer with a lock and key.
- Available in left or right configuration.
- AISI 304 Tray slider in flush mounted stainless steel is installed on long sides and they can also be folded down to facilitate passage of the units through doorways.
- Unit mounted on 125 mm wheels 2 swivel and 2 with brakes.
- Food introduced at the correct temperature maintains its core temperature according to Afnor Standards.

Construction


- Top in AISI 304.
- Sturdy construction with laminated panelings on 4 sides

APPROVAL:











Flexy Compact Cashier Unit with wheels and two stainless steel tray sliders, H=900mm

Key Information:

N° of doors:

External dimensions,

Width: 1100 mm

External dimensions,

Depth:

External dimensions,

900 mm Height: Net weight: 83 kg 1100 mm Shipping height: Shipping width: 920 mm Shipping depth: 1230 mm Shipping volume: 1.24 m³

1180 mm

