



Electrolux
PROFESSIONAL

Modular Preparation 3400 mm Work Top with Upstand

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



121172 (TPLA34A)

Work Top with upstand
3400mm

Short Form Specification

Item No. _____

The 40mm high worktop in 304 AISI stainless steel, incorporates an 18mm under panel made of sound deadening material. Front and rear longitudinal stainless steel c-channel reinforcement. Special shaped front profile, without burrs, to avoid water leakage. Fully welded and shapely polished corners. 100mm boxed heavy duty splash back with a 45° top angle and fully welded sides. Work tops can be mounted on brackets, legs or bases in order to obtain a work height of 900mm.

Main Features

- Special shaped front and rear profiles without burrs to avoid water leakage on modules below.
- Extremely easy to clean thanks to the large and smooth seamless surface with Scotch-Brite finishing.

Construction

- 304 AISI stainless steel worktop (CrNi 18/10) 40 mm high, 15/10 (16 gauges) thickness.
- 18mm under panel made of sound deadening material according to E1 European specifications.
- Front and rear lengthwise stainless steel c-channel reinforcement, 15/10 (16 gauges).
- For a work height of 900 mm, worktops can be mounted on: solid bracket, solid bracket plus 50x50mm legs, 710 mm ambient, hot, refrigerated or freezer units with hinged doors or telescopic drawers, placed on oversized (65x65mm) or 150mm high feet (0/+90mm adjustable in height).
- Fully welded and polished corners.
- 100 mm boxed heavy duty splashback with a 45° degrees top angle, folded directly from the worktop, has fully welded sides and rear part completely covered by stainless steel profile to avoid water spillage on modules below.

Optional Accessories

- Drop-in soaking unit 800x500x350mm PNC 855216 ☐
- Single plastic drain syphon 1,5 " for work tables with bowl PNC 855306 ☐
- Drop-in Bowl and right-hand drainage 400x400x200mm PNC 855800 ☐
- Drop-in Bowl and right-hand drainage 600x500x250mm PNC 855801 ☐
- Side upstand, h=100mm PNC 855802 ☐
- Bowl Skirting (400x400x200) for cantilever execution PNC 855806 ☐
- Bowl Skirting (600x500x250) for cantilever execution PNC 855807 ☐
- Bowl Skirting (2x600x500x250) for cantilever execution PNC 855808 ☐
- Stainless steel square tube wall bracket PNC 855814 ☐
- Stainless steel wall bracket with squared leg 50x50mm PNC 855815 ☐
- Drop-in Bowl and left-hand drainage 400x400x200mm PNC 855816 ☐
- Drop-in Bowl and left-hand drainage 600x500x250mm PNC 855817 ☐
- False bottom for right hand 600x500mm Bowl PNC 895100 ☐
- False bottom for left hand 600x500mm Bowl PNC 895110 ☐

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com



Key Information:

External dimensions, Width:	
121172 (TPLA34A)	3400 mm
External dimensions, Depth:	700 mm
External dimensions, Height:	140 mm
Upstand Dimensions, Height:	100 mm
Upstand Dimensions, Radius:	90°
Worktop thickness:	40 mm
Net weight:	107 kg