



Drop-In Refrigerated quartz surface - 2GN with A overshell



341168 (D21C2O)

Drop-in Refrigerated Quartz Surface (2 GN container capacity) with one A type overshell and LED light

Short Form Specification

Item No.

Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free. Automatic defrosting guarantees evaporators clearance and efficient well cooling. High-density expanded polyurethane foam with cyclopentane guarantees excellent well insulation to reduce energy dispersion. The bottom is equipped with copper tubes to ensure proper cooling, with this system the air touches the cold surface and gets cooled. Designed to serve the food on plates. Stylish A type overshell designed for extra increased visibility on the surface for charming food display.

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____

Main Features

- CB and CE certified by a third party notified body.
- Precise temperature control and setting at 0,1°C .
- As standard the product comes with digitally controlled thermostat which is in line of HACCP norms and provides visual alarm as a warning of the increasing or decreasing temperatures.
- Food introduced at the correct temperature maintains its core temperature according to Afnor Standards.
- Automatic defrosting guarantees evaporators clearance and efficient well cooling.
- Designed to serve the food on plates .
- Equipped with a drain hole to easily discharge top condensation.
- It comes with stylish white coloured quartz top and stainless steel framed that makes it ideal to serve cold dishes in an elegant way.
- Stylish A type overshell designed for extra increased visibility on the surface for charming food display.
- Overshell equipped with LED lights.
- Designed to be positioned in flush installation providing improved cleanability and suitable for modern design installations.

Construction

- Electronic control with temperature display.
- IPx2 water protection.
- The bottom is equipped with copper tubes to ensure proper cooling, with this system the air touches the cold surface and gets cooled.
- AISI 304 Stainless steel frame with rounded corners to facilitate cleaning operations.
- Overshell in complete AISI 304.

Sustainability

- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- High-density expanded polyurethane foam with cyclopentane guarantees excellent well insulation to reduce energy



APPROVAL:



Experience the Excellence
www.electroluxprofessional.com




**Drop-In
Refrigerated quartz surface - 2GN
with A overshell**

dispersion.

**Drop-In
Refrigerated quartz surface - 2GN with A overshell**


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.01.05



EI = Electrical inlet (power)

Top



Electric

Supply voltage: 220-240 V/1N ph/50 Hz
 Electrical power, max: 0.47 kW

Water:

Drain line size:
 Water drain outlet size:

Key Information:

External dimensions, Width: 770 mm
 External dimensions, Depth: 620 mm
 External dimensions, Height: 784 mm
 Net weight: 53.06 kg
 Shipping weight: 63.86 kg
 Shipping height: 1050 mm
 Shipping width: 660 mm
 Shipping depth: 810 mm
 Shipping volume: 0.56 m³
 Set temperature: -10 / 0 °C
 Top temperature: -10 / 0 °C

Refrigeration Data

Refrigerant type: R290

Sustainability

Noise level: 58,23 dBA



Drop-In

Refrigerated quartz surface - 2GN with A overshell


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.01.05




Front view
Scala: 1:10
Dettaglio D
Scala 1:7
ONLY FOR FLUSH
INSTALLATION
Dettaglio B
Scala 1:2
Section Cut A-A
Scala: 1:10

Top view
Scala: 1:20
ONLY FOR FLUSH
INSTALLATION

CAPACITY	CUTOUT		LOWERING FOR FLUSH INSTALLATION		C	K
	A1	B1	A2	B2		
2GN	740		774		855	
3GN	1070	560	1104	624	1190	470
4GN	1390		1424		1510	


595T03700 - COLD QUARTZ SURFACE OVERSH. ON THE FRAME