



Drop-In Drop-in refrigerated well, static (2 GN container capacity) with A overshell



341177 (D10C2O)

Drop-in Refrigerated Well,
static (2 GN container
capacity) with one A type
overshell and LED light

Short Form Specification

Item No.

Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free. Designed to serve the food in gastronorm containers. Suitable for GN 1/1 containers with a maximum height of 200 mm. Well in 304 AISI stainless steel with rounded corners to facilitate cleaning operations. The well is also equipped with a drain hole. Automatic defrosting guarantees evaporators clearance and efficient well cooling. High-density expanded polyurethane foam with cyclopentane guarantees excellent well insulation to reduce energy dispersion. The bottom is equipped with copper tubes to ensure proper cooling, with this system the air touches the cold surface and gets cooled. Stylish A type overshell designed for extra increased visibility on the surface for charming food display. Overshell equipped with LED lights.

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____

Main Features

- CB and CE certified by a third party notified body.
- Designed to serve the food in gastronorm containers.
- Suitable for GN 1/1 containers with a maximum height of 200 mm.
- Precise temperature control and setting at 0,1°C .
- As standard the product comes with digitally controlled thermostat which is in line of HACCP norms and provides visual alarm as a warning of the increasing or decreasing temperatures.
- Food introduced at the correct temperature maintains its core temperature according to Afnor Standards.
- Automatic defrosting guarantees evaporators clearance and efficient well cooling.
- Stylish A type overshell designed for extra increased visibility on the surface for charming food display.
- Overshell equipped with LED lights.
- Designed to be positioned in flush installation providing improved cleanability and suitable for modern design installations.

Construction

- Electronic control with temperature display.
- Well bottom is inclined to facilitate water drainage.
- Well in 304 AISI stainless steel with rounded corners to facilitate cleaning operations. The well is also equipped with a drain hole.
- IPx2 water protection.
- The bottom is equipped with copper tubes to ensure proper cooling, with this system the air touches the cold surface and gets cooled.
- Overshell in complete AISI 304.

Sustainability

- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- High-density expanded polyurethane foam with cyclopentane guarantees excellent well insulation to reduce energy



APPROVAL:



Experience the Excellence
www.electroluxprofessional.com





**Drop-In
Drop-in refrigerated well, static (2 GN
container capacity) with A overshelf**


dispersion.

**Drop-In
Drop-in refrigerated well, static (2 GN container capacity) with A
overshelf**

The company reserves the right to make modifications to the products
without prior notice. All information correct at time of printing.

2026.02.13


Front

Side
EI = Electrical inlet (power)

Top

Electric
Supply voltage: 220-240 V/1N ph/50 Hz
Electrical power, max: 0.44 kW

Water:
Water drain outlet size:
Key Information:
External dimensions, Width: 770 mm
External dimensions, Depth: 620 mm
External dimensions, Height: 999 mm
Net weight: 57.06 kg
Shipping weight: 74 kg
Shipping height: 1230 mm
Shipping width: 670 mm
Shipping depth: 820 mm
Shipping volume: 0.68 m³
Set temperature: -15 / 0 °C

Refrigeration Data
Refrigerant type: R290

Sustainability
Noise level: 56 dBA

