# Electrolux PROFESSIONAL

Modular Cooking Range Line 700XP 800mm Gas Fry Top, Smooth Polished Chrome Plate



371409 (E7IIDTAOMEI)

Full module gas Fry Top with smooth polished chrome cooking Plate, sloped, thermostatic control, Q Mark

## **Short Form Specification**

#### Item No.

To be installed on open base installations or bridging supports. Smooth polished chrome cooking surface. Suitable to be used with Natural or LPG gas. Temperature range from 100°C to 280°C. Removable drawer below the cooking surface for the collection of grease and fat. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Rightangled side edges to allow flush-fitting junction between units.

#### APPROVAL:

TEM #
10DEL #
IAME #
ils #
NA #

### **Main Features**

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Large drain hole on cooking surface permits the draining of fat into large 1,5 liter collector placed under the cooking surface.
- Large grease collection container available as optional accessory to be installed under top units over open base cupboard.
- Stainless steel high splash guard on the rear and sides of cooking surface. Splash guard can be easily removed for cleaning.
- Cooking surface 12mm thick polished chrome for optimum grilling results and ease of use.
- Piezo spark ignition for added safety.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- IPx4 water protection.
- Frontal simmering zone.
- Temperature range from 100° up to 280°C.
- Polished chromium surface avoids the mixing of flavors when passing from one type of food to another.
- Suitable for countertop installation.

### Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Cooking surface completely smooth.
- Q Mark model delivered with nozzles for G30-50 mbar.

### **Included Accessories**

• 1 of Scraper for smooth plate PNC 164255 fry tops

#### **Optional Accessories**

- Scraper for smooth plate fry PNC 164255 tops
- Junction sealing kit PNC 206086 □
- Draught diverter, 150 mm PNC 206132 🗆 diameter
- Matching ring for flue PNC 206133 condenser, 150 mm diameter
  - Support for bridge type PNC 206137 installation, 800mm
- Support for bridge type PNC 206138 🗆 installation, 1000mm

Experience the Excellence www.electroluxprofessional.com



• Support for bridge type installation, 1200mm	PNC 206139			
<ul> <li>Support for bridge type installation, 1400mm</li> </ul>	PNC 206140			
<ul> <li>Support for bridge type installation, 1600mm</li> </ul>	PNC 206141			
• Flue condenser for 1 module, 150 mm diameter	PNC 206246			
<ul> <li>Pair of side kicking strips</li> </ul>	PNC 206249			
Chimney upstand, 800mm	PNC 206304			
Right and left side handrails	PNC 206307			
Back handrail 800 mm	PNC 206308			
• Grease/oil kit container for 700 line frytops (half and module) and 900 line frytops (module)	PNC 206346			
<ul> <li>Chimney grid net, 400mm (700XP/900)</li> </ul>	PNC 206400			
<ul> <li>Cloche for fry tops</li> </ul>	PNC 206455			
<ul> <li>Kit G.25.3 (NI) gas nozzles for 700 fry tops</li> </ul>	PNC 206466			
• Frontal handrail, 800mm	PNC 216047			
<ul> <li>Frontal handrail, 1200mm</li> </ul>	PNC 216049			
<ul> <li>Frontal handrail, 1600mm</li> </ul>	PNC 216050			
<ul> <li>Large handrail - portioning shelf, 800mm</li> </ul>	PNC 216186			
<ul> <li>2 side covering panels for top appliances</li> </ul>	PNC 216277			
<ul> <li>Pressure regulator for gas units</li> </ul>	PNC 927225			
Recommended Detergents				

## • C41 HI-TEMP RAPID DEGREASER, 1 PNC 0S2292 pack of six 1 lt. bottles (trigger incl.)

## Electrolux PROFESSIONAL

## Modular Cooking Range Line 700XP 800mm Gas Fry Top, Smooth Polished Chrome Plate


#### Gas

Gas Power:	14 kW
Standard gas delivery:	G30 – 50 mbar
Gas Type Option:	G31 37 mbar
Gas Inlet:	1/2"

#### Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Working Temperature MIN:	100 °C
Working Temperature MAX:	280 °C
External dimensions, Width:	800 mm
External dimensions, Depth:	730 mm
External dimensions, Height:	250 mm
Net weight:	70 kg
Shipping weight:	78 kg
Shipping height:	520 mm
Shipping width:	820 mm
Shipping depth:	860 mm
Shipping volume:	0.37 m³
Certification group:	N7RG
Cooking surface width:	730 mm
Cooking surface depth:	540 mm



Modular Cooking Range Line 700XP 800mm Gas Fry Top, Smooth Polished Chrome Plate

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.