

Modular Cooking Range Line 700XP Two Wells Freestanding Gas Fryer 15 liter

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



371421 (E7KKETBAMEI)

15+15-It gas Fryer free standing with 2 "V" shape wells (external burners), 2 baskets and lids included, Q Mark

Short Form Specification

Item No.

To be installed on height adjustable feet in stainless steel. Four high efficiency 7 kW burners in stainless steel. Suitable for natural gas or LPG. Deep drawn V-shaped well. Oil drains through a tap into a container under the well. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Rightangled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on 50mm height adjustable feet in stainless steel.
- Deep drawn V-Shaped wells.
- Four high efficiency 7 kW burners in stainless steel with flame failure device attached to the outside of
- Thermostatic regulation of oil temperature up to a maximum of 185°C.
- Flame failure device on each burner.
- Overheat protection thermostat as standard on all
- Oil drains through a tap into a drainage container positioned under the well.
- All major compartments located in front of unit for ease of maintenance.
- · Piezo spark ignition for added safety.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- IPx4 water protection.
- Optional portable oil quality monitoring tool (code 9B8081) for efficient oil management.

Construction

- Interior of well with rounded corners for ease of cleaning.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Q Mark model delivered with nozzles for G30-50 mbar.

Included Accessories

•	2 of Door for open base cupboard	PNC 206350
•	2 of 1 full size basket for 14/15lt fryers	PNC 921691

Optional Accessories		
 Junction sealing kit 	PNC 206086	
 Draught diverter, 150 mm diameter 	PNC 206132	
 Matching ring for flue condenser, 150 mm diameter 	PNC 206133	
 Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels 	PNC 206135	
 Flanged feet kit 	PNC 206136	
• Frontal kicking strip for concrete installation, 800mm	PNC 206148	
• Frontal kicking strip for concrete installation, 1000mm	PNC 206150	
• Frontal kicking strip for concrete installation, 1200mm	PNC 206151	

APPROVAL:







Modular Cooking Range Line 700XP Two Wells Freestanding Gas Fryer 15 liter

 Frontal kicking strip for concrete installation, 1600mm Frontal kicking strip, 800mm (not for refr-freezer base) Frontal kicking strip, 1000mm (not for refr-freezer base) Frontal kicking strip, 1200mm (not for refr-freezer base) Frontal kicking strip, 1200mm (not for refr-freezer base) Frontal kicking strip, 1600mm (not for refr-freezer base) Kit 4 feet for concrete installation (not for 900 line free standing grill) Sediment tray for 15lt fryers Flue condenser for 1 module, 150 mm diameter Pair of side kicking strips Pair of side kicking strips for concrete installation Oil drain pipe for 15lt free standing fryer PNC 206301
 Frontal kicking strip, 800mm (not for refr-freezer base) Frontal kicking strip, 1000mm (not for refr-freezer base) Frontal kicking strip, 1200mm (not for refr-freezer base) Frontal kicking strip, 1200mm (not for refr-freezer base) Frontal kicking strip, 1600mm (not for refr-freezer base) Kit 4 feet for concrete installation (not for 900 line free standing grill) Sediment tray for 15lt fryers Flue condenser for 1 module, 150 mm diameter Pair of side kicking strips PNC 206249 Pair of side kicking strips for concrete installation
 Frontal kicking strip, 1000mm (not for refr-freezer base) Frontal kicking strip, 1200mm (not for refr-freezer base) Frontal kicking strip, 1600mm (not for refr-freezer base) Kit 4 feet for concrete installation (not for 900 line free standing grill) Sediment tray for 15lt fryers Flue condenser for 1 module, 150 mm diameter Pair of side kicking strips PNC 206249 Pair of side kicking strips for concrete installation
 Frontal kicking strip, 1200mm (not for refr-freezer base) Frontal kicking strip, 1600mm (not for refr-freezer base) Kit 4 feet for concrete installation (not for 900 line free standing grill) Sediment tray for 15lt fryers Flue condenser for 1 module, 150 mm diameter Pair of side kicking strips PNC 206249 PNC 206245
 Frontal kicking strip, 1600mm (not for refr-freezer base) Kit 4 feet for concrete installation (not for 900 line free standing grill) Sediment tray for 15lt fryers Flue condenser for 1 module, 150 mm diameter Pair of side kicking strips PNC 206249 PNC 206245 PNC 206245
 Kit 4 feet for concrete installation (not for 900 line free standing grill) Sediment tray for 15lt fryers Flue condenser for 1 module, 150 mm diameter Pair of side kicking strips Pair of side kicking strips for concrete installation
 Sediment tray for 15lt fryers Plue condenser for 1 module, 150 mm diameter Pair of side kicking strips Pair of side kicking strips for concrete installation PNC 206246 PNC 206249 PNC 206265 □
 Flue condenser for 1 module, 150 mm diameter Pair of side kicking strips Pair of side kicking strips for concrete installation PNC 206246 PNC 206249 PNC 206265 □
 Pair of side kicking strips Pair of side kicking strips for concrete installation PNC 206249 PNC 206265
 Pair of side kicking strips for concrete PNC 206265 ☐ installation
• Oil drain pipe for 15lt free standing fryer PNC 206301
• Chimney upstand, 800mm PNC 206304
• Right and left side handrails PNC 206307
Back handrail 800 mm PNC 206308
• Door for open base cupboard PNC 206350 📮
Base support for feet or wheels - PNC 206367 □ 800mm (700/900)
Base support for feet or wheels - PNC 206368 ☐ 1200mm (700/900)
Base support for feet or wheels - PNC 206369 ☐ 1600mm (700/900)
Base support for feet or wheels - PNC 206370 □ 2000mm (700/900)
• Rear paneling - 800mm (700/900) PNC 206374
• Rear paneling - 1000mm (700/900) PNC 206375
• Rear paneling - 1200mm (700/900) PNC 206376
• Chimney grid net, 400mm (700XP/900) PNC 206400
 Kit G.25.3 (NI) gas nozzles for 900 PNC 206467 Pryers
• 2 side covering panels for free standing PNC 216000 appliances
• 1 full size basket for 14/15lt fryers PNC 921691
• 2 half size baskets for 14/15lt fryers PNC 921692 \Box
• Filter for fryer oil collection basin for 7lt, PNC 921693 14lt, 15lt free standing fryers
 Unclogging rod for 15lt fryers drainage PNC 921695 pipe
 Deflector for floured products for 15lt PNC 921696 pryers
• Pressure regulator for gas units PNC 927225 \Box



Modular Cooking Range Line 700XP Two Wells Freestanding Gas Fryer 15 liter





Equipotential screw Gas connection

> Top 31 1/2 28 3/4 " 730 mm 0 3/16 "

Gas

Gas Power: 28 kW

Standard gas delivery: G30 - 50 mbar Gas Type Option: G31 37 mbar

Working pressure, mBar (min/Max): 0/0 Gas Inlet: 1/2"

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Usable well dimensions

(width): 240 mm

Usable well dimensions

(height): 505 mm

Usable well dimensions

380 mm (depth):

Well capacity: 13 It MIN; 15 It MAX Thermostat Range: 105 °C MIN; 185 °C MAX

Net weight: 85 kg 97 kg Shipping weight: Shipping height: 1130 mm Shipping width: 820 mm Shipping depth: 860 mm Shipping volume: 0.8 m³ Certification group: N7FG

Modular Cooking Range Line 700XP Two Wells Freestanding Gas Fryer 15 liter