



Electrolux
PROFESSIONAL

Modular Cooking Range Line 900XP One Well Programmable Gas Fryer 23 liter, HP

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



391343 (E9KKLBAMCG)

23-It gas Fryer with 1 "V" shaped well (external heating elements), electronic control, programmable, oil recirculation pump, 2 half size baskets and lid included, automatic lifting system for baskets, automatic cooking function, prearranged for advanced filtering system

391379 (E9KKLQBAMCG)

23-It gas Fryer with 1 "V" shaped well (external heating elements), electronic control, programmable, oil recirculation pump, 2 half size baskets and lid included, automatic lifting system for baskets, automatic cooking function, prearranged for advanced filtering system

Short Form Specification

Item No. _____

Burners in stainless steel. Suitable for natural gas or LPG attached to the outside of the well. Deep drawn V-Shaped well. The unit is equipped with a programmable electronic control panel. Automatic basket lifting system with automatic cooking mode. Unit predisposed for advanced filtering system. Melting function. Oil drains through a tap into a container positioned under the well; stainless steel filter included.

Height adjustable feet in stainless steel. Exterior panels in stainless steel. Worktop in 20/10, stainless steel. Right-angled side edges eliminate gaps and possible dirt traps between units.

Main Features

- High efficiency 26 kW burners in stainless steel with flame failure device attached to the outside of the well.
- Thermostatic regulation of oil temperature up to a maximum of 190 °C.
- Built-in smart electronic control system to monitor the temperature during frying to guarantee the safety of the process.
- The unit is predisposed for ADVANCED FILTERING SYSTEM with paper filters to remove the smallest food residuals and extend the oil life.
- Unit to feature automatic basket lifting system and AUTOMATIC COOKING mode - Patented (EP3125644B1 and related family).
- Unit able to memorize 5 programs (temperature and time) and 5 extra programs can be customized using the automatic cooking mode allowing to adjust the cooking time automatically according to the load.
- The special design of the control panel offers a better guarantee against oil infiltration.
- Flame failure device.
- Supplied as standard with 2 half size baskets and 1 right side door for cupboard and stainless steel sediment filter.
- Deep drawn V-Shaped well.
- Overheat protection thermostat as standard on all units.
- Integrated oil filtering system with a pump for oil circulation.
- All major compartments located in front of unit for ease of maintenance.
- Optional portable oil quality monitoring tool (code 9B8081) for efficient oil management.

Construction

- Interior of well with rounded corners for ease of cleaning.
- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Unit delivered with four 50 mm legs in stainless steel as standard.

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com

Included Accessories

- 1 of Stainless steel oil filter for 18/23-litre fryer to remove particles of grease and food residuals) - 900XP PNC 200086
- 1 of Door for open base cupboard PNC 206350
- 1 of 2 half size baskets for 18/23 lt fryers PNC 927223

Optional Accessories


- | | | |
|---|------------|--------------------------|
| • Kit for advanced filtration system for 23-litre fryer, allowing to remove the smallest food residuals and extend oil life - 900XP | PNC 200084 | ☐ |
| • Pack of paper filter (100 pieces) for advanced filtration system for 23-litre fryer - 900XP | PNC 200085 | ☐ |
| • Stainless steel oil filter for 18/23-litre fryer to remove particles of grease and food residuals) - 900XP | PNC 200086 | ☐ |
| • Kit for 23-litre fryer, drain extension in high resistant elastomer with stainless steel extremities to drain oil - 900XP | PNC 200087 | ☐ |
| • Junction sealing kit | PNC 206086 | ☐ |
| • Draught diverter, 120 mm diameter | PNC 206126 | ☐ |
| • Matching ring for flue condenser, 120 mm diameter | PNC 206127 | ☐ |
| • Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels | PNC 206135 | ☐ |
| • Flanged feet kit | PNC 206136 | ☐ |
| • Support for bridge type installation, 1000mm (only for 391379) | PNC 206138 | ☐ |
| • Pair of side kicking strips (not for refr-freezer base) | PNC 206180 | ☐ |
| • Frontal kicking strip for 23lt fryers in two parts | PNC 206203 | ☐ |
| • Extension pipe for oil drainage for fryers | PNC 206209 | ☐ |
| • Flue condenser for 1/2 module, 120 mm diameter | PNC 206310 | ☐ |
| • 2 drawers for open base cupboards, 100mm height (only for 391343) | PNC 206334 | ☐ |
| • Door for open base cupboard | PNC 206350 | ☐ |
| • Base support for feet or wheels (lateral) for 23lt fryers, pasta cookers and refrigerated bases (900XP) | PNC 206372 | ☐ |
| • Kit G.25.3 (NI) gas nozzles for 900 fryers (only for 391343) | PNC 206467 | ☐ |
| • 2 side covering panels for free standing appliances | PNC 216134 | ☐ |
| • Sediment collection tray for 23-litre fryer (to be put in the well) | PNC 921023 | ☐ |
| • 2 half size baskets for 18/23 lt fryers | PNC 927223 | ☐ |
| • Pressure regulator for gas units | PNC 927225 | ☐ |
| • 1 full size basket for 18/23 lt fryers | PNC 927226 | ☐ |
| • Unclogging rod for 23lt fryers drainage pipe | PNC 927227 | ☐ |
| • Deflector for floured products for 23lt fryers | PNC 960645 | ☐ |




Electrolux
PROFESSIONAL

Modular Cooking Range Line 900XP One Well Programmable Gas Fryer 23 liter, HP

Front




Side



EI = Electrical inlet (power)
EQ = Equipotential screw
G = Gas connection

Top



Electric

Frequency:

391343 (E9KKLBAMCG) 50Hz

391379 (E9KKLQBAMCG) 60Hz

Gas

Gas Power: 26 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG; Natural Gas

Gas Inlet: 1/2"

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Usable well dimensions (width):

340 mm

Usable well dimensions (height):

575 mm

Usable well dimensions (depth):

400 mm

Well capacity:

21 lt MIN; 23 lt MAX

Performance*:

36.5 kg/hr

Thermostat Range:

110 °C MIN; 190 °C MAX

Net weight:

96 kg

Shipping weight:

111 kg

Shipping height:

1480 mm

Shipping width:

460 mm

Shipping depth:

1020 mm

Shipping volume:

0.69 m³

*Based on:

ASTM F1361-Deep fat fryers

Certification group:

GF91L23



Modular Cooking Range Line
900XP One Well Programmable Gas Fryer 23 liter, HP

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.09.08