



Modular Cooking Range Line 900XP Gas Pasta Cooker, 1 Well, 40 litres

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



391624 (E90OCTBAMCI)

40-lt gas Pasta Cooker with
1 well, Q Mark

Short Form Specification

Item No.

High efficiency 16.5 kW burners. Suitable for natural gas or LPG. Constant starch removal during the cooking process. The 40 liter tank is pressed in 316-L type stainless steel to protect against corrosion. Control panel with gas cock and piezo ignition. Safety thermostat prevents the machine from working without water. Height adjustable feet in stainless steel. Exterior panels in stainless steel. Worktop in 20/10, stainless steel. Right angled side edges eliminate gaps and possible dirt traps between units.

Main Features

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- High efficiency 16.5 kW burners in stainless steel with flame failure device and power settings for each well, located below the well.
- Water basin in 316-L type Stainless steel.
- Water basin is seamlessly welded into the top of the appliance.
- Provided with integrated drip zone on which baskets can be placed for draining purposes.
- 40 liters water basin.
- Automatic starch removal function during cooking: improved water quality over time.
- Automatic low-water level shut-off: no accidental over-heating.
- Easy-to-use control panel with gas cock and piezo ignition.
- All major compartments located in front of unit for ease of maintenance.
- Continuous water filling regulated through a manual water tap.
- Large drain with manual ball-valve for fast emptying of well.
- Thermocouple device for added safety.
- Automatic lifting system (optional accessory): 200mm wide unit with three stainless steel basket supports, holding one GN 1/3 basket each, to be placed on either or both sides of machine to provide automatic lifting for six small portion baskets (to be ordered separately). Possibility to memorize nine cooking times through digital control.
- The special design of the control knob system guarantees against water infiltration.
- One piece pressed 2 mm work top in Stainless steel.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Q Mark model delivered with nozzles for G30-50 mbar.
- IPX5 water resistance certification.

Sustainability



- ESD available as accessory (installed separately): energy saving device uses heat produced by water drained through the overflow to pre-heat tap-in water up to 60°C, for constant water boiling.
- EnergyControl: unique feature for fine power adjustment to control boiling level and optimize energy consumption.

Included Accessories


APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com



Front



Technical drawing of the front elevation of a cabinet. The drawing includes the following dimensions:

- Overall width: $30\frac{3}{4}"$ (780 mm)
- Overall height: $27\frac{5}{8}"$ (707 mm)
- Left side panel height: $11\frac{7}{8}"$ (301 mm)
- Distance from left edge to first drawer center: $2\frac{3}{4}"$ (71 mm)
- Distance from left edge to second drawer center: $4\frac{15}{16}"$ (126 mm)
- Distance between drawer centers: $26\frac{1}{2}"$ (674 mm)
- Distance from second drawer center to right edge: $3\frac{15}{16}"$ (100 mm)
- Distance from second drawer center to right edge (alternative): $6\frac{7}{8}"$ (175 mm)
- Distance from second drawer center to right edge (alternative): $1"$ (26 mm)
- Distance from second drawer center to right edge (alternative): $5\frac{7}{8}"$ (149 mm)
- Distance from second drawer center to right edge (alternative): $27\frac{5}{8}"$ (707 mm)
- Label 'F' is located in the top left corner.
- Label 'EQ' is located in the bottom center.

- D = Drain
EQ = Equipotential screw
G = Gas connection
WI = Water inlet

Gas Power:	16.5 kW
Standard gas delivery:	G30 – 50 mbar
Gas Type Option:	G31 37 mbar
Gas Inlet:	1/2"

Total hardness:	5-50 ppm
Drain "D":	1"
Incoming Cold/hot Water line size:	3/4"

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions. Please refer to user manual for detailed water quality information.

Usable well dimensions (width):	300 mm
Usable well dimensions (height):	260 mm
Usable well dimensions (depth):	520 mm
Well Capacity (MAX):	40 lt MAX
Net weight:	62 kg
Shipping weight:	57 kg
Shipping height:	1080 mm
Shipping width:	460 mm
Shipping depth:	1020 mm
Shipping volume:	0.51 m ³
Certification group:	N9ECPG

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.