

Modular Preparation 400 mm Ambient Unit with 1 Door & GN 1/1 Runners



such as the control of the strengthener structure. Door incorporates a sound deadening reinforcements to strengthen structure. Door incorporates a sound deadening internal panel and is fitted with 304 AISI stainless steel hinges allowing an opening of 180° degrees. 150mm heightadjustable (0/+90mm) oversized feet (65x65mm) can be removed for masonry installation. 45° degree internal side corner junction system. 304 AISI stainless steel quide runners GN 1/1.

| ITEM # | | |
|---------|------|------|
| MODEL # | | |
| NAME # | | |
| SIS # | | |
| AIA # | | |
| | | |

Main Features

- Masonry installation possible by simply removing feet.
- Extremely easy to clean thanks to the smooth edges.

Construction

- Made in 304 AISI CrNi 18/10 stainless steel with Scotch Brite finish.
- Front and rear lengthwise stainless steel c-channel reinforcement, 15/10 (16 gauges).
- Internal sides supporting the structure to have 45° degrees internal side corners junction system.
- 30 mm high middle-shelf in AISI 304 stainless steel, height-adjustable in 3 positions, with inner double fold to eliminate gaps between sides and back.
- Sound deadening reinforcements between internal and external side panels to strengthen structure.
- Mounted on 150 mm height adjustable (0/+90 mm) oversized (65x65 mm) feet.
- Hinged door with sound deadening internal panels, fitted with 304 AISI stainless steel hinges on the inner sides, allows a 180° degree opening.

APPROVAL:

Electrolux PROFESSIONAL

Modular Preparation 400 mm Ambient Unit with 1 Door & GN 1/1 Runners



Modular Preparation 400 mm Ambient Unit with 1 Door & GN 1/1 Runners

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.