# Electrolux

MODEL #		
NAME #		
SIS #		





## Sustainability

- 304 AISI stainless steel front panel, load bearing frame, wash tank, wash and rinse arms.
- Simple operation control panel.
- Insulated double skin door construction preserves heat inside the tank to lower energy consumption and the noise. Counter-balance mechanism minimizes impact when opening and closing.

APPROVAL:

electric cable.

washing spray arms from both bottom and top. Rinse temperature

and pressure guaranteed by built in pressure boiler. The cold rinse

cycle provides hygiene glasses and cold enough to handle. Double

skinned counter-balance door. Large door opening of 290mm for

washing tall glasses. Double skinmed cabinet. Pressed tank with round

corners, 304 stainless steel construction to include door, frame, wash



- Deep drawn pressed wash tank with fully rounded corners, sloped towards the drain to prevent dirt build up provides fast drainage in only a few minutes. Pressed wash tank with no welded points offer a guaranteed water tight solution.
- Built-in pressure boiler designed to raise incoming water to a guaranteed minimum temperature of 82 C for sanitizing rinse. No external boiler is required.
- Maximum capacity of 30 racks per hour.
- Washing system endowed with rotating washing arms from both top and bottom, high powered wash pump and large capacity wash tank guarantee professional washing.
- Easy service access to main components without
- Equipped with drain pump for easy and quick installation without opening the machine.
- Built-in rinse aid dispenser with automatic initial and continuous cycle loading for perfect result while minimizing service and maintenance needs.
- Extra program to cold rinse beer and wine glasses providing sanitized glasses, cool enough to
- Equipped with single phase electric cable for easy and fast installation.
- Built in rinse booster pump allows to connect to
- Completely closed on the back by a cover plate.
- Wash/rinse arms and nozzles in stainless steel.
- Finished in top quality stainless steel with double skinned construction to aid durability and reduce

tank, wash arms and rinse arms. The unit shall include rinse booster pump, drain pump and rinse aid dispenser pump and is equipped with



Included Accessories	
<ul> <li>1 of Square basket for glasses 400x400x150mm</li> </ul>	PNC 864470
<ul> <li>2 of Insert for 12 saucers, 290X90x75mm</li> </ul>	PNC 867048
Optional Accessories	
Filter for partial demineralization	PNC 864017
<ul> <li>Kit to measure total and partial water hardness</li> </ul>	PNC 864050
<ul> <li>Yellow cutlery container</li> </ul>	PNC 864242
<ul> <li>Filter for total demineralization</li> </ul>	PNC 864367
<ul> <li>Pressure reducer for single tank dishwasher</li> </ul>	PNC 864461
<ul> <li>Kit 4 plastic boxes for cutlery - yellow</li> </ul>	PNC 865574
<ul> <li>Cover rack for small and light items (500x500 baskets)</li> </ul>	PNC 867016
<ul> <li>Basket for glasses (395x395x115)</li> </ul>	PNC 867033
<ul> <li>Basket for 16 plates diam.190 mm, 8 plates diam. 240 mm</li> </ul>	PNC 867052
<ul> <li>Basket for glasses (h 100 mm)</li> </ul>	PNC 867053
<ul> <li>Basket for glasses (h 200 mm)</li> </ul>	PNC 867054
<ul> <li>Basket for glasses and saucers/ cutlery inserts</li> </ul>	PNC 867055
Basket for glasses with angled base	PNC 867056
<ul> <li>Round basket kit with square frame</li> </ul>	PNC 867057
<ul> <li>Insert for "flute" glasses</li> </ul>	PNC 867058
<ul> <li>Insert for 14 saucers</li> </ul>	PNC 867060

• Inclined insert for cups

• Insert for 7 plates d. 240mm

PNC 867061

PNC 867062

# **Electrolux**

Warewashing Small Double Skin Glasswasher, 1 cycle, rinse booster, drain pump and rinse aid dispenser, 60b/h



### Electric Supply voltage: 220-230 V/1 ph/60 Hz **Default Installed Power:** 3.3 kW **Boiler heating elements:** 3 kW Tank heating elements: 0,8 kW 0.3 kW Wash pump size: Water: Pressure, min-max: 1-3 bar Water supply temperature\*: 15-60 °C Drain line size: 27mm Washing tank capacity (It): 6 Water consumption per cycle (It): 0/2.3 Boiler Capacity (It): 5 Incoming water line size: G 3/4" Key Information: Wash temperature: 55-65°C

wash temperatore.	55 65 C
Cell dimensions - width:	400 mm
Cell dimensions - depth:	400 mm
Cell dimensions - height:	290 mm
Rinse temperature:	80-90 °C
External dimensions, Width:	460 mm
External dimensions, Depth:	565 mm
External dimensions, Height:	715 mm
Net weight:	41.7 kg
Shipping weight:	46 kg
Shipping height:	900 mm
Shipping width:	520 mm
Shipping depth:	640 mm
Shipping volume:	0.3 m³
Productivity, baskets/h:	60
Productivity, dishes/h:	1680
Working cycle, sec:	60
Suchainghiliby	

## **Sustainability**

Noise level:

61 dBA



Warewashing Small Double Skin Glasswasher, 1 cycle, rinse booster, drain pump and rinse aid dispenser, 60b/h The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.